

# Package ‘IBrokers’

February 19, 2015

**Type** Package

**Title** R API to Interactive Brokers Trader Workstation

**Version** 0.9-12

**Date** 2014-09-22

**Depends** xts, zoo

**Author** Jeffrey A. Ryan

**Maintainer** Joshua M. Ulrich <josh.m.ulrich@gmail.com>

**Description** Provides native R access to Interactive Brokers Trader Workstation API.

**License** GPL-3

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2014-09-22 07:59:21

## R topics documented:

IBrokers-package . . . . .	2
.placeOrder . . . . .	4
.twIncomingMSG . . . . .	5
calculateImpliedVolatility . . . . .	5
eWrapper . . . . .	6
exerciseOptions . . . . .	8
processMsg . . . . .	10
reqAccountUpdates . . . . .	11
reqContractDetails . . . . .	12
reqCurrentTime . . . . .	14
reqHistoricalData . . . . .	15
reqIds . . . . .	17
reqMktData . . . . .	18
reqMktDepth . . . . .	20
reqNewsBulletins . . . . .	22
reqRealTimeBars . . . . .	23
setServerLogLevel . . . . .	25

twsCALLBACK . . . . .	26
twsConnect . . . . .	27
twsConnectionTime . . . . .	28
twsContract . . . . .	29
twsCurrency . . . . .	31
twsEquity . . . . .	32
twsFuture . . . . .	34
twsOption . . . . .	35
twsOrder . . . . .	37
twsScannerSubscription . . . . .	41

<b>Index</b>	<b>44</b>
--------------	-----------

---

IBrokers-package	<i>R API to the Interactive Brokers Trader Workstation (TWS).</i>
------------------	-------------------------------------------------------------------

---

## Description

*This software is in no way affiliated, endorsed, or approved by Interactive Brokers or any of its affiliates. It comes with absolutely no warranty and should not be used in actual trading unless the user can read and understand the source.*

**IBrokers** is a pure R implementation of the TWS API. At present it is only able pull data from the Interactive Brokers servers via the TWS. Future additions will include more API access, including live order handling, and better management across R sessions.

Possible real-time charting via the **quantmod** package may be incorporated into future releases.

Changes to move to version 0.1-0 have made this API implementation much more robust on all platforms. Many new error-checking calls have been incorporated, as well as a more reliable event-loop to capture the data from the TWS.

The underlying socket connections are pure R. This was a design decision to maximize cross-platform availability, as well as a recognition that historical data requests, or any requests while in a single threaded R session, must be non-threaded.

Recent additions include `reqMktData` to handle live market data from one or more symbols, `reqMktDepth` to capture market depth for one or more symbols, and `reqRealTimeBars` to receive 5 second real time bars. Each of these functions have been implemented with optional user defined callback handlers to allow for R code to interact with the API while receiving data from the TWS.

Please report any and all bugs/experiences to the maintainer so they can be corrected or incorporated into future versions.

Additionally, beta testers are needed to make this a viable alternative for IB-API interaction. Don't be shy.

## Details

Package: IBrokers  
 Type: Package  
 Version: 0.9-7

Date: 2012-04-27  
License: GPL-3

The current API methods supported are:

twsConnect: Establish TWS connection  
twsDisconnect: Close TWS connection  
isConnected: Check connection  
setServerLogLevel: Set logging level

twsAccountUpdates: Get Account Details  
reqIds: Request next available ID  
reqCurrentTime: The TWS server time in seconds since the epoch  
reqHistoricalData: Fetch historical data  
reqMktData: Receive real-time market data  
reqMktDepth: Receive real-time order book depth  
reqRealTimeBars: Receive 5 second OHLCVWC bar data

*Experimental support:*

placeOrder: Place a live order to the TWS  
cancelOrder: Cancel a pending order on the TWS

### Author(s)

Jeffrey A. Ryan

Maintainer: Joshua M. Ulrich <josh.m.ulrich@gmail.com>

### References

Interactive Brokers: [www.interactivebrokers.com](http://www.interactivebrokers.com)

### Examples

```
## Not run:  
IBrokersRef()      # IBrokers Reference Card in PDF viewer  
  
tws <- twsConnect() # make a new connection to the TWS  
reqCurrentTime(tws) # check the server's timestamp  
  
contract <- twsEquity('IBKR', 'SMART', 'ISLAND') # equity specification  
  
reqHistoricalData(tws, contract) # request historical data  
twsDisconnect(tws) # disconnect from the TWS  
  
## End(Not run)
```

---

<code>.placeOrder</code>	<i>TWS Orders</i>
--------------------------	-------------------

---

**Description**

Place or cancel an order to the TWS.

**Usage**

```
placeOrder(twsconn, Contract, Order)
```

```
cancelOrder(twsconn, orderId)
```

**Arguments**

<code>twsconn</code>	A <code>twsConnection</code> object.
<code>Contract</code>	A <code>twsContract</code> object.
<code>Order</code>	A <code>twsOrder</code> object.
<code>orderId</code>	A valid order id.

**Details**

As described by the official Interactive Brokers (tm) documentation. Caveat Emptor!!

**Value**

Called for its side effect of placing or cancelling an order on the TWS. This also returns the `orderId` used for `placeOrder`. An additional side-effect is that a variable `.Last.orderId` will be created or updated in the `GlobalEnv` as well.

**Note**

Orders via the API are quite complicated, or at least can be. It is strongly advised to only proceed with trading real money after one understands not only all the R code in this package, but the official API as well. If you are more comfortable clicking shiny buttons in a GUI, it is probably better that you keep clicking the buttons and not pretend to program.

Not for the faint of heart. All profits and losses related are yours and yours alone. If you don't like it, write it yourself.

**Author(s)**

Jeffrey A. Ryan

**References**

Official Place Order API: <http://www.interactivebrokers.com/php/apiUsersGuide/apiguide/java/placeorder.htm>

### See Also

[twsContract twsOrder reqIds](#)

### Examples

```
## Not run:
tws <- twsConnect()
id <- reqIds(tws)

placeOrder(tws, twsSTK("AAPL"), twsOrder(id))
cancelOrder(id)

## End(Not run)
```

---

.twsIncomingMSG

*Internal TWS-API MSG and ERR List*

---

### Description

Internal List of MSG Codes and Undocumented (Experimental) Functions

---

calculateImpliedVolatility

*Calculate Option Values*

---

### Description

Using the IB API, calculates the implied volatility or option price given parameters.

### Usage

```
calculateImpliedVolatility(twsconn,
                           Contract,
                           optionPrice,
                           underPrice,
                           reqId = 1)
```

```
calculateOptionPrice(twsconn,
                     Contract,
                     volatility,
                     underPrice,
                     reqId = 1)
```

**Arguments**

twscconn	A twsConnection object
Contract	A twsContract object
optionPrice	The option price from which to calculate implied
volatility	The volatility from which to calculate price
underPrice	The underlying price
reqId	The request id

**Details**

Both calls will use the IB described method for calculation. See the official API for documentation.

**Value**

A numeric value corresponding to the request

**Author(s)**

Jeffrey A. Ryan

**References**

<http://www.interactivebrokers.com/php/apiUsersGuide/apiguide/java/calculateimpliedvolatility.htm>  
<http://www.interactivebrokers.com/php/apiUsersGuide/apiguide/java/calculateoptionprice.htm>

---

eWrapper

*eWrapper Closure For Message Processing*

---

**Description**

Create an eWrapper closure to allow for custom incoming message management.

**Usage**

```
eWrapper(debug = FALSE, errfile=stderr())
```

```
eWrapper.data(n)
```

```
eWrapper.MktData.CSV(n=1)
```

```
eWrapper.RealTimeBars.CSV(n=1)
```

**Arguments**

debug	should debugging be enabled
errfile	where error messages are directed (stderr)
n	number of contracts being watched

## Details

**IBrokers** implements an eWrapper scheme similar to that provided by the official Java API.

The general idea is that each real-time data capture function must manage all incoming signals correctly, while allowing for the end user to create custom handlers for each specific event.

Internal to the `reqRealTimeBars`, `reqMktData`, and `reqMktDepth` functions is a single call to the `CALLBACK` routine passed to it. By default this is `twscallback` (see also). A standard argument to this callback is an `eventWrapper` — which is an instance of `eWrapper`.

`eWrapper` is an R closure that contains a list of functions to manage all incoming message type, as found in `.twscallbackIncomingMSG`. Each message has a corresponding function in the `eWrapper` designed to handle the particular details of each incoming message type.

There is also an embedded environment in which data can be saved and retrieved via a handful of accessor functions mimicking the standard R tools.

The data environment is `.Data`, with accessor methods `get.Data`, `assign.Data`, and `remove.Data`.

These methods can be called from the closure object `eWrapper$get.Data`, `eWrapper$assign.Data`, etc.

The basic `eWrapper` call simply produces a visually informative display of the incoming stream. E.g. `bidSize` data would be represented with a *bidSize* label, instead of the internal TWS code(s) returned by the TWS.

By creating an instance of an `eWrapper`, accomplished by calling it as a function call, one can then modify any or all the particular methods embedded in the object.

This allows for rapid customization, as well as a built in assurance that all incoming messages will be handled appropriately without additional programmer time and resources.

An example of this ability to modify the object is given in the `eWrapper.MktData.CSV` code. This object produces output designed to be space efficient, as well as easily read back into any R session as a standard CSV file.

Setting `debug=NULL` will cause empty function objects to be created within the `eWrapper` object returned. This object can be treated as a template to implement only the methods that are needed. By default, all functions silently return the entire message they would normally parse. This includes *empty* functions created by setting `debug` to `NULL`.

`eWrapper.data()` allows for data states to be maintained from call to call, as an `xts` history of updates/messages is stored within the object. This is designed to minimize calling overhead by removing unneeded function calls from each message parsed.

Additional, but creating methods that update the internal environment of the `eWrapper` object, it is possible to maintain a snapshot of last `k` values for any field of interest. This is directly applicable to implementing an automated strategy from within a custom `twscallback` method.

## Value

A list of functions [and optionally data] to be used for the `eventWrapper` argument to `reqMktData` and `reqMktDepth`

**Note**

It is possible to also attach data to the closure object, allowing for a single in-memory object to contain current top of book data. This is exemplified in the `eWrapper.MktData.CSV` code, and can be extended in the user's own direction.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[twSCALLBACK](#), [processMsg](#)

**Examples**

```
myWrapper <- eWrapper()

str(myWrapper)

# remove tickPrice action
myWrapper$tickPrice <- function(msg, timestamp, file, ...) {}

# add new tickPrice action
myWrapper$tickPrice <- function(msg, timestamp, file, ...) { cat("tickPrice",msg) }

# add new data into the object, and retrieve
myWrapper$assign.Data("myData", 1010)
myWrapper$get.Data("myData")

## Not run:
twS <- twSConnect()
reqMktData(twS, twSSTK("SBUX"))
reqMktData(twS, twSSTK("SBUX"), eventWrapper=myWrapper)
twSDisconnect(twS)

## End(Not run)
```

---

exerciseOptions

*Exercise Options Contracts*

---

**Description**

Send message to exercise option contracts.



**Usage**

```
exerciseOptions(twsconn,  
                contract,  
                exerciseAction = 1,  
                exerciseQuantity = 1,  
                account = "",  
                override = 0,  
                tickerId = 1)
```

**Arguments**

twsconn	A twsConnection object
contract	A twsContract object
exerciseAction	exercise=1 or lapse=2
exerciseQuantity	number of contracts to exercise
account	IB account [institutional orders]
override	override system's natural action. 0 for do not override, 1 for override
tickerId	id for request

**Details**

Exercise option contract.

**Value**

Called for its side-effect.

**Note**

exch='SMART' is not valid in exerciseOptions calls. See the official API for further details.

**Author(s)**

Jeffrey A. Ryan

**References**

<http://www.interactivebrokers.com/php/apiUsersGuide/apiguide/java/exerciseoptions.htm>

---

 processMsg

*Main TWS-API Event Manager*


---

### Description

Function to manage all incoming messages from the TWS in a consistent manner.

This is used within the context of an event loop (often twsCALLBACK) and allows for custom processing by message type via the eWrapper argument.

### Usage

```
processMsg(curMsg, con, eWrapper, timestamp, file, twsconn, ...)
```

### Arguments

curMsg	The current incoming message
con	a socket connection from a twsConnection
eWrapper	a functional closure with methods for each message
timestamp	the timestamp format needed
file	the file or connection to write to
twsconn	the twsConnection object
...	additional arguments to internal calls

### Details

This is used internally within the context of a larger infinite listener/loop.

The basic process involves one or more requests to the TWS for data/action, followed by a call to twsCALLBACK. Inside of the CALLBACK is a loop that fetches the incoming message type, and calls processMsg at each new message.

processMsg internally is a series of if-else statements that branch according to a known incoming message type. The eWrapper object is a closure containing a data environment that is static and a collection of callback functions for each type of incoming data.

This eWrapper function can be defined at multiple points prior to the use within processMsg, to allow for access to data outside of the processMsg call, as well as facilitate custom handling in an efficient manner.

### Value

Called for its side-effects.

### Note

The entire mechanism (twsCALLBACK -> processMsg -> eWrapper) is modeled after the official API.

**Author(s)**

Jeffrey A. Ryan

**References**

Interactive Brokers: <http://www.interactivebrokers.com>

**See Also**

[twsCALLBACK](#), [eWrapper](#)

---

reqAccountUpdates	<i>Request Account Updates</i>
-------------------	--------------------------------

---

**Description**

Request and view account details from Interactive Brokers

**Usage**

```
reqAccountUpdates(conn,
    subscribe = TRUE,
    acctCode = "1",
    eventWrapper = eWrapper(),
    CALLBACK=twsCALLBACK,
    ...)

.reqAccountUpdates(conn, subscribe = TRUE, acctCode = "1")

twsPortfolioValue(x, zero.pos=TRUE, ...)
```

**Arguments**

conn	A twsConnection object
subscribe	subscribe (TRUE) or unsubscribe (FALSE)
acctCode	an account description - not used for most accounts
eventWrapper	message-level callback closure
CALLBACK	main receiver loop, if any
x	object to extract PortfolioValue from. See details.
zero.pos	should PortfolioValue include zero positions?
...	additional args

**Details**

By default, for non-FA accounts, this returns the current login's account information.

This main version returns a list of objects as returned by the TWS. `.reqAccountUpdates` sends the request to subscribe or cancel, but returns immediately. This is designed to be used within a larger custom callback routine, where the `eventWrapper` object passed to `processMsg` (see also) keeps trace of the portfolio updates in a consistent manner.

`twPortfolioValue` extracts into a `data.frame` commonly used fields from all positions held. There are currently methods for the the default returned object of `reqAccountUpdates`.

**Author(s)**

Jeffrey A. Ryan

**References**

Interactive Brokers API: <http://www.interactivebrokers.com>

**Examples**

```
## Not run:
tw <- twConnect()

reqAccountUpdates(tw)      # this will return a AccountUpdate object
.reqAccountUpdates(tw)    # this will return immediately

.reqAccountUpdates(tw, FALSE) # cancel the request
cancelAccountUpdates(tw)    # the same

twDisconnect(tw)

## End(Not run)
```

---

reqContractDetails      *Request Contract Details From TWS*

---

**Description**

Returns an object (a list of class `twContractDetails` objects) of IB contract details relating to a particular IB tradeable product.

**Usage**

```
reqContractDetails(conn,
                    Contract,
                    reqId = "1",
                    verbose = FALSE,
                    eventWrapper = eWrapper(),
                    CALLBACK = twSCALLBACK, ...)
```

**Arguments**

conn	a valid twsConnection
Contract	a valid twsContract
reqId	a unique ID
verbose	be verbose?
eventWrapper	event callback closure
CALLBACK	main callback loop
...	be verbose?

**Details**

Returns a list of details for the product specified. See the TWS API for specifics at this point.

**Value**

A twsContractDetails object, or list of the same.

**Author(s)**

Jeffrey A. Ryan

**References**

Interactive Brokers <http://www.interactivebrokers.com>

**See Also**

[twsContract](#)

**Examples**

```
## Not run:
tws <- twsConnect()
reqContractDetails(tws, twsEquity("QQQQ"))

# retrieve all QQQQ contracts as a list
reqContractDetails(tws, twsOption(local="", right="", symbol="QQQQ"))
# retrieve only calls
reqContractDetails(tws, twsOption(local="", right="C", symbol="QQQQ"))
# retrieve only puts
reqContractDetails(tws, twsOption(local="", right="P", symbol="QQQQ"))

opt.details <- lapply(c("MSFT", "AAPL"),
  function(x) {
    reqContractDetails(tws,
      twsOption(local="", right="",
        symbol=x))
  } )
```

```
length(opt.details) #number of symbols passed e.g. 2
sapply(opt.details, length) # contracts per symbol

## End(Not run)
```

---

reqCurrentTime            *Request The Current TWS Time*

---

### Description

Returns the current time from the TWS server, expressed as seconds since 1970-01-01 GMT.

### Usage

```
reqCurrentTime(twsconn)
```

### Arguments

twsconn            a valid tws connection object

### Value

Seconds since 1970-01-01 GMT

### Author(s)

Jeffrey A. Ryan

### References

Interactive Brokers [www.interactivebrokers.com](http://www.interactivebrokers.com)

### Examples

```
## Not run:
tws <- twsConnect()
reqCurrentTime(tws)

## End(Not run)
```

---

reqHistoricalData	<i>Request Historical Data From TWS</i>
-------------------	-----------------------------------------

---

### Description

Makes a request to the Interactive Brokers Trader Workstation (TWS), and returns an xts object containing the results of the request if successful.

### Usage

```
reqHistoricalData(conn,
                  Contract,
                  endDateTime,
                  barSize = "1 day",
                  duration = "1 M",
                  useRTH = "1",
                  whatToShow = "TRADES",
                  timeFormat = "1",
                  tzone = "",
                  verbose = TRUE,
                  tickerId = "1",
                  eventHistoricalData,
                  file)
```

```
reqHistory(conn, Contract, barSize, ...)
```

### Arguments

conn	a twsConnection object
Contract	a twsContract
endDateTime	end date/time for request. See details.
barSize	bar size to retrieve
duration	time span the request will cover
useRTH	limited to regular trading hours
whatToShow	type of data to be extracted
timeFormat	POSIX style or seconds from 1970-01-01
tzone	time zone of the resulting intraday series (if applicable)
verbose	should progress be documented
tickerId	a unique id to associate with the request
eventHistoricalData	callback function to process data
file	file to write data to
...	args to pass to reqHistoricalData

## Details

The reqHistory function is a simple wrapper to request maximal history from IB. It is meant to be used directly, or as a template for new wrappers.

All arguments should be character strings. Attempts will be made to coerce, but should not be relied upon.

The endDateTime argument must be of the form 'CCYYMMDD HH:MM:SS TZ'. If not specified the current time as returned from the TWS server will be used. This is the preferred method for backfilling data. The 'TZ' portion of the string is optional.

Legal barSize settings are technically '1 secs', '5 secs', '15 secs', '30 mins', '1 min', '2 mins', '3 mins', '5 mins', '15 mins', '30 mins', '1 hour', '1 day', '1 week', '1 month', '3 months', and '1 year'. They must be specified exactly and there is no guarantee from the API that all will work for all securities or durations.

The duration string must be of the form 'n S' where the last character may be any one of 'S' (seconds), 'D' (days), 'W' (weeks), 'M' (months), and 'Y' (year). At present the limit for years is 1.

useRTH takes either '1' or '0', indicating the request to return only regular trade hour data, or all data, respectively.

whatToShow can be any one of the following, though depending on the overall request it may not succeed. 'TRADES', 'MIDPOINT', 'BID', 'ASK', 'BID\_ASK'.

time.format should simply be left alone. :D

eventHistoricalData accepts a user function to process the raw data returned by the TWS. This consists of a character vector that includes the first five elements of header information, with the fifth element specifying the number of rows in the results set. Passing NULL to eventHistoricalData will return the raw character vector. If nothing is specified, an xts object is returned.

The eventHistoricalData function, if any, is called after all data has been received by the client.

The file argument calls write.table to produce output suitable to reading in by read.csv. The file argument is passed to the write.table call, and if an empty string will return the output to the console.

The hasGaps column is converted automatically from (true,false) to 1 or 0, respectively.

## Value

Returns an xts object containing the requested data, along with additional information stored in the objects xtsAttributes, unless callback or file is specified.

## Note

The rules for historical data requests are somewhat vague. Not all symbols have data, and those that do may only be available with specific combinations of barSize and duration arguments. At present the only way to know is to try the combination in question.

There is a strictly enforced 10 seconds between request pacing rule implemented by the TWS. Keep this in mind. IBrokers currently does *not* manage this for the user via reqHistoricalData, though reqHistory does.



**Author(s)**

Jeffrey A. Ryan

**References**

Interactive Brokers [www.interactivebrokers.com](http://www.interactivebrokers.com)

**See Also**

[twContract](#), [twConnect](#)

**Examples**

```
## Not run:
tw <- twConnect()
contract <- twEquity('QQQQ', 'SMART', 'ISLAND')

# by default retrieves 30 days of daily data
reqHistoricalData(tw, Contract=contract)

# by default retrieves a year of 1 minute bars
Sys.sleep(10) # mandatory 10s between request to avoid IB pacing violation
reqHistory(tw, Contract=contract)

## End(Not run)
```

---

reqIds	<i>Request Next Valid Id</i>
--------	------------------------------

---

**Description**

Get the next valid order ID for use with the TWS.

**Usage**

```
reqIds(conn, numIds = 1)
```

**Arguments**

conn	a valid twsConnection object of class twsconn.
numIds	currently ignored by the TWS.

**Details**

twsconn objects maintain the next valid id inside of the object, returning the current id, and incrementing by 1 with each call to reqIds.

For twsconn objects, reqIds and .reqIds results are identical.

**Value**

A character representation of the next numeric ID.

**Note**

The TWS will keep track of order ids across connection ids and sessions. The values may be reset only as outlined by the official TWS documentation. IBrokers simply records and manages the data as recieved from the TWS upon initial connection. Each connection id will have a different order id associated with it.

**Author(s)**

Jeffrey A. Ryan

---

 reqMktData

---

*Request Market Data Feed from TWS*


---

**Description**

Allows for streaming market data to be handled in R.

**Usage**

```
reqMktData(conn,
            Contract,
            tickGenerics = "100,101,104,106,165,221,225,236",
            snapshot = FALSE,
            tickerId = "1",
            timeStamp = "%Y%m%d %H:%M:%OS",
            playback = 1,
            file = "",
            verbose = TRUE,
            eventWrapper = eWrapper(),
            CALLBACK = twsCALLBACK, ...)
```

```
cancelMktData(conn, tickerId)
```

**Arguments**

conn	a valid twsConnection or twsPlayback connection
Contract	twsContract object(s) requested data for
tickGenerics	a comman delimited string of generic tick types
snapshot	should snapshot data be returned
tickerId	the ticker id to associate with the returned data
timeStamp	include R time stamps

playback	playback speed adjustment
file	passed to internal cat calls. See associated help
verbose	print diagnostics?
eventWrapper	eWrapper object
CALLBACK	main reciever callback
...	additional args

### Details

This function provides R level access to market data streams as returned by the TWS API. The Interactive Brokers documentation should be reference for the exact meaning of the returned data.

timeStamps is unique to the R API in that each incoming signal will be marked with a (potentially) unique timestamp. Alternatively it is possible to pass a formatting string for use in `format(Sys.time())`. To suppress the time stamp set the argument to NULL. This is *not* sent by the TWS - merely prepended to the output by R.

Callbacks, via CALLBACK and eventWrapper are designed to allow for R level processing of the real-time data stream.

Each message recieved (each update to the market data) will invoke one the appropriately names eWrapper callback, depending on the message type. By default when nothing is specified, the code will call the default method for printing the results to the screen via `cat`.

Note that the use of the argument `file` will be passed to these `cat` calls, and therefore it will be possible to use the functionality of `cat` directly - e.g. piping output or writing to a connection. The simplest use of `file` would be to specify the name of a file to append the output of the stream to.

The CALLBACK argument is used for more control of the incoming results. This requires user-level error checking as well as TWS API interaction. It is here for advanced use and until documented should be left alone.

### Value

The real-time market data from the TWS.

### Note

As R is single threaded - this request will run until interrupted by an error or by user action. Both will clean up after themselves when appropriate.

### Author(s)

Jeffrey A. Ryan

### References

Interactive Brokers API: <http://individuals.interactivebrokers.com/php/apiguide/apiguide.htm>

**See Also**

[twsCALLBACK](#), [eWrapper](#), [twsConnect](#), [twsContract](#)

**Examples**

```
## Not run:
tws <- twsConnect()
contract <- twsEquity("QQQQ", "SMART", "ISLAND")
reqMktData(tws, contract)

# write to an open file connection
fh <- file('out.dat', open='a')
reqMktData(tws, contract, file=fh)
close(fh)

## End(Not run)
```

---

reqMktDepth

*Request Market Depth Feed from TWS*


---

**Description**

Allows for streaming market depth (order book) data to be handled in R.

**Usage**

```
reqMktDepth(conn,
             Contract,
             tickerId = "1",
             numRows = "20",
             timeStamp = TRUE,
             playback = 1,
             file = "",
             verbose = TRUE,
             eventWrapper = eWrapper(),
             CALLBACK = twsCALLBACK, ...)

cancelMktDepth(conn, tickerId)
```

**Arguments**

conn	a valid twsConnection connection
Contract	twsContract object(s) requested data for
tickerId	the ticker id to associate with the returned data
numRows	depth of book
timeStamp	include R time stamps

playback	playback speed adjustment
file	passed to internal cat calls. See associated help.
verbose	print diagnostics?
eventWrapper	callback closure
CALLBACK	main receiver loop
...	additional args

## Details

This function provides R level access to book data as returned by the TWS API. The Interactive Brokers documentation should be reference for the exact meaning of the returned data.

timeStamps is unique to the R API in that each incoming signal will be marked with a (potentially) unique timestamp. Alternatively it is possible to pass a formatting string for use in `format(Sys.time())`. To suppress the time stamp set the argument to NULL.

Callbacks, via `eventUpdateMktDepth`, `eventUpdateMktDepthL2`, or `CALLBACK` are designed to allow for R level processing of the real-time data stream.

The first two correspond to actions based upon the actual signal received. These may be user-defined functions taking the appropriate arguments. Each message received (each update to the market depth) will invoke one of these callbacks. By default when nothing is specified, the code will call the default method for printing the results to the screen via `cat`.

Note that the use of the argument `file` will be passed to these `cat` calls, and therefore it will be possible to use the functionality of `cat` directly - e.g. piping output or writing to a connection. The simplest use of `file` would be to specify the name of a file to append the output of the stream to.

The `CALLBACK` argument is used for more control of the incoming results. This requires user-level error checking as well as TWS API interaction. It is here for advanced use and until documented should be left alone.

## Value

The book depth.

## Note

As R is single threaded - this request will run until interrupted by an error or by user action. Both will clean up after themselves when appropriate.

## Author(s)

Jeffrey A. Ryan

## References

Interactive Brokers API: <http://individuals.interactivebrokers.com/php/apiguide/apiguide.htm>

**See Also**

[twConnect](#), [twContract](#)

**Examples**

```
## Not run:
tw <- twConnect()
contract <- twEquity("QQQQ", "SMART", "ISLAND")
reqMktDepth(tw, contract)

# write to a file
reqMktDepth(tw, contract, file='out.dat')

## End(Not run)
```

---

reqNewsBulletins

*Subscribe or Unsubscribe To News Bulletins*

---

**Description**

Subscription start and end methods for the API.

**Usage**

```
reqNewsBulletins(twsconn, allMsgs=TRUE)

cancelNewsBulletins(twsconn)
```

**Arguments**

twsconn	A twsConnection object
allMsgs	Should all existing bulletins be returned (TRUE), or just new ones?

**Details**

Calling reqNewsBulletins will start a subscription via the API. This will continue and incoming messages will be handled by eWrapper 'updateNewBulletin' method. Bulletins are cancelled by calling the cancel version.

**Value**

Called for its side-effects.

**Note**

This is not "news" per se, it is a subscription to the API bulletins.

**Author(s)**

Jeffrey A. Ryan

**References**

<http://www.interactivebrokers.com/php/apiUsersGuide/apiguide/java/reqnewsbulletins.htm>

---

 reqRealTimeBars

*Request Real Time Bars from TWS*


---

**Description**

Allows for streaming real-time bars to be handled in R

**Usage**

```
reqRealTimeBars(conn,
                Contract,
                whatToShow = "TRADES",
                barSize = "5",
                useRTH = TRUE,
                playback = 1,
                tickerId = "1",
                file = "",
                verbose = TRUE,
                eventWrapper=eWrapper(),
                CALLBACK=twscallback,
                ...)
```

```
cancelRealTimeBars(conn, tickerId)
```

**Arguments**

conn	a valid twsConnection or twsPlayback object
Contract	twsContract object(s) requested
tickerId	the ticker id to associate with the returned bars
whatToShow	what to show
barSize	bar size - currently on 5 secs is TWS supported
playback	playback speed adjustment
useRTH	regular trading hours (logical)
file	passed to internal cat calls. See associated help.
verbose	print diagnostics
eventWrapper	eventWrapper object
CALLBACK	main reciever callback
...	additional args to callback

## Details

This function provides R level access to real time (5 second) bars returned by the TWS API. The Interactive Brokers documentation should be reference for the exact meaning of the returned data.

If the conn is a connection of data to be played back all other arguments are ignores, except for playback, which is a multiplier of the bar size in seconds. To force all data to be read without pause set this to 0.

Callbacks, via eventRealTimeBars and CALLBACK are designed to allow for R level processing of the real-time data stream.

eventWrapper allows for direct manipulation of the actual signal recieved. These may be user-defined functions taking the appropriate arguments. Each message recieved (each new bar) will invoke one of this callback. By default when nothing is specified, the code will call the default method for printing the results to the screen via 'cat'.

Note that the use of the argument 'file' will be passed to these 'cat' calls, and therefore it will be possible to use the functionality of 'cat' directly - e.g. piping output or writing to a connection. The simplest use of file would be to specify the name of a file, or open connection to append the output of the stream to.

The 'CALLBACK' argument is used for more control of the incoming results. This requires user-level error checking as well as TWS API interaction. It is here for advanced use and until documented should be left alone.

## Value

The real-time bar data requested.

## Note

As R is single threaded - this request will run until interrupted by an error or by user action. Both will clean up after themselves when appropriate.

## Author(s)

Jeffrey A. Ryan

## References

Interactive Brokers TWS API <http://individuals.interactivebrokers.com/php/apiguide/apiguide.htm>

## See Also

[twConnect](#), [twContract](#), [eWrapper](#)

## Examples

```
## Not run:
tw <- twConnect()
contract <- twEquity("QQQQ", "SMART", "ISLAND")
reqRealTimeBars(tw, contract)
```



```
# write to an open file connection
fh <- file('out.dat',open='a')
reqRealTimeBars(tws, contract, file=fh)
close(fh)

## End(Not run)
```

---

setServerLogLevel	<i>Enable API Logging Via TWS</i>
-------------------	-----------------------------------

---

### Description

Set level of API logging to be done by TWS.

### Usage

```
setServerLogLevel(conn, logLevel = 2)
```

### Arguments

conn	a valid twsConnection
logLevel	an integer from 1 to 5

### Details

Calling this function will set the logging level for the current connection according to the following table:

- 1:SYSTEM (least detail)
- 2:ERROR (default)
- 3:WARNING
- 4:INFORMATION
- 5:DETAIL (most detail)

See TWS documentation for further details.

### Value

This function is called for its side-effects.

### Note

The online documentation warns of performance overhead when setting logLevel=5.

### Author(s)

Jeffrey A. Ryan

## References

TWS API Logging [http://www.interactivebrokers.com/php/apiUsersGuide/apiguide/api/api\\_logging.htm#XREF\\_63640\\_API\\_Logging](http://www.interactivebrokers.com/php/apiUsersGuide/apiguide/api/api_logging.htm#XREF_63640_API_Logging)

---

twscallback

*Internal Data Callback Routine*

---

## Description

twscallback is the primary function that is called after a request for data is sent. Within this call messages are received from the TWS, processed, and further actions can be handled.

## Usage

```
twscallback(twsCon, eWrapper, timestamp, file, playback = 1, ...)
```

## Arguments

twscCon	a twsConnection object
eWrapper	a closure created by eWrapper()
timestamp	a logical indicating if timestamps should be created
file	the file or connection to write to
playback	is this a live or playback connection
...	additional arguments to internal calls

## Details

This function is used as the primary management tool within all data calls built into **IBrokers**.

It works as is, or can be modified to manage unique data and trading requirements.

The general logic of the function is to receive the header to each incoming message from the TWS. This then gets passed to the processMsg function, along with the eWrapper object.

The eWrapper object can maintain state data (prices), and has functions for managing all incoming message types from the TWS.

Once the processMsg call returns, another cycle of the infinite loop occurs.

If the eWrapper object is used to maintain state information, it is possible to access this information from outside of the processMsg call, and thus be able to apply trade logic based upon the data acquired from the TWS.

An example will soon be available in the vignettes included in the package.

## Value

No value is returned. This function is called for its side effects.

**Author(s)**

Jeffrey A. Ryan

**See Also**[eWrapper](#)

---

**twsConnect***Establish, Check or Terminate a Connection to TWS or IBG*

---

**Description**

Functions to initiate, check, or disconnect from the Trader Workstation (TWS) or IB Gateway (IBG).

**Usage**

```

twsConnect(clientId = 1, host = 'localhost',
           port = 7496, verbose = TRUE, timeout = 5,
           filename = NULL, blocking=.Platform$OS.type=="windows")
ibgConnect(clientId = 1, host = 'localhost',
           port = 4001, verbose = TRUE, timeout = 5,
           filename = NULL, blocking=.Platform$OS.type=="windows")

twsDisconnect(twsconn)

isConnected(twsconn)
is.twsConnection(x)
is.twsPlayback(x)

```

**Arguments**

clientId	the unique client id to associate with
host	the host server
port	the port that the TWS is listening on
verbose	should the connection attempt be verbose
timeout	length in seconds before aborting attempt
filename	file containing recorded TWS data
blocking	should a blocking connection be established. See details.
twsconn	a valid twsConnection object
x	a connection to be checked

**Details**

Returns a `twConnection` object for use in subsequent TWS API calls. Attempting to create another connection to the server with the same `clientId` will result in an error.

If `filename` is set to a file containing data recorded in the standard TWS format - calls using this connection will playback the recorded data.

While the **IBrokers** package is fully cross-platform, the behavior of sockets varies by operating system implementation. In general, setting `blocking=TRUE` on Windows (the default on Windows) results in more consistent and reliable connections. This option is only exposed to enable debugging of platform differences and optimization - and is not intended to be altered except in those cases.

**Value**

A `twconn` object.

**Note**

While it is not strictly required to disconnect via `twDisconnect` it is probably advisable.

If not set `options(digits.secs=6)` will be called internally to properly represent on screen the R based timestamps.

**Author(s)**

Jeffrey A. Ryan

**References**

Interactive Brokers: [www.interactivebrokers.com](http://www.interactivebrokers.com)

**Examples**

```
## Not run:  
tw <- twConnect()  
twDisconnect(tw)  
  
## End(Not run)
```

---

<code>twConnectionTime</code>	<i>TWS API Utility Functions</i>
-------------------------------	----------------------------------

---

**Description**

General API utility functions.

**Usage**

```
twConnectionTime(con)  
  
serverVersion(con)
```

**Arguments**

con                    a twsConnection object

**Details**

This is simply extracted from the twsConnection object. No API request is made.

**Value**

The requested value.

**Author(s)**

Jeffrey A. Ryan

**References**

Interactive Brokers LLC <http://www.interactivebrokers.com>

**See Also**

[twConnect](#)

**Examples**

```
## Not run:  
twConnectionTime(con)  
serverVersion(con)  
  
## End(Not run)
```

---

twContract	<i>Create a twContract</i>
------------	----------------------------

---

**Description**

Create, test, and coerce a twContract for use in API calls.

**Usage**

```
twContract(conId,  
           symbol,  
           sectype,  
           exch,  
           primary,  
           expiry,  
           strike,  
           currency,
```

```

        right,
        local,
        multiplier,
        combo_legs_desc,
        comboleg,
        include_expired,
        secIdType = "",
        secId = ""
    )

is.twsContract(x)

as.twsContract(x, ...)
```

### Arguments

conId	the IB contract ID
symbol	the IB symbol requested
sectype	the security type
exch	the requested exchange
primary	the primary exchange of the security
expiry	the expiration date
strike	the strike price
currency	the requested currency
right	the requested right
local	the local security name
multiplier	the contract multiplier
combo_legs_desc	not implemented yet
comboleg	not implemented yet
include_expired	should expired contracts be included
secIdType	unique identifier for secIdType
secId	security identifier: ISIN, CUSIP, SEDOL, RIC
x	object to test or coerce
...	additional arguments

### Details

These are directly from the TWS API. See that help until I can find time to fill in this one.

More useful for specific requests are `twsEquity`, `twsOption`, `twsBond`, `twsFuture`, and `twsCurrency`.

### Value

A `twsContract` object.

**Author(s)**

Jeffrey A. Ryan

**References**Interactive Brokers: [www.interactivebrokers.com](http://www.interactivebrokers.com)**See Also**[reqHistoricalData](#)**Examples**

```
contract <- twsContract(0,"AAPL","STK","SMART","ISLAND",
                        "", "0.0", "USD", "", "", "", NULL, NULL, "0")
```

twsCurrency

*Create a twsCurrency***Description**

Create a twsCurrency for use in API calls.

**Usage**

```
twsCurrency(symbol,
            currency='USD',
            exch='IDEALPRO',
            primary='',
            strike='0.0',
            right='',
            local='',
            multiplier='',
            include_expired='0',
            conId=0)
```

**Arguments**

symbol	the IB symbol requested
currency	the requested currency
exch	the requested exchange
primary	the primary exchange of the security
strike	the strike price
right	the requested right
local	the local security name

multiplier	the contract multiplier
include_expired	should expired contracts be included
conId	contract ID

**Details**

A wrapper to twsContract to make 'currency/FX' contracts easier to specify.  
twsCASH is an alias.

**Value**

A twsContract object.

**Author(s)**

Jeffrey A. Ryan

**References**

Interactive Brokers: [www.interactivebrokers.com](http://www.interactivebrokers.com)

**See Also**

[reqHistoricalData](#), [twsContract](#)

**Examples**

```
currency <- twsCurrency("EUR")
```

---

twsEquity

*Create a twsEquity*

---

**Description**

Create a twsEquity for use in API calls.

**Usage**

```
twsEquity(symbol,
           exch="SMART",
           primary,
           strike='0.0',
           currency='USD',
           right='',
           local='',
           multiplier='',
           include_expired='0',
           conId=0)
```



**Arguments**

symbol	the IB symbol requested
exch	the requested exchange (defaults to 'SMART')
primary	the primary exchange of the security
strike	the strike price
currency	the requested currency
right	the requested right
local	the local security name
multiplier	the contract multiplier
include_expired	should expired contracts be included
conId	contract ID

**Details**

A wrapper to `twsContract` to make 'equity' contracts easier to specify.  
`twsSTK` is an alias.

**Value**

A `twsContract` object.

**Author(s)**

Jeffrey A. Ryan

**References**

Interactive Brokers: [www.interactivebrokers.com](http://www.interactivebrokers.com)

**See Also**

[reqHistoricalData](#), [twsContract](#)

**Examples**

```
equity <- twsEquity("AAPL", "SMART", "ISLAND")
```

---

twsFuture

*Create a twsFuture Contract*


---

**Description**

Create a twsFuture contract for use in API calls.

**Usage**

```
twsFuture(symbol,
           exch,
           expiry,
           primary='',
           currency='USD',
           right='',
           local='',
           multiplier='',
           include_expired='0',
           conId=0)
```

**Arguments**

symbol	the IB symbol requested
exch	the requested exchange
expiry	the requested contract expiration
primary	the primary exchange of the security
currency	the requested currency
right	the requested right
local	the local security name
multiplier	the contract multiplier
include_expired	should expired contracts be included
conId	contract ID

**Details**

A wrapper to twsContract to make ‘futures’ contracts easier to specify.  
twsFUT is an alias.

**Value**

A twsContract object.

**Author(s)**

Jeffrey A. Ryan

**References**

Interactive Brokers: [www.interactivebrokers.com](http://www.interactivebrokers.com)

**See Also**

[reqHistoricalData](#), [twsContract](#)

**Examples**

```
future <- twsFuture("NQ", "GLOBEX", "200803")
```

---

twsOption	<i>Create a twsContract for Options</i>
-----------	-----------------------------------------

---

**Description**

Create a twsContract for use in API calls.

**Usage**

```
twsOption(local,
           expiry="",
           strike="",
           right="",
           exch="SMART",
           primary="",
           currency='USD',
           symbol=' ',
           multiplier="100",
           include_expired='0',
           conId=0)
```

**Arguments**

local	the IB symbol requested
expiry	option expiration CCYYMM [optional]
strike	the strike price [optional]
right	the requested right - 'C', 'CALL', 'P', or 'PUT' [optional]
exch	the requested exchange [optional, defaults to SMART]
primary	the primary exchange of the security [optional]
currency	the requested currency [defaults to USD]

symbol	the security name [optional]
multiplier	the contract multiplier
include_expired	should expired contracts be included [defaults to "0" (false)]
conId	contract ID

### Details

A wrapper to `twsContract` to make 'option' contracts easier to specify.

Some of the optionable parameters are contingent on the request being made. Refer to the *TWS* documentation for details.

`twsOPT` is an alias.

### Value

A `twsContract` object.

### Note

Option contracts on the TWS have certain rules which are different than standard data requests.

The `local` symbol is required. This can be found on the main TWS screen under contract details, or via the web at [www.interactivebrokers.com](http://www.interactivebrokers.com)

Since the local symbol is required, all other values are redundant. It is best to simply specify the local name and let the TWS manage the lookup.

The expiry needs to be either of class `Date` to be coerced to a string of format 'CCYYMM', or provided in that format.

Historical requests cannot be for a `barSize='1 D'` or less frequent.

`barSize` must be "1 min" per Interactive Brokers API.

### Author(s)

Jeffrey A. Ryan

### References

Interactive Brokers: [www.interactivebrokers.com](http://www.interactivebrokers.com)

### See Also

[reqMktData](#), [twsContract](#)

### Examples

```
opt <- twsOption("QQAS", expiry="200901", strike="45.0", right="C")
```

---

twsOrder	<i>Create twsOrder Object</i>
----------	-------------------------------

---

**Description**

Create twsOrder object for placeOrder API call.

**Usage**

```
twsOrder(orderId,
    action = "BUY",
    totalQuantity = "10",
    orderType = "LMT",
    lmtPrice = "0.0",
    auxPrice = "0.0",
    tif = "",
    outsideRTH = "0",
    openClose = "0",
    origin = .twsOrderID$CUSTOMER,
    ocaGroup = "",
    account = "",
    orderRef = "",
    transmit = TRUE,
    parentId = "0",
    blockOrder = "0",
    sweepToFill = "0",
    displaySize = "0",
    triggerMethod = "0",
    hidden = "0",
    discretionaryAmt = "0.0",
    goodAfterTime = "",
    goodTillDate = "",
    faGroup = "",
    faMethod = "",
    faPercentage = "",
    faProfile = "",
    shortSaleSlot = "0",
    designatedLocation = .twsOrderID$EMPTY_STR,
    ocaType = "0",
    rule80A = "",
    settlingFirm = "",
    clearingAccount = "",
    clearingIntent = "",
    allOrNone = "0",
    minQty = "",
    percentOffset = "",
    eTradeOnly = "0",
```

```

firmQuoteOnly = "0",
nbboPriceCap = "",
auctionStrategy = "0",
startingPrice = "",
stockRefPrice = "",
delta = "",
stockRangeLower = "",
stockRangeUpper = "",
overridePercentageConstraints = "0",
volatility = "",
volatilityType = "",
deltaNeutralOrderType = "",
deltaNeutralAuxPrice = "",
continuousUpdate = "0",
referencePriceType = "",
trailStopPrice = "",
basisPoints = "",
basisPointsType = "",
scaleInitLevelSize = "",
scaleSubsLevelSize = "",
scalePriceIncrement = "",
notHeld = FALSE,
algoStrategy = "",
algoParams = NULL,
whatIf = FALSE,
clientId = "",
permId = "")

```

### Arguments

orderId	The id for the order. Use reqIds.
action	Identifies the side. ( BUY, SELL, SSHORT )
totalQuantity	Order quantity.
orderType	Order type. ( MKT, MKTCLS, LMT, LMTCLS, PEGMKT, SCALE, STP, STPLMT, TRAIL, REL, VWAP, TRAILLIMIT )
lmtPrice	The <i>LIMIT</i> price for LMT, STPLMT and REL orderType
auxPrice	The <i>STOP</i> price for STPLMT (stop-limit) orders, and the offset for REL (relative) orders
tif	Time in force. (DAY, GTC, IOC, GTD)
outsideRTH	Allow orders to trigger outside of regular trading hours.
openClose	Specify whether order is open or close only. (Institutional Accounts Only)
origin	The order origin. 0=customer, 1=firm (Institutional Accounts Only)
ocaGroup	Identifies OCA group.
account	The account (Institutional Accounts Only)
orderRef	The order reference (Institutional Accounts Only)

transmit	Specify whether the order is transmitted to the TWS. If FALSE, order is created but not sent. (not implemented)
parentId	The orderId of the parent order, used for bracket and auto trailing stop orders.
blockOrder	ISE block order?
sweepToFill	Sweep to fill order?
displaySize	Publicly disclosed order size for Iceberg orders.
triggerMethod	How should <i>simulated</i> orders be triggered. Valid values are 0-8. See the official API for details.
hidden	Hide order on ISLAND?
discretionaryAmt	Amount off limit for discretionary orders.
goodAfterTime	Trades Good After Time: YYYYMMDD hh:mm:ss or ""
goodTillDate	Trades Good Till Date: YYYYMMDD hh:mm:ss or ""
faGroup	NA
faMethod	NA
faPercentage	NA
faProfile	NA
shortSaleSlot	1 or 2
designatedLocation	Only when shortSaleSlot=2
ocaType	Cancel on Fill with Block = 1 Reduce on Fill with Block = 2 Reduce on Fill without Block = 3
rule80A	Valid values: I, A, W, J, U, M, K, Y, N. See API.
settlingFirm	(Institutional Only)
clearingAccount	IBExecution customers only.
clearingIntent	IBExecution customers only.
allOrNone	yes=1, no=0
minQty	Minimum quantity order type.
percentOffset	Percent offset for REL (relative) orders.
eTradeOnly	Trade with electronic quotes. yes=1, no=0.
firmQuoteOnly	Trade with firm quotes. yes=1, no=0.
nbboPriceCap	The maximum Smart order distance from the NBBO.
auctionStrategy	BOX only. See API.
startingPrice	BOX only. See API.
stockRefPrice	The stock reference price. VOL orders. See API.
delta	BOX only. See API.
stockRangeLower	See API.

stockRangeUpper	See API.
overridePercentageConstraints	See API.
volatility	See API.
volatilityType	See API.
deltaNeutralOrderType	See API.
deltaNeutralAuxPrice	See API.
continuousUpdate	See API.
referencePriceType	See API.
trailStopPrice	For TRAILLIMIT orders only.
basisPoints	EFP orders only.
basisPointsType	EFP orders only.
scaleInitLevelSize	For Scale orders. See API.
scaleSubsLevelSize	For Scale orders. See API.
scalePriceIncrement	For Scale orders. See API.
notHeld	See API and guess.
algoStrategy	See API and guess.
algoParams	See API and guess.
whatIf	Use to request pre-trade commissions and margin information. TRUE/FALSE
clientId	Id of the client that placed the order.
permId	TWS id used to identify orders. Constant over a session.

### Details

Read the API documentation, code, and experiment with the paper accounts. And good luck!

### Value

Called for its side-effects.

### Note

Documentation is far from complete on this topic. Experiment and share your experiences.

### Author(s)

Jeffrey A. Ryan



**References**

Order API: <http://www.interactivebrokers.com/php/apiUsersGuide/apiguide/java/order.htm>

**See Also**

[placeOrder](#)

---

twScannerSubscription

*Create ScannerSubscription*

---

**Description**

Create an object for use with reqScannerSubscription and .reqScannerSubscription.

**Usage**

```
twScannerSubscription(numberOfRows = -1,
                      instrument = "",
                      locationCode = "",
                      scanCode = "",
                      abovePrice = "",
                      belowPrice = "",
                      aboveVolume = "",
                      averageOptionVolumeAbove = "",
                      marketCapAbove = "",
                      marketCapBelow = "",
                      moodyRatingAbove = "",
                      moodyRatingBelow = "",
                      spRatingAbove = "",
                      spRatingBelow = "",
                      maturityDateAbove = "",
                      maturityDateBelow = "",
                      couponRateAbove = "",
                      couponRateBelow = "",
                      excludeConvertible = "",
                      scannerSettingPairs = "",
                      stockTypeFilter = "")
```

**Arguments**

numberOfRows	Number of rows of scanner results returned
instrument	A character string of STK, ...
locationCode	A character string of STK.NA, STK.US, STK.US.MAJOR, ...
scanCode	One of the available scans. See details

abovePrice	Price to filter above
belowPrice	Price to filter below
aboveVolume	Volume to filter above
averageOptionVolumeAbove	Average option volume above this
marketCapAbove	Market cap to filter above
marketCapBelow	Market cap to filter below
moodyRatingAbove	Moody rating to filter above
moodyRatingBelow	Moody rating to filter below
spRatingAbove	S&P rating to filter above
spRatingBelow	S&P rating to filter below
maturityDateAbove	Maturity date to filter above
maturityDateBelow	Maturity date to filter below
couponRateAbove	Coupon rate to filter above
couponRateBelow	Coupon rate to filter below
excludeConvertible	?
scannerSettingPairs	?
stockTypeFilter	"ALL"?

### Details

By necessity, design, or otherwise - scanner data is difficult to correctly use at the API level. The valid values and some small examples are returned by the API using the related reqScannerParameters function. The XML returned by that call isn't very clear in its value or purpose though.

### Value

A (potentially) valid twsScannerSubscription object for reqScannerSubscription calls.

### Note

Further documentation will be forthcoming. Users are encouraged to email use cases to make for better documentation.

### Author(s)

Jeffrey A. Ryan



# Index

- \*Topic **\textasciitildekwd1**
  - .placeOrder, 4
  - twsOrder, 37
- \*Topic **\textasciitildekwd2**
  - .placeOrder, 4
  - twsOrder, 37
- \*Topic **class**
  - twsScannerSubscription, 41
- \*Topic **misc**
  - calculateImpliedVolatility, 5
  - exerciseOptions, 8
  - reqAccountUpdates, 11
  - reqNewsBulletins, 22
  - twsCALLBACK, 26
- \*Topic **package**
  - IBrokers-package, 2
- \*Topic **utilities**
  - .twsIncomingMSG, 5
  - eWrapper, 6
  - processMsg, 10
  - reqAccountUpdates, 11
  - reqContractDetails, 12
  - reqCurrentTime, 14
  - reqHistoricalData, 15
  - reqIds, 17
  - reqMktData, 18
  - reqMktDepth, 20
  - reqRealTimeBars, 23
  - setServerLogLevel, 25
  - twsCALLBACK, 26
  - twsConnect, 27
  - twsConnectionTime, 28
  - twsContract, 29
  - twsCurrency, 31
  - twsEquity, 32
  - twsFuture, 34
  - twsOption, 35
  - .lastRequest (.twsIncomingMSG), 5
  - .placeOrder, 4
  - .reqAccountUpdates (reqAccountUpdates), 11
  - .reqIds (reqIds), 17
  - .twsERR (.twsIncomingMSG), 5
  - .twsIncomingMSG, 5
  - .twsOutgoingMSG (.twsIncomingMSG), 5
  - as.twsContract (twsContract), 29
  - calculateImpliedVolatility, 5
  - calculateOptionPrice (calculateImpliedVolatility), 5
  - cancelAccountUpdates (reqAccountUpdates), 11
  - cancelHistoricalData (reqHistoricalData), 15
  - cancelMktData (reqMktData), 18
  - cancelMktDepth (reqMktDepth), 20
  - cancelNewsBulletins (reqNewsBulletins), 22
  - cancelOrder (.placeOrder), 4
  - cancelRealTimeBars (reqRealTimeBars), 23
  - eWrapper, 6, 11, 20, 24, 27
  - exerciseOptions, 8
  - ibgConnect (twsConnect), 27
  - IBrokers (IBrokers-package), 2
  - IBrokers-package, 2
  - IBrokersRef (IBrokers-package), 2
  - is.twsConnection (twsConnect), 27
  - is.twsContract (twsContract), 29
  - is.twsPlayback (twsConnect), 27
  - isConnected (twsConnect), 27
  - placeOrder, 41
  - placeOrder (.placeOrder), 4
  - processMsg, 8, 10
  - replaceFA (.twsIncomingMSG), 5
  - reqAccountUpdates, 11

reqContractDetails, 12  
reqCurrentTime, 14  
reqExecutions (. twsIncomingMSG), 5  
reqHistoricalData, 15, 31–33, 35  
reqHistory (reqHistoricalData), 15  
reqIds, 5, 17  
reqManagedAccts (. twsIncomingMSG), 5  
reqMktData, 18, 36  
reqMktDepth, 20  
reqNewsBulletins, 22  
reqOpenOrders (. twsIncomingMSG), 5  
reqRealTimeBars, 23  
reqScannerParameters (. twsIncomingMSG),  
5  
reqScannerSubscription, 43  
reqScannerSubscription  
(. twsIncomingMSG), 5  
requestFA (. twsIncomingMSG), 5  
  
serverVersion (twsConnectionTime), 28  
setServerLogLevel, 25  
  
twsBAG (. twsIncomingMSG), 5  
twsCALLBACK, 8, 11, 20, 26  
twsCASH (twsCurrency), 31  
twsCFD (twsEquity), 32  
twsComboLeg (. twsIncomingMSG), 5  
twsConnect, 17, 20, 22, 24, 27, 29  
twsConnect2 (twsConnect), 27  
twsConnectionTime, 28  
twsContract, 5, 13, 17, 20, 22, 24, 29, 32, 33,  
35, 36  
twsCurrency, 31  
twsDEBUG (. twsIncomingMSG), 5  
twsDisconnect (twsConnect), 27  
twsEquity, 32  
twsExecutionFilter (. twsIncomingMSG), 5  
twsFOP (twsFuture), 34  
twsFUT (twsFuture), 34  
twsFuture, 34  
twsFutureOpt (twsFuture), 34  
twsIND (twsContract), 29  
twsIndex (twsContract), 29  
twsOPT (twsOption), 35  
twsOption, 35  
twsOrder, 5, 37  
twsPortfolioValue (reqAccountUpdates),  
11  
twsScannerSubscription, 41  
twsSTK (twsEquity), 32