

Package ‘crunch’

February 2, 2018

Type Package

Title Crunch.io Data Tools

Description The Crunch.io service <<http://crunch.io/>> provides a cloud-based data store and analytic engine, as well as an intuitive web interface. Using this package, analysts can interact with and manipulate Crunch datasets from within R. Importantly, this allows technical researchers to collaborate naturally with team members, managers, and clients who prefer a point-and-click interface.

Version 1.20.0

URL <http://crunch.io/r/crunch/>, <https://github.com/Crunch-io/rcrunch>

BugReports <https://github.com/Crunch-io/rcrunch/issues>

License LGPL (>= 3)

Depends R (>= 3.0.0)

Imports crayon, curl, grDevices, httr (>= 1.0.0), httpcache (>= 0.1.4), jsonlite (>= 0.9.15), methods

Suggests covr, devtools, httpptest (>= 3.0.0), knitr, rmarkdown, rstudioapi, spelling, testthat (>= 2.0.0)

VignetteBuilder knitr

Language en-US

RoxygenNote 6.0.1

Collate 'AllClasses.R' 'AllGenerics.R' 'variable-definition.R'
'R-to-variable.R' 'abstract-categories.R' 'abstract-category.R'
'add-subvariable.R' 'add-variable.R' 'api.R' 'append-dataset.R'
'as-data-frame.R' 'auth.R' 'batches.R' 'case-variables.R'
'categories.R' 'category.R' 'change-category-id.R'
'combine-categories.R' 'compare-categories.R'
'compare-datasets.R' 'compare-subvariables.R'
'compare-variables.R' 'compare.R' 'conditional-transform.R'
'consent.R' 'context-manager.R' 'copy.R' 'crunch-data-frame.R'
'crunch.R' 'crunchbox.R' 'cube-dims.R' 'cube-query.R'
'cube-residuals.R' 'cube-result.R' 'cube-transforms.R'

'cube-variables.R' 'cut.R' 'dataset-catalog.R'
 'dataset-extract.R' 'dataset-order.R' 'dataset-stream.R'
 'dataset-update.R' 'dataset.R' 'dichotomize.R' 'drop-rows.R'
 'edit-lock.R' 'export-dataset.R' 'expressions.R' 'filters.R'
 'folders.R' 'fork-and-merge.R' 'formula.R' 'geo.R'
 'get-datasets.R' 'github.R' 'hide-variables.R' 'insertions.R'
 'interact.R' 'join-dataset.R' 'json.R' 'make-array.R'
 'members.R' 'merge-crunch-data-frame.R' 'misc.R'
 'multitables.R' 'new-dataset.R' 'ordering.R'
 'permission-catalog.R' 'pretty-print.R' 'progress.R'
 'projects.R' 'search.R' 'session.R' 'share.R' 'shoji-catalog.R'
 'shoji-entity.R' 'shoji-order-slots.R' 'shoji-order.R'
 'shoji.R' 'show.R' 'subtotals-and-headings.R' 'subvariables.R'
 'tab-book.R' 'teams.R' 'transform-calculate.R' 'transform.R'
 'tuple.R' 'univariate.R' 'user.R' 'variable-catalog.R'
 'variable-delete.R' 'variable-derivation.R'
 'variable-metadata.R' 'variable-order.R' 'variable-summary.R'
 'variable-to-R.R' 'variable-type.R' 'variable-update.R'
 'variable.R' 'versions.R' 'weight.R' 'zcl.R'

NeedsCompilation no

Author Neal Richardson [aut, cre],
 Jonathan Keane [ctb],
 Gordon Shotwell [ctb]

Maintainer Neal Richardson <neal@crunch.io>

Repository CRAN

Date/Publication 2018-02-02 21:20:50 UTC

R topics documented:

addGeoMetadata	6
addSubvariable	7
addVariables	7
appendDataset	8
appendStream	8
as.environment,CrunchDataset-method	9
as.vector,CrunchExpr-method	9
availableGeodataFeatures	10
batches	11
c-categories	11
catalog-dataframes	12
catalog-extract	13
catalog-length	17
Categories-class	17
categoriesFromLevels	19
changeCategoryID	19
cleanseBatches	20

collapseCategories	21
combine	21
compareDatasets	22
conditionalTransform	23
consent	25
ContextManager	25
copyOrder	26
copyVariable	27
createWithPreparedData	28
crtabs	28
crunch	29
crunch-cut	29
crunch-uni	31
crunchBox	32
CrunchDataFrame	33
CrunchDataset-class	34
CrunchGeography-class	34
CrunchVariable-class	36
cube-computing	36
cube-methods	37
cube-residuals	39
dashboard	40
dataset-extract	40
dataset-owner	42
dataset-to-R	43
dataset-update	44
dataset-variables	46
DatasetOrder-class	47
datasets	47
dedupeOrder	48
delete	49
deleteDataset	50
deleteSubvariables	51
deleteVariables	51
derivations	52
describe	54
dichotomize	56
dim-dataset	57
dropRows	58
duplicated	58
embedCrunchBox	59
exclusion	60
exportDataset	61
expressions	62
expropriateUser	63
filter-catalog	64
flattenOrder	65
flipArrays	65

folder	66
forkDataset	67
fortify	67
getTeams	68
grouped	68
hiddenVariables	69
hide	69
hideVariables	70
http-methods	71
importMultitable	71
Insertions-class	72
interactVariables	74
is-na-categories	75
is-public	76
is-selected-categories	77
is.archived,DatasetCatalog-method	77
is.dataset	79
is.editor	80
joinDatasets	81
listDatasets	82
loadDataset	83
locateEntity	83
lock	84
login	84
logout	85
makeArray	85
makeCaseVariable	86
makeWeight	87
matchCatToFeat	89
me	89
members<- ,CrunchTeam,MemberCatalog-method	90
merge	91
mergeFork	92
modifyWeightVariables	92
moveToGroup	93
multitable-catalog	94
mv	95
na-omit-categories	96
name,AbstractCategory-method	96
names,BatchCatalog-method	97
newDataset	99
newFilter	100
newMultitable	101
newProject	102
noTransforms	103
ordering	104
owners	104
pendingStream	105

permissions	105
pk	106
preCrunchBoxCheck	107
prepareDataForCrunch	107
project-icon	108
projects	108
refresh	109
removeEmptyGroups	110
resetPassword	110
restoreVersion	111
saveVersion	111
scoreCatToFeat	112
searchDatasets	112
self	113
session	113
session-extract	114
settings	115
share	116
shoji-index	116
ShojiObject-class	117
ShojiOrder-extract	117
ShojiOrder-length	120
ShojiOrder-slots	120
show-crunch	122
showTransforms,CrunchCube-method	123
Subtotal-class	124
subtotalArray,CrunchCube-method	127
Subvariables-class	128
subvars-extract	129
tabBook	131
tabbook-methods	132
table	133
temp.options	134
tojson-crunch	134
toVariable	135
Transforms-class	137
type	138
unbind	139
unshare	139
var-categories	140
variable-update	141
VariableCatalog-class	142
VariableDefinition	143
variableMetadata	144
VariableOrder-class	144
versions	145
webApp	145
weight	146

weightVariables	146
which	147
with-context-manager	148
write.csv.gz	148
[,CrunchExpr,CrunchLogicalExpr,ANY-method	149
\$,AbstractCategory-method	150

Index 151

addGeoMetadata	<i>Add geodata metadata to a crunch variable</i>
----------------	--

Description

If the variable matches a single geographic shapefile hosted by crunch, addGeoMetadata will make the appropriate [CrunchGeography](#) to add to a variable's `geo()` metadata. It matches based on how well the contents of the variable match the feature properties that are in each shapefile.

Usage

```
addGeoMetadata(variable, ...)
```

Arguments

variable	a Crunch variable to use for matching. This must be either a text or a categorical variable.
...	arguments passed on to <code>matchCatToFeat()</code> for example a set of available geographic features as <code>all_features</code> if you want to limit the number of features to be considered.

Details

If more than one property of the same geographic shapefile has the same highest matching score, the first one will be used.

If more than one geographic shapefile has the same highest matching score, an error will be printed listing the geographic shapefiles that matched. Information from this error can be used to setup an appropriate [CrunchGeography](#) by hand to connect a variable with the metadata needed.

Value

a [CrunchGeography](#) object that can be assigned into `geo(variable)`

Examples

```
## Not run:
geo(ds$state) <- addGeoMetadata(ds$state)

## End(Not run)
```

addSubvariable *Add subvariable to an array*

Description

Add subvariable to an array

Usage

```
addSubvariable(variable, subvariable)

addSubvariables(variable, subvariable)
```

Arguments

variable the array variable to modify
subvariable the subvariable to add, or a list of those to add, or a dataset subset. You can supply variables, variable definitions or lists of variables and variable definitions.

Value

variable with the indicated subvariables added.

See Also

[subvariables](#)

Examples

```
## Not run:
ds$allpets <- addSubvariable(ds$allpets, ds$allpets_4)
ds$petloc <- addSubvariables(ds$petloc, ds[c("petloc_school", "petloc_daycare")])

## End(Not run)
```

addVariables *Add multiple variables to a dataset*

Description

This function lets you add more than one variable at a time to a dataset. If you have multiple variables to add, this function will be faster than doing `ds$var <- value` assignment because it doesn't refresh the dataset's state in between variable POST requests.

Usage

```
addVariables(dataset, ...)
```

Arguments

dataset a CrunchDataset
 ... [VariableDefinitions](#) or a list of VariableDefinitions.

Value

dataset with the new variables added (invisibly)

appendDataset *Append one Crunch dataset to another*

Description

Append one Crunch dataset to another

Usage

```
appendDataset(dataset1, dataset2, autorollback)
```

Arguments

dataset1 a CrunchDataset
 dataset2 another CrunchDataset, or possibly a data.frame. If dataset2 is not a Crunch dataset, it will be uploaded as a new dataset before appending. If it is a Crunch-Dataset, it may be subsetted with a filter expression on the rows and a selection of variables on the columns.
 autorollback Deprecated. This option no longer does anything.

Value

dataset1, updated with dataset2, potentially filtered on rows and variables, appended to it.

appendStream *Manually trigger a pending append to a dataset*

Description

Crunch allows you to stream data to a dataset. Streaming data is useful for datasets which have frequent updates (see the [Crunch API documentation](#) for more information). Crunch automatically appends streamed data periodically; however, if you would like to trigger appending pending streamed data to a dataset, you can call `appendStream()`.

Usage

```
appendStream(ds)
```


Arguments

`ds` a `CrunchDataset`

Value

the dataset with pending stream data appended.

as.environment, CrunchDataset-method

as.environment method for CrunchDataset

Description

This method allows you to `eval` within a `Dataset`.

Usage

```
## S4 method for signature 'CrunchDataset'  
as.environment(x)
```

Arguments

`x` `CrunchDataset`

Value

an environment in which named objects are (promises that return) `CrunchVariables`.

as.vector, CrunchExpr-method

Convert Variables to local R objects

Description

`Crunch Variables` reside on the server, allowing you to work with datasets that are too big to bring into memory on your machine. Many functions, such as `max`, `mean`, and `crtabs()`, translate your commands into API queries and return only the result. But, not every operation you'll want to perform has been implemented on the `Crunch` servers. If you need to do something beyond what is currently supported, you can bring a variable's data into R with `as.vector(ds$var)` and work with it like any other R vector.

Usage

```
## S4 method for signature 'CrunchExpr'
as.vector(x, mode = "any")

## S4 method for signature 'CrunchVariable'
as.vector(x, mode = "any")
```

Arguments

x	a CrunchVariable
mode	for Categorical variables, one of either "factor" (default, which returns the values as factor); "numeric" (which returns the numeric values); or "id" (which returns the category ids). If "id", values corresponding to missing categories will return as the underlying integer codes; i.e., the R representation will not have any NA elements. Otherwise, missing categories will all be returned NA. For non-Categorical variables, the mode argument is ignored.

Details

as.vector transfers data from Crunch to a local R session. Note: as.vector returns the vector in the row order of the dataset. If filters are set that specify an order that is different from the row order of the dataset, the results will ignore that order. If you need the vector ordered in that way, use syntax like as.vector(ds\$var)[c(10, 5, 2)] instead.

Value

an R vector of the type corresponding to the Variable. E.g. CategoricalVariable yields type factor by default, NumericVariable yields numeric, etc.

See Also

[as.data.frame](#) for another interface for (lazily) fetching data from the server as needed; [exportDataset\(\)](#) for pulling all of the data from a dataset.

availableGeodataFeatures

Get the property features for available geographies

Description

Get the property features for available geographies

Usage

```
availableGeodataFeatures(x = getAPIRoot(), geodatum_fields = c("name",
  "description", "location"))
```

Arguments

`x` an API root address (default: the R-session default)

`geodatum_fields` character, what pieces of information about each geodatum should be retained? (default: `c("name", "description", "location")`)

Value

a dataframe with all of the available features and geographies for matching

batches	<i>See the appended batches of this dataset</i>
---------	---

Description

See the appended batches of this dataset

Usage

```
batches(x)
```

Arguments

`x` a CrunchDataset

Value

a BatchCatalog

c-categories	<i>S3 method to concatenate Categories and Category objects</i>
--------------	---

Description

S3 method to concatenate Categories and Category objects

Usage

```
## S3 method for class 'Categories'
c(...)
```

```
## S3 method for class 'Category'
c(...)
```

Arguments

... see [c](#)

Value

An object of class [Categories](#)

Examples

```
cat.a <- Category(name="First", id=1, numeric_value=1, missing=FALSE)
cat.b <- Category(name="Second", id=2)
cat.c <- Category(name="Third", id=3, missing=TRUE)
cats.1 <- Categories(cat.a, cat.b)
identical(cats.1, c(cat.a, cat.b))
identical(c(cats.1, cat.c), Categories(cat.a, cat.b, cat.c))
```

catalog-dataframes *as.data.frame method for catalog objects*

Description

This method gives you a view of a catalog, such as a `VariableCatalog`, as a `data.frame` in order to facilitate further exploration.

Usage

```
## S3 method for class 'VariableCatalog'
as.data.frame(x, row.names = NULL,
  optional = FALSE, keys = c("alias", "name", "type"), ...)
```

```
## S3 method for class 'ShojiCatalog'
as.data.frame(x, row.names = NULL, optional = FALSE,
  ...)
```

```
## S3 method for class 'BatchCatalog'
as.data.frame(x, row.names = NULL, optional = FALSE,
  keys = c("id", "status"), ...)
```

```
## S3 method for class 'FilterCatalog'
as.data.frame(x, row.names = NULL, optional = FALSE,
  keys = c("name", "id", "is_public"), ...)
```

Arguments

`x` A catalog object

`row.names` A character vector of elements to use as row labels for the resulting `data.frame`, or `NULL`, the default, adds no row labels.

optional	part of <code>as.data.frame</code> signature. Ignored.
keys	A character vector of the catalog attributes that you would like included in the <code>data.frame</code> . To include all attributes, set <code>keys</code> to <code>TRUE</code> , which is the default for some catalogs. Other catalog classes specify a narrower default: <ul style="list-style-type: none"> • <code>VariableCatalog</code>: <code>c("alias", "name", "type")</code> • <code>BatchCatalog</code>: <code>c("id", "status")</code> • <code>FilterCatalog</code>: <code>c("name", "id", "is_public")</code>
...	Additional arguments passed to <code>data.frame</code>

Details

Modifying the `data.frame` produced by this function will not update the objects on the Crunch server. Other methods exist for updating the metadata in the variable catalog, for example. See `vingette("variables", package = "crunch")`.

Value

A `data.frame` including metadata about each entity contained in the catalog. The fields in the `data.frame` match the `keys` argument provided to the function, and each row represents a entity.

Examples

```
## Not run:
ds <- loadDataset("iris")
vars <- variables(ds)
var_df <- as.data.frame(vars, keys = TRUE)
# With row names
as.data.frame(vars, row.names = urls(vars))

## End(Not run)
```

catalog-extract

Extract and modify subsets of Catalog-type objects

Description

Extract and modify subsets of Catalog-type objects

Usage

```
## S4 method for signature 'DatasetCatalog,numeric'
x[[i, j, ...]]

## S4 replacement method for signature 'DatasetCatalog,character,missing,DatasetTuple'
x[[i, j]] <- value
```

```
## S4 method for signature 'FilterCatalog,numeric'
x[[i, j, ...]]

## S4 replacement method for signature 'FilterCatalog,character,missing,CrunchLogicalExpr'
x[[i,
  j]] <- value

## S4 replacement method for signature 'FilterCatalog,numeric,missing,CrunchLogicalExpr'
x[[i,
  j]] <- value

## S4 replacement method for signature 'FilterCatalog,character,missing,CrunchFilter'
x[[i, j]] <- value

## S4 replacement method for signature 'FilterCatalog,numeric,missing,CrunchFilter'
x[[i, j]] <- value

## S4 method for signature 'MemberCatalog,character'
x[[i, j, ...]]

## S4 method for signature 'MemberCatalog,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 replacement method for signature 'MemberCatalog,ANY,missing,ANY'
x[[i, j]] <- value

## S4 replacement method for signature 'MemberCatalog,character,missing,`NULL`'
x[[i, j]] <- value

## S4 method for signature 'MultitableCatalog,numeric'
x[[i, j, ...]]

## S4 replacement method for signature 'MultitableCatalog,character,missing,formula'
x[[i, j]] <- value

## S4 replacement method for signature 'MultitableCatalog,numeric,missing,formula'
x[[i, j]] <- value

## S4 replacement method for signature 'MultitableCatalog,ANY,missing,`NULL`'
x[[i, j]] <- value

## S4 method for signature 'PermissionCatalog,character'
x[[i, j, ...]]

## S4 method for signature 'PermissionCatalog,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ProjectCatalog,numeric'
```

```
x[[i, j, ...]]

## S4 replacement method for signature 'ProjectCatalog,character,missing,list'
x[[i, j]] <- value

## S4 replacement method for signature 'ProjectCatalog,character,missing,CrunchProject'
x[[i,
  j]] <- value

## S4 method for signature 'ShojiCatalog,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ShojiCatalog,numeric,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ShojiCatalog,logical,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ShojiCatalog,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ShojiCatalog,ANY'
x[[i, j, ...]]

## S4 method for signature 'ShojiCatalog,character'
x[[i, j, ...]]

## S4 method for signature 'ShojiCatalog'
x$name

## S4 replacement method for signature 'ShojiCatalog'
x$name <- value

## S4 replacement method for signature 'ShojiCatalog,ANY,missing,ShojiCatalog'
x[i, j] <- value

## S4 method for signature 'TeamCatalog,numeric'
x[[i, j, ...]]

## S4 replacement method for signature 'TeamCatalog,character,missing,list'
x[[i, j]] <- value

## S4 replacement method for signature 'TeamCatalog,character,missing,CrunchTeam'
x[[i, j]] <- value

## S4 method for signature 'UserCatalog,character,ANY'
x[i, j, ..., drop = TRUE]
```

```

## S4 method for signature 'UserCatalog,character'
x[[i, j, ...]]

## S4 method for signature 'VariableCatalog,numeric'
x[[i, j, ...]]

## S4 replacement method for signature 'VariableCatalog,character,missing,VariableTuple'
x[[i,
  j]] <- value

## S4 replacement method for signature 'VariableCatalog,character,missing,CrunchVariable'
x[[i,
  j]] <- value

## S4 method for signature 'VariableCatalog,VariableOrder,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'VariableCatalog,VariableGroup,ANY'
x[i, j, ..., drop = TRUE]

## S4 replacement method for signature
## 'VariableCatalog,VariableOrder,missing,VariableCatalog'
x[i,
  j] <- value

## S4 replacement method for signature
## 'VariableCatalog,VariableGroup,missing,VariableCatalog'
x[i,
  j] <- value

```

Arguments

x	a Catalog object
i	which catalog elements to extract
j	Invalid
...	additional arguments (for example secondary a vector of elements to match against like <code>emails(x)</code> or <code>owners(x)</code> by default this is <code>names(x)</code>)
value	For updating, an object of the appropriate class and size to insert
drop	Invalid
name	for \$, the same as i for []

Value

A subset of x if extracting, otherwise x duly modified

catalog-length	<i>Length of Catalog</i>
----------------	--------------------------

Description

Length of Catalog

Usage

```
## S4 method for signature 'ShojiCatalog'
length(x)
```

Arguments

x a Catalog

Value

Integer: the number of elements in the index list

Categories-class	<i>Categories in CategoricalVariables</i>
------------------	---

Description

CategoricalVariables, as well as the array types composed from Categoricals, contain Categories. Categories are a subclass of list that contains only Category objects. Category objects are themselves subclasses of lists and contain the following fields: "name", "id", "numeric_value", "missing", and optionally "selected".

Usage

```
Categories(..., data = NULL)
```

```
Category(..., data = NULL)
```

```
## S4 method for signature 'AbstractCategories,ANY,ANY'
x[i, j, ..., drop = TRUE]
```

```
## S4 method for signature 'AbstractCategories,character,ANY'
x[i, j, ..., drop = TRUE]
```

```
## S4 method for signature 'AbstractCategories,numeric,ANY'
x[i, j, ..., drop = TRUE]
```

```
## S4 replacement method for signature 'AbstractCategories,character,ANY,ANY'
```

```

x[i, j, ...] <- value

## S4 method for signature 'AbstractCategories,character'
x[[i, j, ...]]

## S4 replacement method for signature 'AbstractCategories,character,ANY,ANY'
x[[i, j, ...]] <- value

## S4 method for signature 'AbstractCategories'
names(x)

## S4 replacement method for signature 'AbstractCategories'
names(x) <- value

## S4 method for signature 'AbstractCategories'
ids(x)

## S4 replacement method for signature 'Categories,ANY,ANY,ANY'
x[i, j, ...] <- value

## S4 replacement method for signature 'Categories'
ids(x) <- value

## S4 method for signature 'Categories'
values(x)

## S4 replacement method for signature 'Categories'
values(x) <- value

```

Arguments

...	additional arguments to [, ignored
data	For the constructor functions <code>Category</code> and <code>Categories</code> , you can either pass in attributes via ... or you can create the objects with a fully defined list representation of the objects via the <code>data</code> argument. See the examples.
x	For the attribute getters and setters, an object of class <code>Category</code> or <code>Categories</code>
i	For the [methods, just as with list extract methods
j	Invalid argument to [, but in the generic's signature
drop	Invalid argument to [, but in the generic's signature
value	For [<code><-</code> , the replacement <code>Category</code> to insert

Examples

```

cat.a <- Category(name="First", id=1, numeric_value=1, missing=FALSE)
cat.b <- Category(data=list(name="First", id=1, numeric_value=1, missing=FALSE))
identical(cat.a, cat.b)
cat.c <- Category(name="Second", id=2)
cats.1 <- Categories(cat.a, cat.c)

```

```
cats.2 <- Categories(data=list(cat.a, cat.c))
identical(cats.1, cats.2)
```

categoriesFromLevels *Convert a factor's levels into Crunch categories.*

Description

Crunch categorical variables have slightly richer metadata than R's factor variables. This function generates a list of category data from a factor's levels which can then be further manipulated in R before being imported into Crunch.

Usage

```
categoriesFromLevels(level_vect)
```

Arguments

level_vect A character vector containing the levels of a factor. Usually obtained by running `base::levels()`

Value

A list with each category levels id, name, numeric_value, and missingness.

Examples

```
categoriesFromLevels(levels(iris$Species))
```

changeCategoryID *Change the id of a category for a categorical variable*

Description

Changes the id of a category from an existing value to a new one. The variable can be a categorical, categorical array, or multiple response variable. The category changed will have the same numeric value and missing status as before. The one exception to this is if the numeric value is the same as the id, then the new numeric value will be the same as the new id.

Usage

```
changeCategoryID(variable, from, to)
```

Arguments

variable	the variable in a crunch dataset that will be changed (note: the variable must be categorical, categorical array, or multiple response)
from	the (old) id identifying the category you want to change
to	the (new) id for the category

Value

variable with category from and all associated data values mapped to id to

Examples

```
## Not run:
ds$country <- changeCategoryID(ds$country, 2, 6)

## End(Not run)
```

cleanseBatches	<i>Remove batches from a dataset</i>
----------------	--------------------------------------

Description

Sometimes append operations do not succeed, whether due to conflicts between the two datasets or other server-side issues. Failed appends can leave behind "error" status batch records, which can cause confusion. This function lets you delete batches that don't match the status or statuses you want to keep.

Usage

```
cleanseBatches(dataset, keep = c("imported", "appended"))
```

Arguments

dataset	CrunchDataset
keep	character the statuses that you want to keep. By default, batches that don't have either "imported" or "appended" status will be deleted.

Value

dataset with the specified batches removed.

collapseCategories	<i>Combine Categories in place</i>
--------------------	------------------------------------

Description

This function allows you to combine the categories of a variable without making a copy of the variable.

Usage

```
collapseCategories(var, from, to)
```

Arguments

var	A categorical Crunch variable
from	A character vector of categories you want to combine.
to	A character string with the destination category.

Value

the variable duly modified

See Also

[combine\(\)](#)

combine	<i>Combine categories or responses</i>
---------	--

Description

Crunch allows you to create a new categorical variable by combining the categories of another variable. For instance, you might want to recode a categorical variable with three categories small, medium, and large to one that has just small and large.

Usage

```
combine(variable, combinations = list(), ...)
```

Arguments

variable	Categorical, Categorical Array, or Multiple Response variable
combinations	list of named lists containing <ol style="list-style-type: none"> 1. "categories": category ids or names for categorical types, or for multiple response, "responses": subvariable names, aliases, or positional indices; 2. a "name" for the new category or response; and 3. optionally, other category ("missing", "numeric_value") or subvariable ("alias", "description") attributes. If combinations is omitted, the resulting variable will essentially be a copy (but see <code>copy()</code> for a more natural way to copy variables.
...	Additional variable metadata for the new derived variable

Value

A `VariableDefinition` that will create the new combined-category or -response derived variable. Categories/responses not referenced in combinations will be appended to the end of the combinations.

Examples

```
## Not run:
ds$fav_pet2 <- combine(ds$fav_pet, name="Pets (combined)",
  combinations=list(list(name="Mammals", categories=c("Cat", "Dog")),
    list(name="Reptiles", categories=c("Snake", "Lizard"))))
ds$pets_owned2 <- combine(ds$allpets, name="Pets owned (collapsed)",
  combinations=list(list(name="Mammals", responses=c("Cat", "Dog"))))

## End(Not run)
```

compareDatasets

Compare two datasets to see how they will append

Description

When one dataset is appended to another, variables and subvariables are matched on their aliases, and then categories for variables that have them are matched on category name. This function lines up the metadata between two datasets as the append operation will so that you can inspect how well the datasets will align before you do the append.

Usage

```
compareDatasets(A, B)
```

Arguments

A	CrunchDataset
B	CrunchDataset

Details

Calling `summary` on the return of this function will print an overview of places where the matching on variable alias and category name may lead to undesired outcomes, enabling you to alter one or both datasets to result in better alignment.

Value

An object of class `'compareDatasets'`, a list of three elements: (1) `'variables'`, a `data.frame` of variable metadata joined on alias; (2) `'categories'`, a list of `data.frames` of category metadata joined on category name, one for each variable with categories; and (3) `'subvariables'`, a list of `data.frames` of subvariable metadata joined on alias, one for each array variable.

Summary output reports on (1) variables that, when matched across datasets by alias, have different types; (2) variables that have the same name but don't match on alias; (3) for variables that match and have categories, any categories that have the same id but don't match on name; (4) for array variables that match, any subvariables that have the same name but don't match on alias; and (5) array variables that, after assembling the union of their subvariables, point to subvariables that belong to other arrays.

Examples

```
## Not run:
  comp <- compareDataset(ds1, ds2)
  summary(comp)

## End(Not run)
```

conditionalTransform *Conditional transformation*

Description

Create a new variable that has values when specific conditions are met. Conditions are specified using a series of formulas: the left-hand side is the condition that must be true (a `CrunchLogicalExpr`) and the right-hand side is where to get the value if the condition on the left-hand side is true. This is commonly a `Crunch` variable but may be a string or numeric value, depending on the type of variable you're constructing.

Usage

```
conditionalTransform(..., data, else_condition = NA, type = NULL,
  categories = NULL, formulas = NULL)
```

Arguments

<code>...</code>	a list of conditions to evaluate (as formulas, see Details) as well as other properties to pass to the new conditional variable (i.e. alias, description)
<code>data</code>	a Crunch dataset object to use
<code>else_condition</code>	a default value to use if none of the conditions are true (default: NA)
<code>type</code>	a character that is either "categorical", "text", "numeric" what type of output should be returned? If NULL, the type of the source variable will be used. (default: NULL) The source variables will be converted to this type if necessary.
<code>categories</code>	a vector of characters if <code>type="categorical"</code> , these are all of the categories that should be in the resulting variable, in the order they should be in the resulting variable or a set of Crunch categories.
<code>formulas</code>	a list of conditions to evaluate (as formulas, see Details). If specified, <code>...</code> must not contain other formulas specifying conditions.

Details

The type of the new variable can depend on the type(s) of the source variable(s). By default (`type=NULL`), the type of the new variable will be the type of all of the source variables (that is, if all of the source variables are text, the new variable type will be text, if all of the source variables are categorical, the new variable will be categorical). If there are multiple types in the source variables, the result will be a text variable. The default behavior can be overridden by specifying `type = "categorical", "text", or "numeric"`.

`conditionalTransform` is similar to `makeCaseVariable`; however, `conditionalTransform` can use other Crunch variables as a source of a variable, whereas, `makeCaseVariable` can only use characters. This additional power comes at a cost: `makeCaseVariable` can be executed entirely on Crunch servers, so no data needs to be downloaded or uploaded to/from the local R session. `conditionalTransform` on the other hand will download the data necessary to construct the new variable.

Value

a Crunch VariableDefinition

Examples

```
## Not run:

ds$cat_opinion <- conditionalTransform(pet1 == 'Cat' ~ Opinion1,
                                       pet2 == 'Cat' ~ Opinion2,
                                       pet3 == 'Cat' ~ Opinion3,
                                       data = ds,
                                       name = "Opinion of Cats")

## End(Not run)
```

consent	<i>Give consent to do things that require permission</i>
---------	--

Description

Potentially destructive actions require that you confirm that you really want to do them. If you're running a script and you know that you want to perform those actions, you can preemptively provide consent.

Usage

```
consent()
```

```
with_consent(expr)
```

Arguments

expr	Code to evaluate with consent
------	-------------------------------

Value

consent returns an S3 class "contextManager" object, which you can use with with. with_consent evaluates its arguments inside the consent context.

See Also

[with-context-manager](#) [ContextManager](#)

Examples

```
## Not run:  
with(consent(), delete(ds))  
# Equivalent to:  
with_consent(delete(ds))  
  
## End(Not run)
```

ContextManager	<i>Context managers</i>
----------------	-------------------------

Description

Context managers

Usage

```
ContextManager(enter = function() { }, exit = function() { },
  error = NULL, as = NULL)
```

Arguments

enter	function to run before taking actions
exit	function to run after taking actions
error	optional function to run if an error is thrown
as	character optional way to specify a default name for assigning the return of the enter function.

Value

an S3 class "contextManager" object

See Also

with-context-manager

copyOrder

Copy the variable order from one dataset to another.

Description

Copy the variable order from one dataset to another.

Usage

```
copyOrder(source, target)
```

Arguments

source	the dataset you want to copy the order from
target	the dataset you want to copy the order to

Value

returns an object of class `VariableOrder` (which can be assigned to a dataset with `ordering`)

Examples

```
## Not run:
ordering(ds) <- copyOrder(ds1, ds)

## End(Not run)
```

copyVariable	<i>Copy a variable</i>
--------------	------------------------

Description

Makes a copy of a Crunch variable on the server.

Usage

```
copyVariable(x, deep = FALSE, ...)
```

```
copy(x, deep = FALSE, ...)
```

Arguments

x	a CrunchVariable to copy
deep	logical: should this be a deep copy, in which there is no dependence on the original variable, or a shallow one, in which the copy is more of a symbolic link? Default is FALSE, meaning symlink.
...	Additional metadata to give to the new variable. If not given, the new variable will have a name that is the same as the original but with " (copy)" appended, and its alias will be the old alias with "_copy" appended.

Details

Copies can be shallow (linked) or deep. Shallow copying is faster and is preferable unless a true hard copy is required. Shallow copies are effectively pointers to the original variable, and then you append data to the original variable or otherwise alter its values, the values in the copy automatically update. This linking may be desirable, but it comes with some limitations. First, you cannot edit the values of the copy independently of the original. Second, some attributes of the copy are immutable: of note, properties of categories cannot be altered independently in the copy, but you can alter Subvariable names and ordering within arrays.

Value

a VariableDefinition for the copied variable. Assign into a Dataset to make the copy happen.

```
createWithPreparedData
```

Upload a prepared data.frame with metadata to Crunch

Description

If you have manually created a Crunch dataset object with `prepareDataForCrunch()` this function allows you to upload it to the app.

Usage

```
createWithPreparedData(data, metadata = attr(data, "metadata"))
```

Arguments

<code>data</code>	a data.frame that meets the Crunch API specification, as returned by <code>prepareDataForCrunch()</code> , or a character path to a file or URL where such data has been written as CSV.
<code>metadata</code>	list of Crunch metadata that corresponds to data. Default is the "metadata" attribute of data, as returned by <code>prepareDataForCrunch</code> , or a character path to a file where such metadata has been written as JSON.

Value

A CrunchDataset.

```
crtabs
```

Crunch xtabs: Crosstab and otherwise aggregate variables in a Crunch Dataset

Description

Create a contingency table or other aggregation from cross-classifying variables in a CrunchDataset.

Usage

```
crtabs(formula, data, weight = crunch::weight(data), useNA = c("no",
  "ifany", "always"))
```

Arguments

<code>formula</code>	an object of class 'formula' object with the cross-classifying variables separated by '+' on the right side of the "~". If aggregating by functions other than counts, include the aggregation expression on the left-hand side. Compare to <code>stats::xtabs()</code> .
<code>data</code>	an object of class CrunchDataset

weight	a CrunchVariable that has been designated as a potential weight variable for data, or NULL for unweighted results. Default is the currently applied <code>weight</code> .
useNA	whether to include missing values in tabular results. See <code>base::table()</code> .

Value

an object of class `CrunchCube`

See Also

`weight()`

crunch	<i>Crunch.io: instant, visual, collaborative data analysis</i>
--------	--

Description

Crunch.io provides a cloud-based data store and analytic engine. It has a **web client** for interactive data exploration and visualization. The `crunch` package for R allows analysts to interact with and manipulate Crunch datasets from within R. Importantly, this allows technical researchers to collaborate naturally with team members, managers, and clients who prefer a point-and-click interface: because all connect to the same dataset in the cloud, there is no need to email files back and forth continually to share results.

See Also

To learn more about using the package, see `vignette("getting-started", package="crunch")`. To sign up for a Crunch.io account, visit <https://app.crunch.io/>.

crunch-cut	<i>Cut a numeric Crunch variable</i>
------------	--------------------------------------

Description

`crunch::cut()` is equivalent to `base::cut()` except that it operates on Crunch variables instead of in-memory R objects. The function takes a numeric variable and derives a new categorical variable from it based on the `breaks` argument. You can either break the variable into evenly spaced categories by specifying the number of breaks, or specify a numeric vector identifying the start and end point of each category. For example, specifying `breaks = 5` will break the numeric data into five evenly spaced portions while `breaks = c(1, 5, 10)` will recode the data into two groups based on whether the numeric vector falls between 1 and 5 or 5 and 10.

Usage

```
## S4 method for signature 'NumericVariable'
cut(x, breaks, labels = NULL, name,
    include.lowest = FALSE, right = TRUE, dig.lab = 3,
    ordered_result = FALSE, ...)
```

Arguments

x	A Crunch NumericVariable
breaks	Either a numeric vector of two or more unique cut points or a single number giving the number of intervals into which x is to be cut. If specifying cut points, values that are less than the smallest value in breaks or greater than the largest value in breaks will be marked missing in the resulting categorical variable.
labels	A character vector representing the labels for the levels of the resulting categories. The length of the labels argument should be the same as the number of categories, which is one fewer than the number of breaks. If not specified, labels are constructed using interval notation. For example, [1, 5) indicates that the category goes from 1 to 5. The bracket shape indicates whether the boundary value is included in the category, i.e. whether it is "closed". [1, 5) indicates that the interval includes (is closed on) 1 but does not include (is open on) 5. If labels = FALSE, simple integer codes are returned instead of a factor.
name	The name of the resulting Crunch variable as a character string.
include.lowest	logical, indicating if an x[i] equal to the lowest (or highest, for right = FALSE) breaks value should be included.
right	logical, indicating if the intervals should be closed on the right (and open on the left) or vice versa.
dig.lab	integer which is used when labels are not given. It determines the number of digits used in formatting the break numbers.
ordered_result	Ignored.
...	further arguments passed to makeCaseVariable

Value

a Crunch [VariableDefinition](#). Assign it into the dataset to create it as a derived variable on the server.

Examples

```
## Not run:
ds <- loadDataset("mtcars")
ds$cat_var <- cut(ds$mpg, breaks = c(10, 15, 20),
  labels = c("small", "medium"), name = "Fuel efficiency")
ds$age <- sample(1:100, 32)
ds$age4 <- cut(df$age, c(0, 30, 45, 65, 200),
  c("Youth", "Adult", "Middle-aged", "Elderly"),
  name = "Age (4 category)")

## End(Not run)
```

Description

Univariate statistics on Crunch objects

Usage

```
## S4 method for signature 'CrunchVariable'  
mean(x, ...)  
  
## S4 method for signature 'NumericVariable'  
mean(x, ...)  
  
## S4 method for signature 'CrunchVariable'  
sd(x, na.rm = FALSE)  
  
## S4 method for signature 'NumericVariable'  
sd(x, na.rm = FALSE)  
  
## S4 method for signature 'CrunchVariable'  
min(x, na.rm)  
  
## S4 method for signature 'NumericVariable'  
min(x, na.rm = FALSE)  
  
## S4 method for signature 'DatetimeVariable'  
min(x, na.rm = FALSE)  
  
## S4 method for signature 'CrunchVariable'  
max(x, na.rm)  
  
## S4 method for signature 'NumericVariable'  
max(x, na.rm = FALSE)  
  
## S4 method for signature 'DatetimeVariable'  
max(x, na.rm = FALSE)
```

Arguments

x	a NumericVariable, or for min and max, a NumericVariable or DatetimeVariable
...	additional arguments to summary statistic function
na.rm	logical: exclude missings?

See Also

[base::mean\(\)](#) [stats::sd\(\)](#) [stats::median\(\)](#) [base::min\(\)](#) [base::max\(\)](#)

crunchBox

Make a CrunchBox

Description

CrunchBoxes allow you to publish results to the world.

Usage

```
crunchBox(dataset, filters = crunch::filters(dataset), brand_colors,
  static_colors, category_color_lookup, ...)
```

```
CrunchBox(dataset, filters = crunch::filters(dataset), brand_colors,
  static_colors, category_color_lookup, ...)
```

Arguments

dataset	A CrunchDataset, potentially a selection of variables from it
filters	FilterCatalog, or NULL for no filters. Default all filters in your catalog, <code>filters(dataset)</code> .
brand_colors	an optional color vector of length 3 or less, or a named list with names 'primary', 'secondary', and 'message'. See "Details" for more about color specification.
static_colors	an optional vector of colors to use for categorical plots. Bars and lines are colored in the order of <code>static_colors</code> . See "Details" for more about color specification.
category_color_lookup	an optional list of category names to colors to use for that category, wherever it appears in the data. This allows you to always see a category displayed in a specific color. See "Details" for more about color specification.
...	additional metadata for the box, such as "title", "header", etc.

Details

In addition to specifying the variables and filters to include in your CrunchBox, you can provide custom color palettes. The arguments `brand_colors`, `static_colors`, and `category_color_lookup` allow you to provide color lists to use. Colors should be either a valid hexadecimal string representation, like "#fa1af1", or they may also be an R named color, such as "darkgreen".

Value

The URL to the newly created box.

See Also

[preCrunchBoxCheck\(\)](#) to provide guidance on what you're including in the

Examples

```
## Not run:
# Creating a CrunchBox with three variables
crunchBox(ds[c("var1", "var2", "var3")], title="New CrunchBox")

# Creating a CrunchBox changing primary, secondary, and message brand colors
crunchBox(ds[c("var1", "var2", "var3")],
          title="Branded CrunchBox",
          brand_colors = c("#ff0aa4", "#af17ff", "#260aff"))

# Creating a CrunchBox changing category-specific colors
crunchBox(ds[c("var1", "var2", "var3")],
          title="CrunchBox with category colors",
          category_color_lookup = list("agree" = "#ff0aa4",
                                       "disagree" = "#af17ff",
                                       "don't know" = "#260aff"))

## End(Not run)
```

CrunchDataFrame

CrunchDataFrame

Description

CrunchDataFrames are designed to mimic the ways that [data.frames](#) are used. They should be a drop-in replacement in many places where data.frames are used.

Usage

```
## S3 method for class 'CrunchDataFrame'
dim(x)

## S3 method for class 'CrunchDataFrame'
names(x)

## S3 method for class 'CrunchDataFrame'
x[i, j, drop = TRUE]

## S3 replacement method for class 'CrunchDataFrame'
x[i, j] <- value

## S3 method for class 'CrunchDataFrame'
x[[i]]

## S3 replacement method for class 'CrunchDataFrame'
x[[i]] <- value
```

```
## S3 method for class 'CrunchDataFrame'
x$i

## S3 replacement method for class 'CrunchDataFrame'
x$i <- value
```

Arguments

x	a CrunchDataFrame
i	indicators for rows (integers or logicals)
j	indicators for columns (names, integers, or logicals)
drop	logical. If TRUE the result is coerced to the lowest possible dimension. The default is to drop if only one column is left, but not to drop if only one row is left.
value	value to place (or replace) in the CrunchDataFrame

Details

CrunchDataFrames are generated not by downloading all of the variables from a dataset, but rather only the variables that are needed by subsequent functions. So, if you create a CrunchDataFrame, and then run a linear model using `lm()`, only the variables used by the linear model will be downloaded.

CrunchDataFrames can be altered (that is: adding more columns, removing columns, subsetting rows, etc.) with the same `[], [[],` and `$` syntax as `data.frames`.

CrunchDataset-class *Crunch Datasets*

Description

Crunch Datasets

CrunchGeography-class *Geography properties for crunch variables*

Description

Crunch stores geographic data as variable metadata. There are a number of functions that help access and change this metadata.

Usage

```
CrunchGeography(..., data = NULL)

## S4 method for signature 'CrunchVariable'
geo(x)

## S4 replacement method for signature 'CrunchVariable,CrunchGeography'
geo(x) <- value

## S4 replacement method for signature 'CrunchVariable,`NULL`'
geo(x) <- value

availableGeodata(x = getAPIRoot())
```

Arguments

...	for CrunchGeography, named arguments from which to construct a CrunchGeography: geodatum, feature_key, and match_field
data	for CrunchGeography, list of named arguments from which to construct a CrunchGeography: geodatum, feature_key, and match_field
x	a crunch variable
value	value of the geography property to set

Details

geo retrieves the geographic information associate with a variable. If there is geographic information it returns an object of class CrunchGeography otherwise it returns NULL.

CrunchGeography objects store geography metadata from a variable. There are three slots:

- geodatum an object of class CrunchGeodata which stores references to the Crunch-hosted (geotopo)json to use
- feature_key a character string representing the feature inside of the (geotopo)json which is used to match match_field (e.g. properties.name)
- match_field a character string representing the variable metadata information which is used to match feature_key to (e.g. name)

Value

geographic information of class CrunchGeography (NULL if there is none)

Examples

```
## Not run:
geo(ds$location)

geo(ds$location)$feature_key <- "properties.name"
geo(ds$location)$match_field <- "name"

## End(Not run)
```

CrunchVariable-class *Variables in Crunch*

Description

Variables are S4 objects. All inherit from the base class `CrunchVariable`.

Slots

`filter` either `NULL` or `CrunchLogicalExpr`
`tuple` `VariableTuple`

cube-computing *Work with CrunchCubes, MultitableResults, and TabBookResults*

Description

These functions provide an interface like `base::margin.table()` and `base::prop.table()` for the `CrunchCube` object. `CrunchCubes` contain richer metadata than standard R array objects, and they also conceal certain complexity in the data structures from the user. In particular, multiple-response variables are generally represented as single dimensions in result tables, but in the actual data, they may comprise two dimensions. These methods understand the subtleties in the `Crunch` data types and correctly compute margins and percentages off of them.

Usage

```
## S4 method for signature 'CrunchCube'
margin.table(x, margin = NULL)

## S4 method for signature 'CrunchCube'
prop.table(x, margin = NULL)

## S4 method for signature 'CrunchCube'
round(x, digits = 0)

## S4 method for signature 'CrunchCube'
bases(x, margin = NULL)

## S4 method for signature 'MultitableResult'
prop.table(x, margin = NULL)

## S4 method for signature 'TabBookResult'
prop.table(x, margin = NULL)

## S4 method for signature 'TabBookResult'
```

```
bases(x, margin = NULL)

## S4 method for signature 'MultitableResult'
bases(x, margin = NULL)
```

Arguments

x	a CrunchCube
margin	index, or vector of indices to generate margin for. See base::prop.table() . <code>bases()</code> accepts <code>0</code> as an additional valid value for margin, which yields the unweighted counts for the query.
digits	For round, the number of decimal places to round to. See base::round()

Details

These functions also generalize to `MultitableResults` and `TabBookResults`, which are returned from a `tabBook()` request. When called on one of those objects, they effectively apply over each `CrunchCube` contained in them.

`bases` is an additional method for `CrunchCubes`. When making weighted requests, `bases` allows you to access the unweighted counts for every cell in the resulting table (array). The `bases` function takes a "margin" argument to work like `margin.table`, or with `margin=0` gives all cell counts.

Value

When called on `CrunchCubes`, these functions return an array. Calling `prop.table` on a `MultitableResult` returns a list of `prop.tables` of the `CrunchCubes` it contains. Likewise, `prop.table` on a `TabBookResult` returns a list of lists of `prop.tables`.

See Also

[base::margin.table\(\)](#) [base::prop.table\(\)](#)

cube-methods

Methods on Cube objects

Description

These methods provide an array-like interface to the `CrunchCube` object.

Usage

```
## S4 method for signature 'CubeDims'
dimnames(x)

## S4 method for signature 'CubeDims'
dim(x)
```

```
## S4 method for signature 'CubeDims'  
is.na(x)  
  
## S4 method for signature 'CrunchCube'  
dimensions(x)  
  
## S4 replacement method for signature 'CrunchCube,CubeDims'  
dimensions(x) <- value  
  
## S4 method for signature 'CubeDims,ANY,ANY'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'CrunchCube'  
dim(x)  
  
## S4 method for signature 'CrunchCube'  
dimnames(x)  
  
## S4 method for signature 'CubeDims'  
variables(x)  
  
## S4 method for signature 'CrunchCube'  
measures(x)  
  
## S4 method for signature 'CrunchCube'  
variables(x)  
  
## S4 method for signature 'CrunchCube'  
names(x)  
  
## S4 method for signature 'CrunchCube'  
aliases(x)  
  
## S4 method for signature 'CrunchCube'  
descriptions(x)  
  
## S4 method for signature 'CrunchCube'  
types(x)  
  
## S4 method for signature 'CrunchCube'  
notes(x)
```

Arguments

x	a CrunchCube or its CubeDims component.
value	for dimensions<- a CubeDims object to overwrite a CrunchCube dimensions
i	used with [to extract a dimension
j	not used

... not used
 drop not used

Value

Generally, the same shape of result that each of these functions return when applied to an array object.

See Also

[cube-computing base::array](#)

cube-residuals	<i>Calculate standardized residuals from a CrunchCube</i>
----------------	---

Description

Standardized residuals, $(\text{observed} - \text{expected}) / \sqrt{V}$, where V is the residual cell variance (Agresti, 2007, section 2.4.5). Special care is taken for multiple-response variables which are in effect a series of separate tables where ‘not selected’ cells for each item are are hidden.

Usage

```
## S4 method for signature 'CrunchCube'
rstandard(model)
```

Arguments

model A CrunchCube representing a contingency table

Value

an array of standardized residuals or Z-scores from the hypothesis being tested. The default method is that the joint distributions of (weighted) counts are equal to the marginal distributions of the table.

References

Agresti, A. (2007) *An Introduction to Categorical Data Analysis, 2nd ed.*, New York: John Wiley & Sons. Page 38.

See Also

[stats::chisq.test](#)

dashboard	<i>View or set a dashboard URL</i>
-----------	------------------------------------

Description

You can designate a dashboard that will show when the dataset is loaded in the Crunch web app. This dashboard could be a Crunch Shiny ("Crunchy") app, a CrunchBox, an RMarkdown website or something else.

Usage

```
dashboard(x)

setDashboardURL(x, value)

dashboard(x) <- value
```

Arguments

x	CrunchDataset
value	For the setter, a URL (character) or NULL to unset the dashboard.

Value

The getter returns a URL (character) or NULL. The setter returns the dataset (x).

Examples

```
## Not run:
dashboard(ds) <- "https://shiny.crunch.io/example/"

## End(Not run)
```

dataset-extract	<i>Subset datasets and extract variables</i>
-----------------	--

Description

Subset datasets and extract variables

Usage

```

## S4 method for signature 'CrunchDataset,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchDataset,logical,missing'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'CrunchDataset,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchDataset,VariableGroup,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchDataset,VariableOrder,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchDataset,missing,ANY'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'CrunchDataset,CrunchLogicalExpr,missing'
x[i, j, ...,
  drop = FALSE]

## S4 method for signature 'CrunchDataset,CrunchLogicalExpr,ANY'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'CrunchDataset'
subset(x, ...)

## S4 method for signature 'CrunchDataset,ANY'
x[[i, ..., drop = FALSE]]

## S4 method for signature 'CrunchDataset,character'
x[[i, ..., drop = FALSE]]

## S4 method for signature 'CrunchDataset'
x$name

```

Arguments

x a `CrunchDataset`

i As with a `data.frame`, there are two cases:

1. if no other arguments are supplied (i.e `x[i]`), `i` provides for `as.list` extraction: columns of the dataset rather than rows. If `character`, identifies variables to extract based on their aliases (by default: `set options(crunch.namekey.dataset="name")` to use variable names); if numeric or logical, extracts variables accordingly.
2. If `j` is specified as either `x[i, j]` or `x[i,]`, `i` is an object of class `CrunchLogicalExpr` that will define a subset of rows.

j	columnar extraction, as described above
...	additional arguments
drop	logical: automatically simplify a 1-column Dataset to a Variable? Default is FALSE, and the TRUE option is in fact not implemented.
name	columnar extraction for \$

Value

[yields a Dataset; [[] and \$ return a Variable

dataset-owner	<i>Get and set the owner of a dataset</i>
---------------	---

Description

Get and set the owner of a dataset

Usage

```
## S4 method for signature 'CrunchDataset'
owner(x)

## S4 replacement method for signature 'CrunchDataset'
owner(x) <- value
```

Arguments

x	CrunchDataset
value	For the setter, either a URL (character) or a Crunch object with a self method. Users and Projects are valid objects to assign as dataset owners.

Value

The dataset.

dataset-to-R

as.data.frame method for CrunchDataset

Description

This method is defined principally so that you can use a `CrunchDataset` as a data argument to other R functions (such as `stats::lm()`) without needing to download the whole dataset. You can, however, choose to download a true `data.frame`.

Usage

```
## S3 method for class 'CrunchDataset'
as.data.frame(x, row.names = NULL, optional = FALSE,
  force = FALSE, categorical.mode = "factor", include.hidden = FALSE,
  row.order = NULL, ...)

## S3 method for class 'CrunchDataFrame'
as.data.frame(x, row.names = NULL,
  optional = FALSE, ...)
```

Arguments

<code>x</code>	a <code>CrunchDataset</code> or <code>CrunchDataFrame</code>
<code>row.names</code>	part of <code>as.data.frame</code> signature. Ignored.
<code>optional</code>	part of <code>as.data.frame</code> signature. Ignored.
<code>force</code>	logical: actually coerce the dataset to <code>data.frame</code> , or leave the columns as unevaluated promises. Default is <code>FALSE</code> .
<code>categorical.mode</code>	what mode should categoricals be pulled as? One of <code>factor</code> , <code>numeric</code> , <code>id</code> (default: <code>factor</code>)
<code>include.hidden</code>	logical: should hidden variables be included? (default: <code>FALSE</code>)
<code>row.order</code>	vector of indices. Which, and their order, of the rows of the dataset should be presented as (default: <code>NULL</code>). If <code>NULL</code> , then the <code>CrunchDataset</code> order will be used.
<code>...</code>	additional arguments passed to <code>as.data.frame</code> (default method).

Details

By default, the `as.data.frame` method for `CrunchDataset` does not return a `data.frame` but instead `CrunchDataFrame`, which behaves like a `data.frame` without bringing the whole dataset into memory. When you access the variables of a `CrunchDataFrame`, you get an R vector, rather than a `CrunchVariable`. This allows modeling functions that require select columns of a dataset to retrieve only those variables from the remote server, rather than pulling the entire dataset into local memory.

If you call `as.data.frame` on a `CrunchDataset` with `force = TRUE`, you will instead get a true `data.frame`. You can also get this `data.frame` by calling `as.data.frame` on a `CrunchDataFrame` (effectively calling `as.data.frame` on the dataset twice)

When a `data.frame` is returned, the function coerces `Crunch Variable` values into their R equivalents using the following rules:

- Numeric variables become numeric vectors
- Text variables become character vectors
- Datetime variables become either `Date` or `POSIXt` vectors
- Categorical variables become either factors with levels matching the `Crunch Variable`'s categories (the default), or, if `categorical.mode` is specified as "id" or "numeric", a numeric vector of category ids or numeric values, respectively
- Array variables (`Categorical Array`, `Multiple Response`) are decomposed into their constituent categorical subvariables. An array with three subvariables, for example, will result in three columns in the `data.frame`.

Column names in the `data.frame` are the variable/subvariable aliases.

Value

When called on a `CrunchDataset`, the method returns an object of class `CrunchDataFrame` unless `force = TRUE`, in which case the return is a `data.frame`. For `CrunchDataFrame`, the method returns a `data.frame`.

See Also

[as.vector\(\)](#)

dataset-update	<i>Update a variable or variables in a dataset</i>
----------------	--

Description

Update a variable or variables in a dataset

Usage

```
## S4 replacement method for signature 'CrunchDataset,character,missing,CrunchVariable'
x[[i]] <- value
```

```
## S4 replacement method for signature 'CrunchDataset,ANY,missing,CrunchVariable'
x[[i]] <- value
```

```
## S4 replacement method for signature 'CrunchDataset,character,missing,ANY'
x[[i]] <- value
```

```

## S4 replacement method for signature 'CrunchDataset,character,missing,CrunchLogicalExpr'
x[[
  i]] <- value

## S4 replacement method for signature 'CrunchDataset,ANY,ANY,ANY'
x[[i]] <- value

## S4 replacement method for signature 'CrunchDataset,character,missing,`NULL`'
x[[i]] <- value

## S4 replacement method for signature 'CrunchDataset,ANY,missing,`NULL`'
x[[i]] <- value

## S4 replacement method for signature 'CrunchDataset'
x$name <- value

## S4 replacement method for signature 'CrunchDataset,character,missing,CrunchGeography'
x[[i]] <- value

## S4 replacement method for signature 'CrunchDataset,ANY,missing,CrunchGeography'
x[[i]] <- value

## S4 replacement method for signature 'CrunchDataset,ANY,missing,list'
x[i, j] <- value

## S4 replacement method for signature 'CrunchDataset,CrunchExpr,ANY,ANY'
x[i, j] <- value

```

Arguments

x	a CrunchDataset
i	For [, a CrunchLogicalExpr, numeric, or logical vector defining a subset of the rows of x. For [[, see j for the as.list column subsetting.
value	replacement values to insert. These can be crunchExprs or R vectors of the corresponding type
name	like j but for \$
j	if character, identifies variables to extract based on their aliases (by default: set options(crunch.namekey.dataset="name") to use variable names); if numeric or logical, extracts variables accordingly. Note that this is the as.list extraction, columns of the dataset rather than rows.

Value

x, modified.

dataset-variables *Access a Dataset's Variables Catalog*

Description

Datasets contain collections of variables. For a few purposes, such as editing variables' metadata, it is helpful to access these variable catalogs more directly.

Usage

```
## S4 method for signature 'CrunchDataset'  
variables(x)  
  
## S4 replacement method for signature 'CrunchDataset,VariableCatalog'  
variables(x) <- value  
  
## S4 method for signature 'CrunchDataset'  
allVariables(x)  
  
## S4 replacement method for signature 'CrunchDataset,VariableCatalog'  
allVariables(x) <- value  
  
## S4 method for signature 'SearchResults'  
variables(x)
```

Arguments

x	a Dataset
value	For the setters, a VariableCatalog to assign.

Details

variables gives just the active variables in the dataset, while allVariables returns all variables, including hidden variables.

Value

Getters return VariableCatalog; setters return x duly modified.

DatasetOrder-class *Organize Datasets*

Description

A DatasetOrder object is a subclass of `list` that contains DatasetGroups. DatasetGroup objects contain a group name and an set of "entities", which can be dataset references or other nested DatasetGroups.

Slots

`group` character, the name of the DatasetGroup. In the constructor and more generally, this field can be referenced as "name" as well.

`entities` a character vector of dataset URLs, or a list containing a combination of dataset URLs and DatasetGroup objects.

`datasets` *Get the dataset catalog*

Description

Crunch datasets are associated with catalogs. A project catalog will have a set of datasets associated with it, as will a user or team. This function allows you to get or modify the datasets associated with a catalog.

Usage

```
datasets(x = getAPIRoot())
```

```
datasets(x) <- value
```

Arguments

`x` a ShojiObject, such as a CrunchProject. If omitted, the function will load the user's primary dataset catalog. #'

`value` CrunchDataset for the setter

Value

An object of class DatasetCatalog. The setter returns the project (or other object that contains a dataset catalog with the given dataset added to it (via changing its owner to be the specified object, `x`).

Examples

```
## Not run:
# Get the primary dataset catalog
mydatasets <- datasets()
# Can load a dataset from that
ds <- loadDataset(mydatasets[["Dataset name"]])
# Can use the same function to get the dataset catalog for a project
proj <- projects()[["Project name"]]
projdatasets <- datasets(proj)
# The assignment method lets you move a dataset to a project
datasets(proj) <- ds

## End(Not run)
```

dedupeOrder

Remove duplicated entities from an order/group

Description

This function recurses through a `ShojiOrder` or `OrderGroup` and removes any duplicate entities. As with `base::duplicated`, the first appearance of an entity is kept, and subsequent occurrences are marked as duplicated and removed. (Unlike `duplicated`, there is no option to reverse that order.) The first occurrence of an entity is determined by the function's recursion: within each group, nested groups are processed first, in order, and their nested groups are processed recursively. See the test suite, in `test-variable-order.R`, for an example that illustrates which entities are dropped as duplicate.

Usage

```
dedupeOrder(x)
```

Arguments

x VariableOrder, DatasetOrder, VariableGroup, or DatasetGroup

Value

x with duplicate entities removed.

See Also

`duplicates`, which when set to `FALSE` also calls this function.

`delete`*Delete a Crunch object from the server*

Description

These methods delete entities, notably Datasets and Variables within them, from the server. This action is permanent and cannot be undone, so it should not be done lightly. Consider instead using `archive` for datasets and `hide` for variables.

Usage

```
## S4 method for signature 'CrunchDataset'  
delete(x, ...)
```

```
## S4 method for signature 'Multitable'  
delete(x, ...)
```

```
## S4 method for signature 'CrunchProject'  
delete(x, ...)
```

```
## S4 method for signature 'ShojiObject'  
delete(x, ...)
```

```
## S4 method for signature 'ANY'  
delete(x, ...)
```

```
## S4 method for signature 'CrunchTeam'  
delete(x, ...)
```

```
## S4 method for signature 'CrunchVariable'  
delete(x, ...)
```

```
## S4 method for signature 'VariableTuple'  
delete(x, ...)
```

Arguments

<code>x</code>	a Crunch object
<code>...</code>	additional arguments, in the generic

Details

Deleting requires confirmation. In an interactive session, you will be asked to confirm. To avoid that prompt, or to delete objects from a non-interactive session, wrap the call in `with_consent()` to give your permission to delete.

See Also[hide deleteDataset](#)

deleteDataset	<i>Delete a dataset from the dataset list</i>
---------------	---

Description

This function lets you delete a dataset without first loading it. If you have a dataset that somehow is corrupted and won't load, you can delete it this way.

Usage

```
deleteDataset(x, ...)
```

Arguments

x	The name (character) of a dataset, its (numeric) position in the return of listDatasets() , or an object of class <code>CrunchDataset</code> . x can only be of length 1—this function is not vectorized (for your protection).
...	additional parameters passed to delete

Details

The function also works on `CrunchDataset` objects, just like [delete\(\)](#), which may be useful if you have loaded another package that masks the [delete\(\)](#) method.

Value

(Invisibly) the API response from deleting the dataset

See Also[delete](#)

deleteSubvariables *Delete subvariables from an array*

Description

Deleting variables requires confirmation. In an interactive session, you will be asked to confirm. To avoid that prompt, or to delete subvariables from a non-interactive session, wrap the call in [with_consent\(\)](#) to give your permission to delete.

Usage

```
deleteSubvariables(variable, to.delete)
```

```
deleteSubvariable(variable, to.delete)
```

Arguments

variable	the array variable
to.delete	aliases (following <code>crunch.namekey.dataset</code>) or indices of variables to delete.

Details

To delete the subvariables the function unbinds the array, deletes the subvariable, and then binds the remaining subvariables into a new array.

Value

a new version of variable without the indicated subvariables

deleteVariables *Delete Variables Within a Dataset*

Description

This function permanently deletes a variable from a dataset. For a non-destructive alternative see [hide\(\)](#).

Usage

```
deleteVariables(dataset, variables)
```

```
deleteVariable(dataset, variables)
```

Arguments

`dataset` the Dataset to modify
`variables` aliases (following `crunch.namekey.dataset`) or indices of variables to delete.

Details

In an interactive session, you will be prompted to confirm that you wish to delete the variable. To avoid that prompt, or to delete variables from a non-interactive session, wrap the call in `with_consent()` to give your permission to delete.

Value

(invisibly) dataset with the specified variables deleted

See Also

[hide](#)

`derivations` *Get or set a derived variable's expression*

Description

Get a derived variable's derivation formula as a `CrunchExpr` with `derivation(variable)`. Set (change) a derived variable's derivation with `derivation(variable) <- expression`.

Usage

```
## S4 method for signature 'CrunchVariable'
derivation(x)

## S4 replacement method for signature 'CrunchVariable,ANY'
derivation(x) <- value

## S4 replacement method for signature 'CrunchVariable,`NULL`'
derivation(x) <- value

## S4 method for signature 'CrunchVariable'
is.derived(x)

## S4 replacement method for signature 'CrunchVariable,logical'
is.derived(x) <- value
```

Arguments

x	a variable
value	a CrunchExpr to be used as the derivation (for the setter only) or NULL to integrate a derived variable. For is.derived, FALSE can be used to integrate a derived variable.

Details

To break a derivation link between a derived variable and the originating variable, set the derivation value of the derived variable to NULL with `derivation(variable) <- NULL`

`is.derived` can be used to see if a variable is derived or not. Additionally setting a derived variable's `is.derived` to FALSE will break the derivation link between two variables.

Value

a CrunchExpr of the derivation for `derivation`; a logical for `is.derived`; the variable given in `x` for `is.derived<-` returns

Examples

```
## Not run:

ds$derived_v1 <- ds$v1 + 5

derivation(ds$derived_v1)
# Crunch expression: v1 + 5

derivation(ds$derived_v1) <- ds$v1 + 10
derivation(ds$derived_v1)
# Crunch expression: v1 + 10

is.derived(ds$derived_v1)
# TRUE

# to integrate or instantiate the variable in place (remove the link between
# variable v1 and the derivation) you can:
derivation(ds$derived_v1) <- NULL

# after integrating, the derived variable is no longer derived.
is.derived(ds$derived_v1)
# FALSE

## End(Not run)
```

describe	<i>Name, alias, and description for Crunch objects</i>
----------	--

Description

Name, alias, and description for Crunch objects

Usage

```
## S4 method for signature 'CrunchDataset'  
name(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
name(x) <- value  
  
## S4 method for signature 'CrunchDataset'  
description(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
description(x) <- value  
  
## S4 method for signature 'CrunchDataset'  
startDate(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
startDate(x) <- value  
  
## S4 method for signature 'CrunchDataset'  
endDate(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
endDate(x) <- value  
  
## S4 method for signature 'CrunchDataset'  
id(x)  
  
## S4 method for signature 'CrunchDataset'  
notes(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
notes(x) <- value  
  
## S4 method for signature 'Geodata'  
description(x)  
  
## S4 replacement method for signature 'Multitable'  
name(x) <- value
```

```

## S4 method for signature 'ShojiObject'
name(x)

## S4 method for signature 'CrunchVariable'
name(x)

## S4 replacement method for signature 'CrunchVariable'
name(x) <- value

## S4 method for signature 'CrunchVariable'
description(x)

## S4 replacement method for signature 'CrunchVariable'
description(x) <- value

## S4 method for signature 'CrunchVariable'
alias(object)

## S4 replacement method for signature 'CrunchVariable'
alias(x) <- value

## S4 method for signature 'CrunchVariable'
notes(x)

## S4 replacement method for signature 'CrunchVariable'
notes(x) <- value

## S4 method for signature 'CrunchVariable'
digits(x)

## S4 replacement method for signature 'NumericVariable'
digits(x) <- value

## S4 replacement method for signature 'CrunchVariable'
digits(x) <- value

```

Arguments

x	a Dataset or Variable.
value	For the setters, a length-1 character vector to assign
object	Same as x but for the alias method, in order to match the generic from another package. Note that alias and digits are only defined for Variables.

Value

Getters return the character object in the specified slot; setters return x duly modified.

See Also

[Categories describe-catalog](#)

dichotomize	<i>Indicate how categories represent a dichotomized value</i>
-------------	---

Description

Multiple Response variables are essentially Categorical Arrays in which one or more categories are set as "selected". These methods allow you set that state.

Usage

```
## S4 method for signature 'Categories'
is.dichotomized(x)

## S4 method for signature 'Categories,numeric'
dichotomize(x, i)

## S4 method for signature 'Categories,logical'
dichotomize(x, i)

## S4 method for signature 'Categories,character'
dichotomize(x, i)

## S4 method for signature 'Categories'
undichotomize(x)

## S4 method for signature 'CategoricalVariable,ANY'
dichotomize(x, i)

## S4 method for signature 'CategoricalArrayVariable,ANY'
dichotomize(x, i)

## S4 method for signature 'CategoricalVariable'
undichotomize(x)

## S4 method for signature 'CategoricalArrayVariable'
undichotomize(x)
```

Arguments

x	Categories or a Variable subclass that has Categories
i	For the dichotomize methods, the numeric or logical indices of the categories to mark as "selected", or if character, the Category "names". Note that unlike some other categorical variable methods, numeric indices are positional, not with reference to category ids.

Details

dichotomize lets you specify which categories are "selected", while undichotomize strips that selection information. Dichotomize converts a Categorical Array to a Multiple Response, and undichotomize does the reverse.

Value

Categories or the Variable, (un)dichotomized accordingly

See Also

[describe-category](#)

dim-dataset

Dataset dimensions

Description

Dataset dimensions

Usage

```
## S4 method for signature 'CrunchDataset'  
dim(x)
```

```
## S4 method for signature 'CrunchDataset'  
ncol(x)
```

Arguments

x a Dataset

Value

integer vector of length 2, indicating the number of rows and non-hidden variables in the dataset. Array subvariables are excluded from the column count.

See Also

[base::dim\(\)](#)

dropRows	<i>Permanently delete rows from a dataset</i>
----------	---

Description

Permanently delete rows from a dataset

Usage

```
dropRows(dataset, expr)
```

Arguments

dataset	a CrunchDataset
expr	a CrunchLogicalExpr

Value

dataset without the rows indicated by expr

See Also

[exclusion](#) for a non-destructive way to suppress rows

Examples

```
## Not run:
ds <- dropRows(ds, ds$gender == "Male")

## End(Not run)
```

duplicated	<i>"duplicated" method for Crunch objects</i>
------------	---

Description

"duplicated" method for Crunch objects

Usage

```
## S4 method for signature 'CrunchVariable'
duplicated(x, incomparables = FALSE, ...)

## S4 method for signature 'CrunchExpr'
duplicated(x, incomparables = FALSE, ...)
```

Arguments

x	CrunchVariable or CrunchExpr
incomparables	Ignored
...	Ignored

Value

A CrunchLogicalExpr that evaluates TRUE for all repeated entries after the first occurrence of a value.

See Also

[base::duplicated\(\)](#)

embedCrunchBox

Get HTML for embedding a CrunchBox

Description

[crunchBox\(\)](#) returns a URL to the box data that it generates, but in order to view it in a CrunchBox or to embed it on a website, you'll need to translate that to the Box's public URL and wrap it in some HTML. This function takes a CrunchBox and returns the HTML which you can embed in a website.

Usage

```
embedCrunchBox(box, title = NULL, logo = NULL, ...)
```

Arguments

box	character URL of the box data, as returned by crunchBox()
title	character title for the Box, to appear above the iframe. Default is NULL, meaning no title shown
logo	character URL of a logo to show instead of a title. Default is NULL, meaning no logo shown. If both logo and title are provided, only the logo will be shown. Note also that logo must be a URL of a hosted image: it cannot be a path to a local file.
...	Additional arguments, not currently used.

Value

Prints the HTML markup to the screen and also returns it invisibly.

See Also

[crunchBox\(\)](#)

Examples

```
## Not run:  
box <- crunchBox(ds)  
embedCrunchBox(box, logo="//myco.example/img/logo_200px.png")  
  
## End(Not run)
```

exclusion

View and set exclusion filters

Description

Exclusion filters express logic that defines a set of rows that should be dropped from the dataset. The rows aren't permanently deleted—you can recover them at any time by removing the exclusion filter—but they are omitted from all views and calculations, as if they had been deleted.

Usage

```
exclusion(x)  
  
exclusion(x) <- value
```

Arguments

x	a Dataset
value	an object of class <code>CrunchLogicalExpr</code> , or <code>NULL</code>

Details

Note that exclusion filters work opposite from how "normal" filters work. That is, a regular filter expression defines the subset of rows to operate on: it says "keep these rows." An exclusion filter defines which rows to omit. Applying a filter expression as a query filter will have the opposite effect if applied as an exclusion. Indeed, applying it as both query filter and exclusion at the same time will result in 0 rows.

Value

exclusion returns a `CrunchFilter` if there is one, else `NULL`. The setter returns x with the filter set.

exportDataset	<i>Export a dataset to a file</i>
---------------	-----------------------------------

Description

This function allows you to write a CrunchDataset to a .csv or SPSS .sav file.

Usage

```
exportDataset(dataset, file, format = c("csv", "spss"),
  categorical = c("name", "id"), na = NULL, varlabel = c("name",
  "description"), ...)
```

```
## S4 method for signature 'CrunchDataset'
write.csv(x, ...)
```

Arguments

dataset	CrunchDataset, which may have been subsetted with a filter expression on the rows and a selection of variables on the columns.
file	character local filename to write to
format	character export format: currently supported values are "csv" and "spss".
categorical	character: export categorical values to CSV as category "name" (default) or "id". Ignored by the SPSS exporter.
na	Similar to the argument in <code>utils::write.table()</code> , 'na' lets you control how missing values are written into the CSV file. Supported values are: <ol style="list-style-type: none"> 1. NULL, the default, which means that categorical variables will have the category name or id as the value, and numeric, text, and datetime variables will have the missing reason string; 2. A string to use for missing values. 3. "" means that empty cells will be written for missing values for all types.
varlabel	For SPSS export, which Crunch metadata field should be used as variable labels? Default is "name", but "description" is another valid value.
...	additional options. See the API documentation. Currently supported boolean options include 'include_personal' for personal variables (default: FALSE) and 'prefix_subvariables' for SPSS format: whether to include the array variable's name in each of its subvariables "varlabels" (default: FALSE).
x	(for write.csv) CrunchDataset, which may have been subsetted with a filter expression on the rows and a selection of variables on the columns.

Value

Invisibly, file.

 expressions

Construct Crunch Expressions

Description

Crunch Expressions, i.e. `CrunchExpr` and `CrunchLogicalExpr`, encapsulate derivations of Crunch variables, which are only evaluated when passed to a function like `as.vector`. They allow you to compose functional expressions of variables and evaluate them against the server only when appropriate.

Usage

```
## S4 method for signature 'CrunchExpr'
!x

## S4 method for signature 'CategoricalVariable,character'
x %in% table

## S4 method for signature 'CategoricalVariable,factor'
x %in% table

## S4 method for signature 'TextVariable,character'
x %in% table

## S4 method for signature 'NumericVariable,numeric'
x %in% table

## S4 method for signature 'DatetimeVariable,Date'
x %in% table

## S4 method for signature 'DatetimeVariable,POSIXt'
x %in% table

## S4 method for signature 'DatetimeVariable,character'
x %in% table

## S4 method for signature 'CategoricalVariable,numeric'
x %in% table

## S4 method for signature 'CategoricalVariable,character'
e1 == e2

## S4 method for signature 'CategoricalVariable,factor'
e1 == e2

## S4 method for signature 'CategoricalVariable,character'
e1 != e2
```

```
## S4 method for signature 'CategoricalVariable,factor'
e1 != e2

## S4 method for signature 'CrunchVariable'
is.na(x)

bin(x)

rollup(x, resolution = rollupResolution(x))
```

Arguments

x	an input
table	For %in%. See base::match()
e1	an input
e2	an input
resolution	For rollup. Either NULL or a character in c("Y", "Q", "M", "W", "D", "h", "m", "s", "ms") indicating the unit of time at which a Datetime variable should be aggregated. If NULL, the server will determine an appropriate resolution based on the range of the data.

Value

Most functions return a `CrunchExpr` or `CrunchLogicalExpr`. `as.vector` returns an R vector.

expropriateUser	<i>Expropriate all Crunch objects from a user</i>
-----------------	---

Description

If you want to transfer all teams, projects, and datasets owned by one user to another you can with `expropriateUser`. To use `expropriateUser` you must be an account admin and be from the same account as the user who is being expropriated. This is useful if a user leaves your organization and you want to transfer all of the teams, projects, and datasets they own to someone else.

Usage

```
expropriateUser(from, to)
```

Arguments

from	a character of the email address of the user to expropriate from
to	a character of the email address of the user who should be the new owner

Details

Expropriating requires confirmation. In an interactive session, you will be asked to confirm. To avoid that prompt, or to expropriate datasets from a non-interactive session, wrap the call in `with_consent()` to give your permission to expropriate

Value

None

filter-catalog	<i>Get or set a dataset's filters</i>
----------------	---------------------------------------

Description

You can build and save filters in the Crunch web app, and these filters are stored in a `FilterCatalog`. This function allows you to retrieve and modify those filters.

Usage

```
## S4 method for signature 'CrunchDataset'  
filters(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
filters(x) <- value
```

Arguments

x	a <code>CrunchDataset</code>
value	for the setter, a <code>FilterCatalog</code>

Value

an object of class `FilterCatalog` containing references to `Filter` entities usable in the web application. (Setter returns the `Dataset`.)

flattenOrder	<i>Remove nesting of groups within an order/group</i>
--------------	---

Description

This function reduces a potentially nested order to its flattened representation, containing no nested groups. Entities are ordered in the result by their first appearance in the order object.

Usage

```
flattenOrder(x)
```

Arguments

x	VariableOrder, DatasetOrder, VariableGroup, or DatasetGroup; or a Crunch-Dataset or catalog that has an ordering property.
---	--

Value

x, or its order resource, flattened.

flipArrays	<i>Rearrange array subvariables</i>
------------	-------------------------------------

Description

Sometimes it is useful to group subvariables across arrays in order to compare them more easily. This function generates a set of derived views of common subvariables across arrays. Because they are derived, they share data with the underlying array variables, and they are thus automatically updated when new data is appended.

Usage

```
flipArrays(variables, suffix = "", flipped")
```

Arguments

variables	List of variables, a variable catalog, or a dataset subset containing the categorical array or multiple response variables you want to rearrange.
suffix	character string to append to the new variable names. Pass "" if you don't want it to append anything.

Value

A list of derived VariableDefinitions, one per unique subvariable name across all variables. Each variable in variables that contains this subvariable will appear as a subvariable in these new derived array definitions. Use [addVariables](#) to add these to your dataset.

Examples

```
## Not run:
ds <- addVariables(ds, flipArrays(ds[c("petloc", "petloc2")], suffix=", rearranged"))

## End(Not run)
```

 folder

Find and move variables to a new folder

Description

Find and move variables to a new folder

Usage

```
folder(variable)

folder(x) <- value
```

Arguments

variable	For folder, a Variable to find
x	For folder assignment, a Variable, selection of variables in a Dataset, or any other object that can be moved to a folder.
value	For assignment, a character "path" to the folder: either a vector of nested folder names or a single string with nested folders separated by a delimiter ("/" default)

Value

folder returns the path to the Variable. folder<- returns the x input, having been moved to the requested location.

See Also

[mv\(\)](#)

Examples

```
## Not run:
ds <- loadDataset("Example survey")
folder(ds$income) <- "Demographics/Economic"
folder(ds$income)
## [1] "Demographics" "Economic"

## End(Not run)
```

forkDataset	<i>Create a fork of a dataset</i>
-------------	-----------------------------------

Description

As with many other version control systems, in Crunch you can fork a dataset's revision history, effectively making a copy on which you can work independently of the original dataset. You can then merge those change back to the original dataset or keep working independently.

Usage

```
forkDataset(dataset, name = defaultForkName(dataset), draft = FALSE, ...)
```

Arguments

dataset	The CrunchDataset to fork
name	character name to give the fork. If omitted, one will be provided for you
draft	logical: Should the dataset be a draft, available only to editors? Default is FALSE.
...	Additional dataset metadata

Value

The new fork, a CrunchDataset.

fortify	<i>Fortify crunch objects for use with ggplot</i>
---------	---

Description

Fortify crunch objects for use with ggplot

Usage

```
fortify.CrunchDataFrame(model, data, ...)
```

```
fortify.CrunchDataset(model, data, ...)
```

Arguments

model	model or other R object to convert to data frame
data	original dataset, if needed
...	other arguments passed to methods

getTeams	<i>Retrieve your teams</i>
----------	----------------------------

Description

Retrieve your teams

Usage

```
getTeams()
```

Value

A TeamCatalog. Extract an individual team by name. Create a team by assigning in with a new name.

See Also

[teams](#)

grouped	<i>Get grouped or ungrouped OrderGroups</i>
---------	---

Description

"ungrouped" is an OrderGroup that contains all entities not found in groups at a given level of nesting.

Usage

```
grouped(order.obj)
```

```
ungrouped(order.obj)
```

Arguments

order.obj an subclass of ShojiOrder or OrderGroup

Value

For grouped(), an Order/Group, respectively, with "ungrouped" omitted. For ungrouped(), an OrderGroup subclass.

See Also

[VariableOrder](#)

hiddenVariables	<i>Show the names of a dataset's hidden variables</i>
-----------------	---

Description

Show the names of a dataset's hidden variables

Usage

```
hiddenVariables(dataset, key = namekey(dataset))
```

Arguments

dataset	the Dataset
key	the Variable attribute to return. Default is "alias", following <code>getOption("crunch.namekey.dataset")</code> .

Value

a vector of the names of Variables marked as hidden.

hide	<i>Hide and Unhide Variables</i>
------	----------------------------------

Description

Hide and Unhide Variables

Usage

```
## S4 method for signature 'CrunchVariable'
hide(x)

## S4 method for signature 'VariableCatalog'
hide(x)

## S4 method for signature 'CrunchVariable'
unhide(x)

## S4 method for signature 'VariableCatalog'
unhide(x)
```

Arguments

x	a Variable or subset of a VariableCatalog to hide or unhide
---	---

Value

(invisibly) the Variable or VariableCatalog, hidden or unhidden

See Also

[hideVariables](#)

hideVariables	<i>Hide and unhide variables within a dataset</i>
---------------	---

Description

Hide and unhide variables within a dataset

Usage

```
hideVariables(dataset, variables)
```

```
hiddenVariables(x) <- value
```

```
unhideVariables(dataset, variables)
```

Arguments

dataset	the Dataset to modify
variables	names or indices of variables to (un)hide
x	same as dataset, for hiddenVariables<-
value	same as variables, for hiddenVariables<-

Value

(invisibly) dataset with the specified variables (un)hidden

See Also

[hide](#)

`http-methods`*HTTP methods for communicating with the Crunch API*

Description

These methods let you communicate with the Crunch API, for more background see [Crunch Internals](#).

Usage`crGET(...)``crPUT(...)``crPATCH(...)``crPOST(...)``crDELETE(...)`**Arguments**

... see [crunchAPI](#) for details. `url` is the first named argument and is required; `body` is also required for PUT, PATCH, and POST.

Value

Depends on the response status of the HTTP request and any custom handlers.

`importMultitable`*Import a Multitable*

Description

Allows you to import a multitable from a different dataset

Usage`importMultitable(data, multitable, ...)`**Arguments**

`data` a `CrunchDataset` in which to create the multitable

`multitable` an object of class `Multitable` that you want copied to the new dataset

... Additional multitable attributes to set. Options include `name` and `is_public`.

Value

An object of class Multitable

Examples

```
## Not run:
m <- newMultitable(~ gender + age4 + marstat, data=ds)
copied_m <- importMultitable(another_ds, m)
name(copied_m) # [1] "gender + age4 + marstat"

## End(Not run)
```

Insertions-class

Insert categories in transformations

Description

Insertions allow you to insert new categories into a categorical-like response on a variable's [transformations](#).

Usage

```
Insertions(..., data = NULL)

Insertion(...)

.Insertion(..., data = NULL)

## S4 replacement method for signature 'Insertion'
anchor(x) <- value

## S4 replacement method for signature 'Subtotal'
anchor(x) <- value

## S4 replacement method for signature 'Heading'
anchor(x) <- value

## S4 replacement method for signature 'Insertion,ANY'
subtotals(x) <- value

## S4 replacement method for signature 'Insertion'
arguments(x) <- value

## S4 replacement method for signature 'Subtotal'
arguments(x) <- value

## S4 replacement method for signature 'Heading'
```



```

arguments(x) <- value

## S4 method for signature 'Insertion'
arguments(x)

## S4 method for signature 'Subtotal'
arguments(x, var_categories)

## S4 method for signature 'Heading'
arguments(x)

## S4 method for signature 'Insertion'
anchor(x)

## S4 method for signature 'Subtotal'
anchor(x, var_categories)

## S4 method for signature 'Heading'
anchor(x, var_categories)

## S4 method for signature 'Insertion'
func(x)

## S4 method for signature 'Subtotal'
func(x)

## S4 method for signature 'Heading'
func(x)

## S4 method for signature 'Insertions'
anchors(x)

## S4 method for signature 'Insertions'
funcs(x)

```

Arguments

...	additional arguments to [, ignored
data	For the constructor functions Insertion and Insertions, you can either pass in attributes via ... or you can create the objects with a fully defined list representation of the objects via the data argument. See the examples.
x	For the attribute getters and setters, an object of class Insertion or Insertions
value	For [<code><-</code> , the replacement Insertion to insert
var_categories	categories (from <code>categories()</code>) to used by the arguments and anchor methods when needed to translate between category names and category ids.

Working with Insertions

Insertions are used to add information about a variable or CrunchCube that extends the data in the dataset but does not alter it. This new data includes: aggregations like [subtotals](#) that sum the count of more than one category together or [headings](#) which can be added between categories.

Insertions objects are containers for individual Insertion objects. The individual Insertions contain all the information needed to calculate, apply, and display insertions to CrunchCubes and categorical variables.

An Insertion must have two properties:

- anchor - which is the id of the category the insertion should follow
- name - the string to display

Additionally, Insertions may also have the following two properties (though if they have one, they must have the other):

- function - the function to use to aggregate (e.g. "subtotal")
- args - the category ids to use as operands to the function above.

Although it is possible to make both subtotals and headings using Insertion alone, it is much easier and safer to use the functions [Subtotal\(\)](#) and [Heading\(\)](#) instead. Not only are they more transparent, they also are quicker to type, accept both category names as well as ids, and have easier to remember argument names.

interactVariables *Create a variable by interacting categorical variables*

Description

interactVariables takes two or more variables and creates a new one that is the cartesian product expansion of their unique values. For example, if we cross ethnicity (with 2 categories) and race (with 4 categories), the new variable would have 8 valid categories (e.g. black:hispanic, white:hispanic, black:non-hispanic, etc.) and 7 categories where at least one of the variables is missing (e.g. white:No Data).

Usage

```
interactVariables(..., name, sep = ":")
```

Arguments

...	a sequence of categorical variables to make an interaction from as well as other properties to pass about the case variable (i.e. alias, description)
name	a character to use as the name for the interaction variable
sep	a character to separate the values of the individual variables (default: :)

Value

A [VariableDefinition](#) that creates the new interaction variable.

Examples

```
## Not run:
ds$ethn_race <- interactVariables(ds$ethnicity, ds$race, name="Interaction of ethnicity and race")

## End(Not run)
```

is-na-categories *is.na for Categories*

Description

Crunch categorical variables allow you to set multiple categories as missing. For instance, you might have "not answered" and "doesn't know" both coded as missing. This function returns a logical vector of all dataset entries that fall into any of the missing categories. It also allows you to append additional categories to the list of missing categories using the setter.

Usage

```
## S4 method for signature 'Categories'
is.na(x)

## S4 method for signature 'Categories'
is.na(x)

## S4 replacement method for signature 'Categories,character'
is.na(x) <- value

## S4 replacement method for signature 'Categories,logical'
is.na(x) <- value

## S4 method for signature 'Category'
is.na(x)

## S4 replacement method for signature 'Category,logical'
is.na(x) <- value
```

Arguments

x	Categories or a single Category
value	To change the missingness of categories, supply either: <ol style="list-style-type: none"> 1. a logical vector of equal length of the categories (or length 1 for the Category method); or 2. the names of the categories to mark as missing. If supplying the latter, any categories already indicated as missing will remain missing.

Value

Getters return logical, a named vector in the case of the `Categories` method; setters return `x` duly modified.

is-public	<i>View and modify "public" attribute</i>
-----------	---

Description

View and modify whether all dataset viewers have access to the dataset. This will return `FALSE` if the dataset is in draft.

Usage

```
## S4 method for signature 'CrunchFilter'
is.public(x)

## S4 replacement method for signature 'CrunchFilter'
is.public(x) <- value

## S4 method for signature 'MultitableCatalog'
is.public(x)

## S4 replacement method for signature 'MultitableCatalog'
is.public(x) <- value

## S4 method for signature 'Multitable'
is.public(x)

## S4 replacement method for signature 'Multitable'
is.public(x) <- value
```

Arguments

<code>x</code>	a Crunch object
<code>value</code>	an attribute to set

Value

For `is.public`, a logical value for whether the object is flagged as shared with all dataset viewers. (Its setter thus takes a logical value as well.) Catalogs of datasets return a vector of logicals corresponding to the length of the catalog, while entities return a single value.

```
is-selected-categories
  is.selected for Categories
```

Description

Crunch Multiple Response variables identify one or more categories as "selected". These methods allow you to get or set which categories should indicate a selection.

Usage

```
## S4 method for signature 'Categories'
is.selected(x)

## S4 replacement method for signature 'Categories'
is.selected(x) <- value

## S4 replacement method for signature 'Category'
is.selected(x) <- value
```

Arguments

x	Categories or a single Category
value	A logical vector indicating whether the category should be selected. For a single category the value should be either TRUE or FALSE to change the selection status for a Categories object, supply a logical vector which is the same length as the number of categories.

Value

Getters return a logical vector indicating selection status. Setters return the Categories or Category object, duly modified.

```
is.archived, DatasetCatalog-method
  Get and set "archived" and "published" status of a dataset
```

Description

"Archived" datasets are excluded from some views. "Draft" datasets are visible only to editors, while published datasets are available to all viewers. A dataset can either be published or in draft, but not both. These properties are accessed and set with the "is" methods. You can also set the properties by assigning into the function. The verb functions archive and publish are alternate versions of the setters.

Usage

```
## S4 method for signature 'DatasetCatalog'
is.archived(x)

## S4 method for signature 'DatasetCatalog'
is.draft(x)

## S4 method for signature 'DatasetCatalog'
is.published(x)

## S4 replacement method for signature 'DatasetCatalog,logical'
is.archived(x) <- value

## S4 replacement method for signature 'DatasetCatalog,logical'
is.draft(x) <- value

## S4 replacement method for signature 'DatasetCatalog,logical'
is.published(x) <- value

## S4 method for signature 'CrunchDataset'
is.archived(x)

## S4 method for signature 'CrunchDataset'
is.draft(x)

## S4 method for signature 'CrunchDataset'
is.published(x)

## S4 replacement method for signature 'CrunchDataset,logical'
is.archived(x) <- value

archive(x)

## S4 replacement method for signature 'CrunchDataset,logical'
is.draft(x) <- value

## S4 replacement method for signature 'CrunchDataset,logical'
is.published(x) <- value

publish(x)
```

Arguments

x	CrunchDataset
value	logical

Value

For the getters, the logical value of whether the dataset is archived, in draft mode, or published, where draft and published are inverses. The setters return the dataset.

Examples

```
## Not run:
ds <- loadDataset("mtcars")
is.draft(ds) # FALSE
is.published(ds) # TRUE
identical(is.draft(ds), !is.published(ds))
# Can make a dataset a "draft" by:
is.draft(ds) <- TRUE
is.published(ds) # FALSE
# Could also have set is.published(ds) <- FALSE
# Now, can go the other way by setting is.draft, is.published, or:
ds <- publish(ds)
is.published(ds) # TRUE

is.archived(ds) # FALSE
is.archived(ds) <- TRUE
is.archived(ds) # TRUE
# Could have achieved the same effect by:
ds <- archive(ds)

## End(Not run)
```

is.dataset

Test whether a Crunch object belongs to a class

Description

Test whether a Crunch object belongs to a class

Usage

```
is.dataset(x)
```

```
is.CrunchExpr(x)
```

```
is.Expr(x)
```

```
is.Geodata(x)
```

```
is.shoji(x)
```

```
is.variable(x)
```

```
is.Numeric(x)
is.Categorical(x)
is.Text(x)
is.Datetime(x)
is.Multiple(x)
is.MR(x)
is.MultipleResponse(x)
is.CA(x)
is.Array(x)
is.CategoricalArray(x)
```

Arguments

x an object

Value

logical

is.editor	<i>Read and set edit privileges</i>
-----------	-------------------------------------

Description

Read and set edit privileges

Usage

```
## S4 method for signature 'MemberCatalog'
is.editor(x)

## S4 replacement method for signature 'MemberCatalog,logical'
is.editor(x) <- value

## S4 method for signature 'PermissionCatalog'
is.editor(x)

## S4 method for signature 'PermissionTuple'
is.editor(x)
```


Arguments

x	PermissionCatalog or MemberCatalog
value	For the setter, logical: should the indicated users be allowed to edit the associated object?

Value

is.editor returns a logical vector corresponding to whether the users in the catalog can edit or not.is.editor<- returns the catalog, modified.

joinDatasets	<i>Add columns from one dataset to another, joining on a key</i>
--------------	--

Description

As [merge](#) does for data.frames, this function takes two datasets, matches rows based on a specified key variable, and adds columns from one to the other.

Usage

```
joinDatasets(x, y, by = intersect(names(x), names(y)), by.x = by,
  by.y = by, all = FALSE, all.x = TRUE, all.y = FALSE, copy = TRUE)

extendDataset(x, y, by = intersect(names(x), names(y)), by.x = by,
  by.y = by, all = FALSE, all.x = TRUE, all.y = FALSE, ...)

## S3 method for class 'CrunchDataset'
merge(x, y, by = intersect(names(x), names(y)),
  by.x = by, by.y = by, all = FALSE, all.x = TRUE, all.y = FALSE, ...)
```

Arguments

x	CrunchDataset to add data to
y	CrunchDataset to copy data from. May be filtered by rows and/or columns.
by	character, optional shortcut for specifying by.x and by.y by alias if the key variables have the same alias in both datasets.
by.x	CrunchVariable in x on which to join, or the alias (following crunch.namekey.dataset) of a variable. Must be type numeric or text and have all unique, non-missing values.
by.y	CrunchVariable in y on which to join, or the alias (following crunch.namekey.dataset) of a variable. Must be type numeric or text and have all unique, non-missing values.
all	logical: should all rows in x and y be kept, i.e. a "full outer" join? Only FALSE is currently supported.

all.x	logical: should all rows in x be kept, i.e. a "left outer" join? Only TRUE is currently supported.
all.y	logical: should all rows in y be kept, i.e. a "right outer" join? Only FALSE is currently supported.
copy	logical: make a virtual or materialized join. Default is TRUE, which means materialized. Virtual joins are experimental and not advised.
...	additional arguments, ignored

Value

x extended by the columns of y, matched on the "by" variables.

listDatasets	<i>Show the names of all Crunch datasets associated with a catalog</i>
--------------	--

Description

Show the names of all Crunch datasets associated with a catalog

Usage

```
listDatasets(kind = c("active", "all", "archived"), project = NULL,
             refresh = FALSE)
```

Arguments

kind	character specifying whether to look in active, archived, or all datasets. Default is "active", i.e. non-archived.
project	CrunchProject entity, character name of a project, or NULL, the default. If a Project entity or reference is supplied, the function will display datasets from that Project's datasets. If NULL, the primary dataset catalog for the user will be used.
refresh	logical: should the function check the Crunch API for new datasets? Default is FALSE.

Value

Character vector of dataset names, each of which would be a valid input for [loadDataset\(\)](#)

loadDataset	<i>Load a Crunch Dataset</i>
-------------	------------------------------

Description

Load a Crunch Dataset

Usage

```
loadDataset(dataset, kind = c("active", "all", "archived"), project = NULL,  
            refresh = FALSE)
```

Arguments

dataset	character, the name of a Crunch dataset that you have access to, or a DatasetTuple.
kind	character specifying whether to look in active, archived, or all datasets. Default is "active", i.e. non-archived.
project	CrunchProject entity, character name of a project, or NULL, the default. If a Project entity or reference is supplied, the function will display datasets from that Project's datasets. If NULL, the primary dataset catalog for the user will be used.
refresh	logical: should the function check the Crunch API for new datasets? Default is FALSE.

Value

An object of class CrunchDataset

Examples

```
## Not run:  
dsName <- listDatasets()[1]  
ds <- loadDatasets(dsName)  
  
## End(Not run)
```

locateEntity	<i>Find an entity in an order object</i>
--------------	--

Description

Find an entity in an order object

Usage

```
locateEntity(x, ord)
```

Arguments

x	Variable or Dataset, depending on the type of order, or URL for it
ord	ShojiOrder (VariableOrder or DatasetOrder)

Value

If x is found in ord, a character vector of group names that provide the "path" to the entity. The length of the vector corresponds to the depth of nesting. If not found, NA is returned

lock	<i>Lock and unlock a dataset for editing</i>
------	--

Description

Crunch allows a single active editor. If you have edit privileges but are not currently editing the dataset, you must unlock the dataset before making changes. You may then lock the dataset when you're done editing.

Usage

```
lock(dataset)

unlock(dataset)
```

Arguments

dataset	a CrunchDataset
---------	-----------------

Value

dataset, invisibly, after having set the current editor.

login	<i>Authenticate with the Crunch API</i>
-------	---

Description

Note that you can store your Crunch account info in your .Rprofile under crunch.email and crunch.pw for convenience. If you do so, you can simply login() to authenticate. For running batch jobs, this could be particularly useful. However, be warned that storing your password in a plain text file such as .Rprofile is a security risk (though perhaps less so than in every .R script you write), and we cannot officially recommend that you do so.

Usage

```
login(email = envOrOption("crunch.email"),
      password = envOrOption("crunch.pw"), ...)
```

Arguments

email	the email address associated with the user's Crunch account
password	the password associated with the user's Crunch account
...	additional parameters passed in the authentication. Not currently supported by the Crunch API.

Details

Additionally, your email and password can be stored in and read from the environmental variables R_CRUNCH_EMAIL and R_CRUNCH_PW respectively.

If a password is not supplied (or, if no arguments are supplied and only the `crunch.email` is specified in `.Rprofile`), and you are in an interactive session, you will be prompted to enter your password. At present, this is the most secure practice as your password is not stored locally.

logout	<i>Kill the active Crunch session</i>
--------	---------------------------------------

Description

Kill the active Crunch session

Usage

```
logout()
```

makeArray	<i>Make a Categorical Array or Multiple Response variable</i>
-----------	---

Description

Array variables are composed of a set of "subvariables" bound together for display in the app. For example, you might have a set of survey questions that ask how the respondent would rate a tv show from 1-5. Array variables allow you to display all of their ratings in a compact table rather than a set of distinct variables.

Usage

```
makeArray(subvariables, name, ...)

makeMR(subvariables, name, selections, ...)

deriveArray(subvariables, name, selections, ...)
```

Arguments

subvariables	a list of Variable objects to bind together, or a Dataset subset which contains only the Variables to bind.
name	character, the name that the new Categorical Array variable should have.
...	Optional additional attributes to set on the new variable.
selections	character, for makeMR and deriveArray the names of the categories to mark as the dichotomous selections. Required for makeMR; optional for deriveArray; ignored in makeArray.

Value

A VariableDefinition that when added to a Dataset will create the categorical-array or multiple-response variable. deriveArray will make a derived array expression (or a derived multiple response expression if selections are supplied), while makeArray and makeMR return an expression that "binds" variables together, removing them from independent existence.

makeCaseVariable	<i>Make a case variable</i>
------------------	-----------------------------

Description

The makeCaseVariable function derives a variable using values from other variables. These are evaluated in the order they are supplied in the list as the cases argument (they proceed in an IF, ELSE IF, ELSE IF, ..., ELSE fashion); the first one that matches selects the corresponding value from the case list.

Usage

```
makeCaseVariable(..., cases, data = NULL, name)
```

Arguments

...	a sequence of named expressions to use as cases as well as other properties to pass about the case variable (i.e. alias, description)
cases	a list of lists with each case condition to use each must include at least a name and an expression element. Cases may also include missing (logical) and numeric_value (numeric).
data	(optional) a crunch dataset to use. Specifying this means you don't have to put dataset\$ in front of each variable name.
name	a character to use as the name of the case variable to create

Details

There are two ways to specify cases, but you must pick only one (note these two will produce the same case variable):

1. When you just want to specify conditions, you can use named conditions: `makeCaseVariable(case1=ds$v1 == 1, ca`
2. You can also use the `cases` argument, which is useful when you want to provide category ids, numeric values, or missingness: `makeCaseVariable(cases=list(list(expression=ds$v1 == 1, name="case1"),`

Rows in the dataset that do not match any of the provided "cases" will be assigned to an "else" category. By default, Crunch will use the system missing "No Data" category. Alternatively, you can provide an else case definition for these rows by including as the last "case" you provide one with its expression set to the string "else". See the examples for details.

Value

A [VariableDefinition](#) that will create the new case variable when assigned into the Dataset.

Examples

```
## Not run:
makeCaseVariable(case1=ds$v1 == 1, case2=ds$v2 == 2, name="new case")
makeCaseVariable(cases=list(list(expression=ds$v1 == 1, name="case1"),
                             list(expression=ds$v2 == 2, name="case2")),
                 name="new case")

# different ways to specify else cases
makeCaseVariable(cases=list(list(expression=ds$v1 == 1, name="case1"),
                             list(expression=ds$v2 == 2, name="case2"),
                             list(expression="else", name="other")),
                 name="new case")
makeCaseVariable(case1=ds$v1 == 1, case2=ds$v2 == 2, other="else", name="new case")

# the dataset can be specified with data=
makeCaseVariable(case1=v1 == 1, case2=v2 == 2, data=ds, name="new case")

## End(Not run)
```

makeWeight

Generate a weight variable

Description

This function allows you to generate a weight variable by supplying a set of categorical variables and the target distribution for each of the variables' categories. Weights are computed by iteratively 'raking' conditional 'cells' to the provided marginal targets.

Usage

```
makeWeight(..., name)
```

Arguments

...	A series of expressions of the form <code>variable ~ target_weights</code> . The variable must be a categorical Crunch variable, and the target weights must be a numeric vector whose length should be equal to the number of categories contained in the variable, and whose sum is equal to 100 or 1. If you supply fewer target weights than there are categories <code>makeWeight</code> will pad the target weight vector with 0s.
name	The name of the resulting variable

Details

For instance, if you wanted to create a weight variable which equally weighted four categories stored in `ds$var` you would call `ds$weight1 <- makeWeight(ds$var ~ c(25, 25, 25, 25), name = "weight1")`. Note that `makeWeight` returns a `VariableDefinition`, an expression that when assigned into your Dataset becomes a derived variable. This does not on its own set the new variable as "the weight" for your dataset. To set that attribute, use `weight()`. Alternatively, you can also create the variable and set the weight attribute in one step with `weight(ds) <- makeWeight(ds$var ~ c(25, 25, 25, 25), name = "weight1")`

Value

A crunch `VariableDefinition()` of the weight variable

See Also

`weight<-()`; `settings()` for the "default weight" for other dataset viewers.

Examples

```
## Not run:
mtcars$cyl <- as.factor(mtcars$cyl)
mtcars$gear <- as.factor(mtcars$gear)
ds <- newDataset(mtcars)
# Create a new "raked" variable
ds$weight <- makeWeight(ds$cyl ~ c(30, 30, 40, 0),
  ds$gear ~ c(20, 20, 60, 0), name = "weight")
summary(ds$weight)
# ds$weight is not "the weight" for the dataset unless you set it:
weight(ds) <- ds$weight
# Or, you can create the variable and set as weight in one step:
weight(ds) <- makeWeight(ds$var ~ c(25, 25, 25, 25), name = "weight2")

## End(Not run)
```

matchCatToFeat	<i>Match categories with features from geodata</i>
----------------	--

Description

Match categories with features from geodata

Usage

```
matchCatToFeat(categories, all_features = availableGeodataFeatures())
```

Arguments

categories	a vector of categories to match
all_features	a dataframe of all available geodata features. (default: downloaded from Crunch servers)

Value

geodatum to associate with the variable that produced categories

me	<i>My user entity</i>
----	-----------------------

Description

Get the user entity of the currently authenticated user.

Usage

```
me()
```

Value

A UserEntity

```
members<- ,CrunchTeam,MemberCatalog-method
```

Teams

Description

Teams contain users and datasets. You can share a dataset with a group of users by sharing the dataset with a team. You can also share a set of datasets with a user all at once by adding the user to a team that contains those datasets.

Usage

```
## S4 replacement method for signature 'CrunchTeam,MemberCatalog'
members(x) <- value

## S4 replacement method for signature 'CrunchTeam,character'
members(x) <- value

## S4 method for signature 'CrunchProject'
members(x)

## S4 replacement method for signature 'CrunchProject,MemberCatalog'
members(x) <- value

## S4 replacement method for signature 'CrunchProject,character'
members(x) <- value

## S4 method for signature 'CrunchTeam'
members(x)
```

Arguments

x	a <i>CrunchTeam</i>
value	for <i>members<-</i> , a character vector of emails or URLs of users to add to the team.

Details

These methods allow you to work with teams. Find your teams with the [getTeams\(\)](#) function, which returns your *TeamCatalog*. You can extract an individual team by name, or create a team by assigning into the function. To create a team by assignment, assign a list to `teams("myteam") <- value_list`, the `value_list` can either empty (to just create a team with that name), or can contain a "members" element with the emails or URLs of users to add to the team. Users can be also be added later with the *members<-* method.

Value

members returns a *MemberCatalog*, which has references to the users that are members of the team. *members<-* returns `x` with the given users added to the members catalog.

See Also[getTeams](#)

merge*Merge a CrunchDataFrame*

Description

merging a `CrunchDataFrame` with a local dataframe is useful in situations where you have new information in your local R session that you want to connect with Crunch data. For example, for making plots with Crunch and non-Crunch data. It produces a hybrid `CrunchDataFrame` that has the local data attached to it, but like normal `CrunchDataFrames` it is still judicious about downloading data from the server only when it is needed.

Usage

```
## S3 method for class 'CrunchDataFrame'
merge(x, y, by = intersect(names(x), names(y)),
      by.x = by, by.y = by, sort = c("x", "y"), ...)
```

Arguments

<code>x</code>	a <code>CrunchDataFrame</code>
<code>y</code>	a standard <code>data.frame</code>
<code>by</code>	name of the variable to match in both data sources (default: the intersection of the names of <code>x</code> and <code>y</code>)
<code>by.x</code>	name of the variable to match in <code>x</code>
<code>by.y</code>	name of the variable to match in <code>y</code>
<code>sort</code>	character, either "x" or "y" (default: "x"). Which of the inputs should be used for the output order. Unlike <code>merge.data.frame</code> , <code>merge.CrunchDataFrame</code> will not re-sort the order of the output. It will use the order of either <code>x</code> or <code>y</code> .
<code>...</code>	ignored

Details

Merging a `CrunchDataFrame` with a local dataframe does not allow specifying all rows from both sources. Instead, the resulting `CrunchDataFrame` will include all of the rows in whichever source is used for sorting (`x` or `y`). So if you specify `sort="x"` (the default) all rows of `x` will be present but rows in `y` that do not match with rows in `x` will not be present.

Merging a `CrunchDataFrame` with a local dataframe is experimental and might result in unexpected results. One known issue is that using `merge` on a `CrunchDataFrame` will change the both the `CrunchDataFrame` used as input as well as create a new `CrunchDataFrame`.

Value

a `CrunchDataFrame` with columns from both `x` and `y`

mergeFork	<i>Merge changes to a dataset from a fork</i>
-----------	---

Description

Merge changes to a dataset from a fork

Usage

```
mergeFork(dataset, fork, autorollback = TRUE, force = FALSE)
```

Arguments

dataset	The CrunchDataset to merge to
fork	The CrunchDataset, perhaps forked from dataset, that is to be merged in.
autorollback	logical If the merge fails, should dataset be restored to its state prior to the merge, or should it be left in its partially merged state for debugging and manual fixing? Default is TRUE.
force	logical Attempt to push through merge conflicts by dropping all changes to dataset that occurred after fork diverged from and take only the changes from fork? Default is FALSE. You should only use force=TRUE after first attempting and failing to merge without forcing.

Value

dataset with changes from fork merged to it.

modifyWeightVariables	<i>Change which variables can be set as a dataset's weight.</i>
-----------------------	---

Description

modifyWeightVariables allows you to change the variables which are eligible to be used as a dataset's weight. You can also add variables to the weight variables catalog by assignment with `weightVariables(ds) <- "weight"` or `is.weightVariable(ds$weight) <- TRUE`.

Usage

```
modifyWeightVariables(x, vars, type = "append")

## S4 replacement method for signature 'CrunchDataset'
weightVariables(x) <- value

is.weightVariable(x)

## S4 replacement method for signature 'NumericVariable'
is.weightVariable(x) <- value
```

Arguments

x	a CrunchDataset
vars	Variables to add or remove this can be a numeric Crunch variable, list of numeric Crunch variables or a character vector with the aliases of numeric Crunch variables. Setting vars to NULL clears a datasets weightVariables
type	a character string determining how the weightVariables will be modified: <ul style="list-style-type: none"> • "append" : add vars to the current weight variables • "remove" : remove vars from the current list of weight variables • "replace": replace the current weight variables with vars
value	For the weightVariables() and is.weightVariable setters the variables to append to a dataset's weightVariables.

Details

Editors can change which variables can be set as the weighting variable for a dataset. For instance if several weights have been calculated they can let the user choose which of those variables to use a weight, but prevent the user from choosing other variables as weight. This function allows you to change the weightVariables of a dataset.

Value

a CrunchDataset

Examples

```
## Not run:
modifyweightVariables(ds, "weight", "append")
weightVariables(ds) <- list(ds$weight, ds$weight2)
weightVariables(ds) <- NULL
weightVariables(ds) <- c("weight", "weight2")
is.weightVariables(ds$weight) <- TRUE

## End(Not run)
```

moveToGroup

Move entities to a group

Description

Shoji entities can be placed into groups, this is mostly used for grouping variables for display in the app, but is technically possible for any of the order catalogs. This function moves an entity to one of these groups.

Usage

```
moveToGroup(x, value)
```

```
moveToGroup(x) <- value
```

Arguments

x	VariableGroup
value	Variable, VariableCatalog subset, or Dataset subset

Details

The function has two versions: a regular function and a setter. They do the same thing, but the setter is probably more succinct.

Value

x with the entities in value appended to it. If the containing order object has `duplicates=FALSE`, the entities will be "moved" to this group. Otherwise, their references will be copied to the group.

Examples

```
## Not run:
moveToGroup(ordering(ds)[["Demographics"]]) <- ds[c("gender", "age")]

## End(Not run)
```

multitable-catalog *Multitable entities for a dataset*

Description

Multitable entities for a dataset

Usage

```
## S4 method for signature 'CrunchDataset'
multitables(x)

## S4 replacement method for signature 'CrunchDataset'
multitables(x) <- value
```

Arguments

x	a CrunchDataset
value	for the assignment method, a MultitableCatalog

Value

an object of class `MultitableCatalog` containing references to `Multitable` entities. (Setter returns the `Dataset`.)

Description

Variables in Crunch datasets are organized into folders, like in a file system. These functions allow you to create new folders and move objects into folders. Their names, `mv` and `mkdir`, suggest their Unix file utility inspiration.

Usage

```
mv(dataset, variables, path)
```

```
mkdir(dataset, path, variables = NULL)
```

Arguments

<code>dataset</code>	A Crunch dataset
<code>variables</code>	A Variable, selection of variables from <code>dataset</code> , or any other object that can be moved to a folder. For <code>mkdir</code> , <code>variables</code> is optional.
<code>path</code>	A character "path" to the folder: either a vector of nested folder names or a single string with nested folders separated by a delimiter ("/" default, configurable via <code>options(crunch.delimiter)</code>)

Details

The functions have some differences from the strict behavior of their Unix ancestors. For one, they work recursively, without additional arguments: `mkdir` will make every directory necessary to construct the requested path, even if all parent directories didn't already exist; and `mv` doesn't require that the directory to move to already exist. `mkdir` also takes an optional `variables` argument, which allows you to say "make this directory **and** put these variables in it" in one command. As a result of these behaviors, `mv` and `mkdir` here are essentially the same, just with arguments in reverse order: `mv` is move "variables" to "path", while `mkdir` is create "path" and put "variables" in it.

Both functions take "dataset" as the first argument, so they naturally support pipelining (as with the `%>%` operator).

Value

`dataset`, with the folder at `path` guaranteed to be created and `variables`, if specified, moved into it.

See Also

[folder\(\)](#)

Examples

```
## Not run:
ds <- loadDataset("Example survey")
ds <- mv(ds, c("gender", "age", "educ"), "Demographics")
ds <- mkdir(ds, "Key Performance Indicators/Brand X")
# These can also be chained together
require(magrittr)
ds <- ds %>%
  mv(c("aware_x", "nps_x"), "Key Performance Indicators/Brand X") %>%
  mv(c("aware_y", "nps_y"), "Key Performance Indicators/Brand Y")

## End(Not run)
```

na-omit-categories	<i>Omit missing categories</i>
--------------------	--------------------------------

Description

Omit missing categories

Usage

```
## S4 method for signature 'Categories'
na.omit(object, ...)
```

Arguments

object	Categories
...	additional arguments, ignored

Value

object with any categories that have missing: TRUE excluded

name,AbstractCategory-method	<i>Category attributes</i>
------------------------------	----------------------------

Description

Functions to access and set category attributes.

Usage

```
## S4 method for signature 'AbstractCategory'  
name(x)  
  
## S4 replacement method for signature 'AbstractCategory'  
name(x) <- value  
  
## S4 replacement method for signature ``NULL``  
name(x) <- value  
  
## S4 method for signature 'AbstractCategory'  
id(x)  
  
## S4 method for signature 'Category'  
value(x)  
  
## S4 replacement method for signature 'Category'  
value(x) <- value  
  
## S4 method for signature 'Category'  
is.selected(x)
```

Arguments

x	a Category
value	For the setters, an appropriate value to set

Value

name returns character; value and id return numeric; value but not id may be NA; is.selected returns logical indicating whether this Category is a "selected" dichotomy. Setters return x duly modified.

See Also

[Categories dichotomize](#)

names, BatchCatalog-method

Get and set names, aliases on Catalog-type objects

Description

These methods let you get and set names and aliases for variables in a Dataset's catalog, or within [Subvariables](#) in an array variable. They work like the base R names methods.

Usage

```
## S4 method for signature 'BatchCatalog'
names(x)

## S4 method for signature 'CrunchDataset'
names(x)

## S4 replacement method for signature 'MultitableCatalog'
names(x) <- value

## S4 method for signature 'ShojiCatalog'
names(x)

## S4 replacement method for signature 'ShojiCatalog'
names(x) <- value

## S4 method for signature 'ShojiCatalog'
emails(x)

## S4 method for signature 'CategoricalArrayVariable'
names(x)

## S4 method for signature 'VariableCatalog'
aliases(x)

## S4 replacement method for signature 'VariableCatalog'
aliases(x) <- value

## S4 method for signature 'VariableCatalog'
notes(x)

## S4 replacement method for signature 'VariableCatalog'
notes(x) <- value

## S4 method for signature 'VariableCatalog'
descriptions(x)

## S4 replacement method for signature 'VariableCatalog'
descriptions(x) <- value

## S4 method for signature 'VariableCatalog'
types(x)

## S4 method for signature 'VariableCatalog'
ids(x)

## S4 method for signature 'VersionCatalog'
names(x)
```

```
## S4 method for signature 'VersionCatalog'
descriptions(x)
```

```
## S4 method for signature 'VersionCatalog'
timestamps(x)
```

Arguments

`x` a `VariableCatalog`, `Subvariables`, or similar object
`value` For the setters, an appropriate-length character vector to assign

Details

Note that the `Dataset` names method returns the aliases of its variables by default. This behavior is controlled by `getOption("crunch.namekey.dataset")`. Set `options(crunch.namekey.dataset="name")` if you wish to use variable names. See the `variables` vignette for more information.

Value

Getters return the character object in the specified slot; setters return `x` duly modified.

See Also

[Subvariables Categories](#) `base::names()` `vignette("variables", package="crunch")`

newDataset

Upload data to Crunch to make a new dataset

Description

This function creates a new dataset on the Crunch server with either a `data.frame` or similar object in your R session, a file, or a URL to a file. It captures available metadata from your R object and translates it into Crunch types.

Usage

```
newDataset(x, name = NULL, ...)
```

Arguments

`x` a `data.frame` or other rectangular R data object, or a string file name or URL to upload to create a dataset. The file may be a compressed Zip file containing a single file in CSV or SPSS format.
`name` character name to give the new Crunch dataset. By default the function uses the name of the R object, or, if passing a file, the file name.
`...` additional arguments passed to `createDataset()`

Details

If you have an SPSS file, it is better specify the file name directly rather than first reading it into R. Uploading SPSS files directly to Crunch will preserve metadata that is stripped by the R import, regardless of the library used to read it into R.

Value

If successful, an object of class `CrunchDataset`.

See Also

[newDatasetFromFile\(\)](#); [newDatasetByColumn\(\)](#) for an alternate upload method.

Examples

```
## Not run:
ds <- newDataset(mtcars, "cars")
ds <- newDataset("mysurvey.sav")

## End(Not run)
```

newFilter

Create a new filter

Description

This function creates a new filter for a `CrunchDataset`. You can achieve the same results by assigning into a dataset's filters catalog using [filters\(\)](#), but this may be a more natural way to think of the action, particularly when you want to do something with the filter entity after you create it.

Usage

```
newFilter(name, expression, catalog = NULL, ...)
```

Arguments

name	character name for the filter
expression	<code>CrunchLogicalExpr</code> with which to make a filter entity
catalog	<code>FilterCatalog</code> in which to create the new filter. May also provide a dataset entity. If omitted, the function will attempt to infer the dataset (and thus its <code>FilterCatalog</code>) from the contents of expression.
...	Additional filter attributes to set, such as <code>is_public</code> .

Value

A `CrunchFilter` object.

newMultitable	<i>Create a new Multitable</i>
---------------	--------------------------------

Description

Multitables, or "banners" or "crossbreaks", define a set of variables or query expressions to crosstab with as a unit. They are used in the Crunch web app to display tables side by side, as well as to define one dimension of a tab book.

Usage

```
newMultitable(formula, data, name, ...)
```

Arguments

formula	an object of class 'formula' object with the cross-classifying variables separated by '+' on the right-hand side. Following how <code>stats::formula()</code> works in R, it should start with "~". Variables on left-hand side of the formula have no meaning in this function.
data	an object of class <code>CrunchDataset</code> in which to create the multitable, and to which the variables referenced in <code>formula</code> belong.
name	character name to give the new multitable object. If omitted, a default name will be derived from <code>formula</code> .
...	Additional multitable attributes to set. Options include <code>is_public</code> .

Value

An object of class `Multitable`

See Also

[stats::formula](#)

Examples

```
## Not run:  
m <- newMultitable(~ gender + age4 + marstat, data=ds)  
name(m) # [1] "gender + age4 + marstat"  
  
## End(Not run)
```

`newProject`*Create a new project*

Description

This function creates a new project. You can achieve the same results by assigning into the projects catalog, but this may be a more natural way to think of the action, particularly when you want to do something with the project entity after you create it.

Usage

```
newProject(name, members = NULL, catalog = projects(), ...)
```

Arguments

<code>name</code>	character name for the project
<code>members</code>	Optional character vector of emails or user URLs to add as project members.
<code>catalog</code>	ProjectCatalog in which to create the new project. There is only one project catalog currently, <code>projects()</code> , but this is left here so that all <code>new*</code> functions follow the same pattern.
<code>...</code>	Additional project attributes to set

Value

A `CrunchProject` object.

Examples

```
## Not run:
proj <- newProject("A project name")
# That is equivalent to doing:
p <- projects()
p[["A project name"]] <- list()
proj <- p[["A project name"]]

proj2 <- newProject("Another project", members="you@yourco.com")
# That is equivalent to doing:
p[["Another project"]] <- list(members="you@yourco.com")
proj <- p[["Another project"]]

## End(Not run)
```

noTransforms	<i>Remove transformations from a CrunchCube</i>
--------------	---

Description

Remove transformations from a CrunchCube

Usage

```
noTransforms(cube)
```

Arguments

cube a CrunchCube

Value

the CrunchCube with no transformations

Removing transforms

noTransforms() is useful if you don't want to see or use any transformations like Subtotals and Headings. This action only applies to the CrunchCube object in R: it doesn't actually change the variables on Crunch servers or the query that generated the CrunchCube.

Examples

```
## Not run:
# A CrunchCube with a heading and subtotals
crtabs(~opinion, ds)
#           All opinions
#           Strongly Agree 23
#           Somewhat Agree 24
#           Agree 47
# Neither Agree nor Disagree 18
#           Somewhat Disagree 16
#           Strongly Disagree 19
#           Disagree 35

noTransforms(crtabs(~opinion, ds))
#           Strongly Agree           Somewhat Agree Neither Agree nor Disagree
#           23                   24                   18
#           Somewhat Disagree       Strongly Disagree
#           16                       19

## End(Not run)
```

 ordering

Get and set VariableOrder

Description

The ordering methods allow you to get and set a [VariableOrder](#) on a [CrunchDataset](#) or on the [VariableCatalog](#) that the dataset contains.

Usage

```
## S4 method for signature 'CrunchDataset'
ordering(x)

## S4 replacement method for signature 'CrunchDataset'
ordering(x) <- value

## S4 method for signature 'VariableCatalog'
ordering(x)

## S4 replacement method for signature 'VariableCatalog'
ordering(x) <- value

## S4 method for signature 'DatasetCatalog'
ordering(x)

## S4 replacement method for signature 'DatasetCatalog'
ordering(x) <- value
```

Arguments

x	a VariableCatalog or CrunchDataset
value	a valid VariableOrder object

Value

ordering returns a VariableOrder object, while ordering<- sets the VariableOrder

 owners

See who owns these datasets

Description

See who owns these datasets

Usage

owners(x)

ownerNames(x)

Arguments

x DatasetCatalog

Value

For owners, the URLs of the users or projects that own these datasets. For ownerNames, their names.

pendingStream *Get the pending streams for a dataset*

Description

Retrieves the number of pending messages. Use [appendStream\(\)](#) to append all pending streamed rows to the dataset.

Usage

pendingStream(ds)

Arguments

ds a CrunchDataset

Value

number of pending messages in the stream for the dataset

permissions *See who has access to a dataset*

Description

See who has access to a dataset

Usage

```
## S4 method for signature 'CrunchDataset'
permissions(x)
```

Arguments

x CrunchDataset

Value

A PermissionCatalog containing information on the users and teams that have access to this dataset.

pk *Get and set the primary key for a Crunch dataset*

Description

A primary key is a variable in a dataset that has a unique value for every row. A variable must be either numeric or text type and have no duplicate or missing values. A primary key on a dataset causes updates to that dataset that have the rows with the same primary key value(s) as the first dataset to update the existing rows rather than inserting new ones.

Usage

```
## S4 method for signature 'CrunchDataset'
pk(x)

## S4 replacement method for signature 'CrunchDataset'
pk(x) <- value
```

Arguments

x a Dataset

value For the setter, a single Variable to use as the primary key or NULL to remove the primary key.

Value

Getter returns the Variable object that is used as the primary key (NULL if there is no primary key); setter returns x duly modified.

preCrunchBoxCheck	<i>Check if a dataset will make a good CrunchBox</i>
-------------------	--

Description

CrunchBoxes allows you to share data with the world in a simple, easy to embed format. However, not all datasets naturally translate to the CrunchBox format. This function checks your dataset to see if it

Usage

```
preCrunchBoxCheck(dataset)
```

Arguments

dataset	CrunchDataset, potentially subsetted on variables
---------	---

Value

Invisibly, the dataset. Called for side-effect of printing things.

See Also

[CrunchBox](#)

prepareDataForCrunch	<i>Translate a data.frame to Crunch format</i>
----------------------	--

Description

This is called within newDataset to extract the Crunch metadata from the data and to transform the data to match the extracted metadata. You can call this directly in order to tailor the data import flow more finely.

Usage

```
prepareDataForCrunch(data, ...)
```

Arguments

data	A data.frame or other rectangular R object
...	additional arguments passed to createDataset . "name" will be required by the Crunch server but is not required by this function.

Value

A data.frame that is a transformation of data suitable for uploading to Crunch, also containing a "metadata" attribute that is the associated Crunch metadata.

See Also

createWithPreparedData writePreparedData

project-icon	<i>Get or set a project's icon</i>
--------------	------------------------------------

Description

This function allows you to change a project's icon. Note that you must first upload the icon to a website, as this function does not allow you to upload a local file.

Usage

```
icon(x)
```

```
icon(x) <- value
```

Arguments

x a CrunchProject

value character file path of the icon image file to set

Value

The URL of the project's icon. The setter returns the project after having uploaded the specified file as the new icon.

projects	<i>Get the project catalog</i>
----------	--------------------------------

Description

Get the project catalog

Usage

```
projects(x = getAPIRoot())
```

Arguments

`x` a `ShojiObject` that has an associated project catalog. If omitted, the default value for `x` means that you will load the user's primary project catalog. (Currently, there are no other project catalogs to load.)

Value

An object of class `ProjectCatalog`.

Examples

```
## Not run:
myprojects <- projects()
proj <- myprojects[["Project name"]]

## End(Not run)
```

refresh

Get a fresh copy from the server

Description

Crunch objects generally keep themselves in sync with the server when you manipulate them, but some operations cause the local version to diverge from the version on the server. For instance, someone else may have modified the dataset you're working on, or maybe you have modified a variable outside of the context of its dataset. `refresh()` allows you to get back in sync.

Usage

```
## S4 method for signature 'CrunchDataset'
refresh(x)

## S4 method for signature 'ShojiObject'
refresh(x)

## S4 method for signature 'CrunchVariable'
refresh(x)
```

Arguments

`x` pretty much any Crunch object

Value

a new version of `x`

removeEmptyGroups	<i>Remove OrderGroups with no entities</i>
-------------------	--

Description

This function recurses through a ShojiOrder/OrderGroup and removes any groups that contain no entities.

Usage

```
removeEmptyGroups(x)
```

Arguments

x	VariableOrder, DatasetOrder, VariableGroup, or DatasetGroup
---	---

Value

x with empty groups removed.

resetPassword	<i>Reset your password</i>
---------------	----------------------------

Description

Trigger the password reset process. Password reset instructions will be emailed to you.

Usage

```
resetPassword(email)
```

Arguments

email	Your email
-------	------------

Value

NULL, invisibly. Called for its side effects.

Examples

```
## Not run:  
resetPassword("me@example.com")  
  
## End(Not run)
```

restoreVersion	<i>Restore a dataset to a previously saved version</i>
----------------	--

Description

You can save a version of a dataset using [saveVersion\(\)](#). Savepoints are also created automatically by certain Crunch functions that make major changes to the dataset. You can get the list of saved versions with the [versions\(\)](#) function.

Usage

```
restoreVersion(dataset, version)
```

Arguments

dataset	a CrunchDataset
version	either the name ("description") of the version to restore to or the integer index of the version, as given by versions(dataset)

Value

dataset, rolled back to version.

See Also

[versions](#) [saveVersion](#)

saveVersion	<i>Create a new saved version</i>
-------------	-----------------------------------

Description

Crunch datasets can be saved and restored using [saveVersion](#) and [restoreVersion\(\)](#). Some Crunch functions, such as [appendDataset\(\)](#) create new savepoints automatically. To see the list of savepoints use [versions\(\)](#).

Usage

```
saveVersion(dataset, description = paste("Version", length(versions(dataset))
+ 1))
```

Arguments

dataset	a CrunchDataset
description	character name to give the saved version, as in a commit message. You are encouraged, though not strictly required, to give versions unique descriptions.

Value

invisibly, the URL of the newly created version

See Also

[versions restoreVersion](#)

scoreCatToFeat	<i>Score similarity between a feature dataframe and categories</i>
----------------	--

Description

Implemented using the Jaccard index, where a number closer to 1 is more similar.

Usage

```
scoreCatToFeat(features, categories)
```

Arguments

features	a vector of features to match (usually from a subset of the output [availableGeodataFeatures]) with a single property for a single geodatum.
categories	a vector of categories to match

Value

the Jaccard index for the values of the property given in feat_df and the vector of categories

searchDatasets	<i>Search Crunch for datasets.</i>
----------------	------------------------------------

Description

searchDatasets searches datasets' metadata for matches to the query argument. This search will include variable names, aliases, categories, but not the content of text variables. See [the API Documentation](#) for more information about searching Crunch.

Usage

```
searchDatasets(query, ...)
```

Arguments

query	the text to search for in datasets and their variables (note: only alpha characters will be used, numbers and other characters will be discarded.)
...	additional options provided to the search endpoint.

Value

If successful, an object of class SearchResults

self	<i>Get the URL of this object</i>
------	-----------------------------------

Description

Get the URL of this object

Usage

```
## S4 method for signature 'ShojiObject'
self(x)

## S4 method for signature 'CrunchVariable'
self(x)
```

Arguments

x a Crunch object

Value

the URL for x

session	<i>Get various catalogs for your Crunch session</i>
---------	---

Description

Get various catalogs for your Crunch session

Usage

```
session()
```

Value

A Session object. Access dataset and project catalogs from it.

Examples

```
## Not run:
cr <- session()
cr$datasets
cr$projects

## End(Not run)
```

session-extract *Extract catalogs from a Session object*

Description

Extract catalogs from a Session object

Usage

```
## S4 method for signature 'Session,ANY'
x[[i, ..., drop = FALSE]]

## S4 method for signature 'Session'
x$name

## S4 replacement method for signature 'Session,ANY,ANY,ANY'
x[[i]] <- value

## S4 replacement method for signature 'Session'
x$name <- value
```

Arguments

x	a Session object
i	which catalog to load. Supported values are "datasets" and "projects"
...	additional arguments, ignored.
drop	Invalid
name	for \$, the same as i for []
value	For updating, an object of the appropriate class and size to insert. In practice value is ignored; Session objects hold no state and it is assumed that any state modification on the server happens in other methods.

Value

The requested catalog when extracting; a Session object if assigning.

See Also

session

settings	<i>View and modify dataset-level settings</i>
----------	---

Description

These methods allow access and control over dataset settings. Currently supported settings include:

- User Authorizations for view-only users ('viewers_can_export', 'viewers_can_share', and 'viewers_can_change_weight'); and
- 'weight', which determines the default weighting variable for the dataset. Additional settings will be added in the future. See <http://docs.crunch.io/#fragments>, under 'Settings', for an up-to-date list of settings supported throughout the Crunch system. Clients may also provide and use custom settings if they choose.

Usage

```
settings(x)

settings(x) <- value
```

Arguments

x	CrunchDataset
value	A settings object (ShojiEntity), for the setter

Value

The getter returns a settings object (ShojiEntity). The setter returns the dataset (x), duly modified.

Examples

```
## Not run:
settings(ds)
settings(ds)$viewers_can_export <- TRUE
settings(ds)$weight <- ds$myWeightVariable

## End(Not run)
```

share	<i>Share a dataset</i>
-------	------------------------

Description

Share a dataset

Usage

```
share(dataset, users, edit = FALSE, notify = TRUE, message = NULL)
```

Arguments

dataset	a CrunchDataset
users	character: email address(es) or URLs of the users or teams with whom to share the dataset. If there is no Crunch user associated with an email, an invitation will be sent.
edit	logical: should the specified user(s) be given edit privileges on the dataset? Default is FALSE. edit can be a single value or, if inviting multiple users, a vector of logical values of equal length of the number of emails given.
notify	logical: should users who are getting new privileges on this dataset be sent an email informing them of this fact? Default is TRUE.
message	character: a message to send to the users who are receiving new privileges.

Value

Invisibly, the dataset.

See Also

[unshare](#)

shoji-index	<i>Get the body of a Catalog</i>
-------------	----------------------------------

Description

The core of Catalog data is in its "index". These methods get and set that slot.

Usage

```
## S4 method for signature 'ShojiCatalog'
index(x)

## S4 replacement method for signature 'ShojiCatalog'
index(x) <- value
```

Arguments

x a Catalog (VariableCatalog, Subvariables, or similar object)
 value For the setters, an appropriate-length list to assign

Value

Getters return the list object in the "index" slot; setters return x duly modified.

ShojiObject-class *Mix-in class for multiple inheritance of variables and datasets.*

Description

Exists for common methods in interacting with Crunch API only. Has no Extract methods declared so as not to conflict with the vector/list/data.frame methods jointly inherited in CrunchVariable and CrunchDataset.

ShojiOrder-extract *Extract and update in VariableOrders and VariableGroups*

Description

Extract and update in VariableOrders and VariableGroups

Usage

```
## S4 method for signature 'ShojiOrder,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ShojiOrder,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ShojiOrder,ANY'
x[[i, j, ...]]

## S4 method for signature 'ShojiOrder,character'
x[[i, j, ...]]

## S4 method for signature 'ShojiOrder'
x$name

## S4 replacement method for signature 'ShojiOrder,character,missing,ShojiOrder'
x[i, j] <- value
```

```
## S4 replacement method for signature 'ShojiOrder,ANY,missing,ShojiOrder'  
x[i, j] <- value  
  
## S4 replacement method for signature 'ShojiOrder,character,missing,list'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ShojiOrder,character,missing,character'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ShojiOrder,character,missing,OrderGroup'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ShojiOrder,ANY,missing,OrderGroup'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ShojiOrder,ANY,missing,ANY'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ShojiOrder,ANY,missing,`NULL`'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ShojiOrder,character,missing,`NULL`'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ShojiOrder,character,missing,ShojiOrder'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ShojiOrder'  
x$name <- value  
  
## S4 method for signature 'OrderGroup,ANY,ANY'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'OrderGroup,character,ANY'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'OrderGroup,character'  
x[[i, j, ...]]  
  
## S4 method for signature 'OrderGroup,ANY'  
x[[i, j, ...]]  
  
## S4 method for signature 'OrderGroup'  
x$name  
  
## S4 replacement method for signature 'OrderGroup,character,missing,list'  
x[[i, j]] <- value
```

```

## S4 replacement method for signature 'OrderGroup,character,missing,character'
x[[i, j]] <- value

## S4 replacement method for signature 'OrderGroup,character,missing,ShojiOrder'
x[[i, j]] <- value

## S4 replacement method for signature 'OrderGroup,character,missing,OrderGroup'
x[[i, j]] <- value

## S4 replacement method for signature 'OrderGroup,ANY,missing,OrderGroup'
x[[i, j]] <- value

## S4 replacement method for signature 'OrderGroup,numeric,missing,`NULL`'
x[[i, j]] <- value

## S4 replacement method for signature 'OrderGroup,character,missing,`NULL`'
x[[i, j]] <- value

## S4 replacement method for signature 'OrderGroup'
x$name <- value

## S4 replacement method for signature 'VariableOrder,character,missing,CrunchDataset'
x[[i, j]] <- value

## S4 replacement method for signature 'VariableGroup,character,missing,CrunchDataset'
x[[i, j]] <- value

```

Arguments

x	a VariableOrder or VariableGroup
i	an index. Numeric and logical indexing supported for both classes; character indexing supported for VariableOrder, matching on VariableGroup names
j	Invalid
...	additional arguments
drop	Ignored
name	Same as i but for \$
value	For update methods, an object equivalent in class to what is being updated

Value

[[and \$ on a VariableOrder return the VariableGroup. [[on VariableGroup returns the entity within, either a character (URL) or nested VariableGroup. [and assignment methods return objects of the same class as x

ShojiOrder-length *Length of an Order*

Description

Length of an Order

Usage

```
## S4 method for signature 'ShojiOrder'
length(x)

## S4 method for signature 'OrderGroup'
length(x)
```

Arguments

x a ShojiOrder

Value

Integer: the number of elements in the Order

ShojiOrder-slots *Manipulate VariableGroup and VariableOrder*

Description

Manipulate VariableGroup and VariableOrder

Usage

```
## S4 method for signature 'OrderGroup'
entities(x, simplify = FALSE)

## S4 method for signature 'ShojiOrder'
entities(x, simplify = FALSE)

## S4 method for signature 'list'
entities(x, simplify = FALSE)

## S4 replacement method for signature 'OrderGroup'
entities(x) <- value

## S4 replacement method for signature 'ShojiOrder'
entities(x) <- value
```



```

## S4 method for signature 'OrderGroup'
name(x)

## S4 replacement method for signature 'OrderGroup'
name(x) <- value

## S4 method for signature 'ShojiOrder'
names(x)

## S4 method for signature 'OrderGroup'
names(x)

## S4 replacement method for signature 'ShojiOrder'
names(x) <- value

## S4 method for signature 'ShojiOrder'
duplicates(x)

## S4 method for signature 'OrderGroup'
duplicates(x)

## S4 method for signature 'VariableCatalog'
duplicates(x)

## S4 replacement method for signature 'ShojiOrder,logical'
duplicates(x) <- value

## S4 replacement method for signature 'OrderGroup,logical'
duplicates(x) <- value

## S4 replacement method for signature 'VariableCatalog,logical'
duplicates(x) <- value

```

Arguments

x	a VariableGroup or VariableOrder
simplify	logical: should variable URLs inside of groups be flattened or preserved in their nested lists? Default isFALSE.
value	<ol style="list-style-type: none"> 1. For name, a character (length-1 vector); for names, a character vector of equal length to the number of VariableGroups being modified; for entities, either a character vector of variable URLs or a list containing a combination of variable URLs and VariableGroups. Note that group names must be unique, should be greater than 0 characters long, and "ungrouped" is a reserved group name. 2. For duplicates, logical for whether duplicate variable entries should be allowed in the VariableOrder.

Value

- entities returns Variable references and VariableGroups;
- names returns group names;
- duplicates returns logical for whether duplicate variable entries should be allowed

See Also

[VariableOrder](#) grouped

show-crunch

Show methods for Crunch objects

Description

Show methods for Crunch objects

Usage

```
## S4 method for signature 'ShojiObject'  
show(object)
```

```
## S4 method for signature 'CrunchVariable'  
show(object)
```

```
## S4 method for signature 'Category'  
show(object)
```

```
## S4 method for signature 'Categories'  
show(object)
```

```
## S4 method for signature 'Insertion'  
show(object)
```

```
## S4 method for signature 'Insertions'  
show(object)
```

```
## S4 method for signature 'CrunchExpr'  
show(object)
```

```
## S4 method for signature 'CrunchLogicalExpr'  
show(object)
```

```
## S4 method for signature 'CrunchCube'  
show(object)
```

```
## S4 method for signature 'OrderGroup'
```

```

show(object)

## S4 method for signature 'CrunchGeography'
show(object)

## S4 method for signature 'MultitableResult'
show(object)

```

Arguments

object the object

Value

invisibly

See Also

[methods::show](#)

showTransforms, CrunchCube-method

Show transformations on a Crunch object

Description

showTransforms([variable]) shows a summary of a categorical variable that has transforms with the transforms calculated and applied. This is useful to see what kind transforms exist before including the variable in a CrunchCube.

Usage

```

## S4 method for signature 'CrunchCube'
showTransforms(x)

## S4 method for signature 'CategoricalVariable'
showTransforms(x)

```

Arguments

x a Categorical variable or CrunchCube

Details

showTransforms([CrunchCube]) shows the CrunchCube with all transforms calculated and applied. This is the default display method for cubes, so should not be frequently needed.

In both cases, an array is returned that includes the values of both the underlying data (either category counts or CrunchCube cell values) as well as the transformations applied.

Value

summary of the variable, or the full CrunchCube with transforms applied

Examples

```
## Not run:
showTransforms(ds$variable)

## End(Not run)
```

Subtotal-class	<i>Subtotals and headings</i>
----------------	-------------------------------

Description

Subtotals and headings for categorical Variables and CrunchCubes. These are especially useful for making aggregates across multiple categories (sometimes referred to as *nets*, *top box*, or *top 2 box*).

Usage

```
Subtotal(name, categories, position = c("relative", "top", "bottom"),
  after = NULL)

Heading(name, position = c("relative", "top", "bottom"), after = NULL)

Subtotal(name, categories, position = c("relative", "top", "bottom"),
  after = NULL)

is.Subtotal(x)

is.Heading(x)

are.Subtotals(x)

are.Headings(x)

Heading(name, position = c("relative", "top", "bottom"), after = NULL)

## S4 method for signature 'CrunchVariable'
subtotals(x)

## S4 method for signature 'VariableTuple'
subtotals(x)

## S4 replacement method for signature 'CrunchVariable,ANY'
subtotals(x) <- value
```

```
## S4 replacement method for signature 'CrunchVariable, `NULL`'
subtotals(x) <- value
```

Arguments

name	character the name of the subtotal or heading
categories	character or numeric the category names or ids for subtotal only
position	character one of "relative", "top", or "bottom". Determines the position of the subtotal or heading, either at the top, bottom, or relative to another category in the cube (default).
after	character or numeric if position is "relative", then the category name or id to position the subtotal or heading after
x	either a variable or CrunchCube object to add or get subtotal transforms for
value	For [<code><-</code> , the replacement Subtotal to insert
...	additional arguments to [, ignored

Details

To see the subtotals or headings set for a variable, use `subtotals(variable)`

Adding Subtotals and Headings

Subtotals and headings can be added either by passing a list of Subtotals or Headings, or they can be added one at a time by passing Subtotal or Heading to `subtotals(variable)` alone.

Adding subtotals or headings is additive; meaning that subtotals or headings that are already set on the variable are not removed when new subtotals or headings are added. To remove all subtotals and headings, set `subtotals(variable)` to `NULL`.

To get an array of just the subtotal rows from a CrunchCube, use the function `subtotalArray(CrunchCube)`.

Working with Subtotals and headings

When interacting programmatically with Subtotals and Headings, it can be useful to be able to tell if something is a Subtotal or a Heading. The `is.*` family of methods are useful here: the singular versions (`is.Subtotal` and `is.Heading`) take a single object and returns `TRUE` if the object is either a Subtotal or a Heading and `FALSE` if not; the plural versions (`are.Subtotals` and `are.Headings`) take a list of objects (including an `Insertions` object) and returns a vector of `TRUE/FALSEs`.

Removing transforms

`noTransforms()` is useful if you don't want to see or use any transformations like Subtotals and Headings. This action only applies to the CrunchCube object in R: it doesn't actually change the variables on Crunch servers or the query that generated the CrunchCube.

Examples

```
## Not run:
# given a variable ds$opinion, with categories: Strongly Agree, Somewhat
# Agree, Neither Agree nor Disagree, Somewhat Disagree, and Strongly Disagree,
# to make two subtotals for Agree and Disagree:
subtotals(ds$opinion) <- list(
  Subtotal(name = "Agree",
           categories = c("Strongly Agree", "Somewhat Agree"),
           after = "Somewhat Agree"),
  Subtotal(name = "Disagree",
           categories = c("Strongly Disagree", "Somewhat Disagree"),
           after = "Strongly Disagree")
)

# headings can also be added:
subtotals(ds$opinion) <- Heading(name = "All opinions", position = "top")

# to see the subtotals and headings associated with a variable
subtotals(ds$opinion)
#      anchor      name      func      args
# 1      2      Agree subtotal 1 and 2
# 2      4      Disagree subtotal 4 and 5
# 3      0 All opinions      <NA>      NA

# when you use a variable with subtotals and headings in a cube, you see them
# by default
opinion_cube <- crtabs(~opinion, ds)
opinion_cube
#      All opinions
#      Strongly Agree 23
#      Somewhat Agree 24
#      Agree 47
# Neither Agree nor Disagree 18
#      Somewhat Disagree 16
#      Strongly Disagree 19
#      Disagree 35

# to get just the subtotals,
subtotalArray(opinion_cube)
#      Agree Disagree
#      47      35

# to remove all subtotals and headings
subtotals(ds$opinion) <- NULL
crtabs(~opinion, ds)
#      Strongly Agree 23
#      Somewhat Agree 24
# Neither Agree nor Disagree 18
#      Somewhat Disagree 16
#      Strongly Disagree 19
```

```
# if you want to temporarily remove subtotals and headings, you can with `noTransforms`
noTransforms(crtabs(~opinion, ds))
#           Strongly Agree           Somewhat Agree Neither Agree nor Disagree
#           23                   24                   18
#           Somewhat Disagree       Strongly Disagree
#           16                   19

## End(Not run)
```

```
subtotalArray, CrunchCube-method
```

Calculate the transforms from a CrunchCube

Description

applyTransforms calculates transforms (e.g. [Subtotals](#)) on a CrunchCube. Currently only the row transforms are supported. This is useful if you want to use the values from the subtotals of the CrunchCube in an analysis.

Usage

```
## S4 method for signature 'CrunchCube'
subtotalArray(x, headings = FALSE)

applyTransforms(x, array = cubeToArray(x), ...)
```

Arguments

x	a CrunchCube
headings	for subtotalArray: a logical indicating if the headings should be included with the subtotals (default: FALSE)
array	an array to use, if not using the default array from the cube itself. (Default: not used, pulls an array from the cube directly)
...	arguments to pass to calcTransforms, for example include

Details

Including the include argument allows you to specify which parts of the CrunchCube to return. The options can be any of the following: "cube_cells" for the untransformed values from the cube itself, "subtotals" for the subtotal insertions, and "headings" for any additional headings. Any combination of these can be given, by default all will be given.

subtotalArray(cube) is a convenience function that is equivalent to applyTransforms(cube, include = c("subtotals"

Value

an array with any transformations applied

Examples

```
## Not run:
# to get an array of just the subtotals
subtotalArray(crtabs(~opinion, ds))
#   Agree Disagree
#     47     35

# to get the full array with the subtotals but not headings
applyTransforms(crtabs(~opinion, ds), include = c("cube_cells", "subtotals"))
#           Strongly Agree           Somewhat Agree           Agree
#           23                24                47
# Neither Agree nor Disagree           Strongly Disagree           Disagree
#           18                19                35
#           Somewhat Disagree
#           16

# to get the full array with the headings but not subtotals
applyTransforms(crtabs(~opinion, ds), include = c("cube_cells", "headings"))
#           All opinions           Strongly Agree           Somewhat Agree
#           NA                23                24
# Neither Agree nor Disagree           Strongly Disagree           Somewhat Disagree
#           18                19                16

## End(Not run)
```

Subvariables-class *Subvariables in Array Variables*

Description

Multiple-response and categorical-array variables are higher order variables which are made up of sets of subvariables. These methods allow you to retrieve and change the subvariables of a multiple-response or categorical-array variable.

Usage

```
## S4 method for signature 'CategoricalArrayVariable'
subvariables(x)

## S4 method for signature 'VariableTuple'
subvariables(x)

## S4 replacement method for signature 'CategoricalArrayVariable,ANY'
subvariables(x) <- value

## S4 replacement method for signature 'CategoricalArrayVariable,Subvariables'
subvariables(x) <- value
```


Arguments

x	A Variable or Subvariables object
value	For the setters, the appropriate values to set

Details

Subvariables can be accessed from array variables (including multiple response) with the `subvariables` method. They can be assigned back with the `subvariables<-` setter, but there are limitations to what is supported. Specifically, you can reorder subvariables, but you cannot add or remove subvariables by `subvariables<-` assignment. See `deleteSubvariable` to remove subvariables from an array.

Subvariables have a `names` attribute that can be accessed, showing the display names of the subvariables. These can be set with the `names<-` method.

Finally, subvariables can be accessed as regular (categorical) variables with the `$` and `[[` extract methods.

See the vignette on array variables for further details and examples.

See Also

[subvars-extract](#) [describe-catalog](#) [deleteSubvariable](#) `vignette("array-variables", package="crunch")`

subvars-extract	<i>Extract and modify subsets of subvariables</i>
-----------------	---

Description

Extract and modify subsets of subvariables

Usage

```
## S4 method for signature 'Subvariables,character'
x[[i, j, ...]]

## S4 method for signature 'Subvariables,numeric'
x[[i, j, ...]]

## S4 method for signature 'Subvariables,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 replacement method for signature 'Subvariables,character,missing,CrunchVariable'
x[[i]] <- value

## S4 replacement method for signature 'Subvariables,ANY,missing,CrunchVariable'
x[[i]] <- value
```

```

## S4 replacement method for signature 'Subvariables,ANY,missing,`NULL`'
x[[i]] <- value

## S4 replacement method for signature 'Subvariables,ANY,missing,ANY'
x[[i]] <- value

## S4 replacement method for signature 'Subvariables,character,missing,Subvariables'
x[i] <- value

## S4 replacement method for signature 'Subvariables,ANY,missing,Subvariables'
x[i] <- value

## S4 replacement method for signature 'Subvariables,ANY,missing,ANY'
x[i] <- value

## S4 method for signature 'CategoricalArrayVariable,character,ANY'
x[i, j, ...,
  drop = TRUE]

## S4 method for signature 'CategoricalArrayVariable,missing,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CategoricalArrayVariable,missing,character'
x[i, j, ...,
  drop = TRUE]

## S4 method for signature 'CategoricalArrayVariable,ANY'
x[[i, j, ...]]

## S4 method for signature 'CategoricalArrayVariable,character'
x[[i, j, ...]]

## S4 method for signature 'CategoricalArrayVariable'
x$name

## S4 replacement method for signature 'CategoricalArrayVariable,ANY,missing,ANY'
x[[i]] <- value

## S4 replacement method for signature 'CategoricalArrayVariable,character,missing,ANY'
x[[i]] <- value

## S4 replacement method for signature 'CategoricalArrayVariable'
x$name <- value

```

Arguments

x	Subvariables or an array Variable which contains subvariables
i	which subvariables to extract

j	Invalid
...	additional arguments
drop	Invalid
value	For updating, a CrunchExpr
name	For \$, the name (not alias) of the subvariable to extract

Value

A subset of x if extracting, otherwise x duly modified

tabBook	<i>Compute a Tab Book</i>
---------	---------------------------

Description

This function allows you to generate a tab book from a multitable and data. As with other functions, you can select the rows and columns you want to work with by subsetting the dataset you pass into the function.

Usage

```
tabBook(multitable, dataset, weight = crunch::weight(dataset),
        format = c("json", "xlsx"), file, ...)
```

Arguments

multitable	a Multitable object
dataset	CrunchDataset, which may have been subsetted with a filter expression on the rows and a selection of variables on the columns.
weight	a CrunchVariable that has been designated as a potential weight variable for dataset, or NULL for unweighted results. Default is the currently applied weight .
format	character export format: currently supported values are "json" (default) and "xlsx".
file	character local filename to write to. A default filename will be generated from the multitable's name if one is not supplied and the "xlsx" format is requested. Not required for "json" format export.
...	Additional "options" passed to the tab book POST request.

Details

By specifying a "json" format, instead of generating an Excel workbook, you'll get a TabBookResult object, containing nested CrunchCube results. You can then further format these and construct custom tab reports.

Value

If "json" format is requested, the function returns an object of class `TabBookResult`, containing a list of `MultitableResult` objects, which themselves contain `CrunchCubes`. If "xlsx" is requested, the function invisibly returns the filename (`file`, if specified, or the the autogenerated file name). If you request "json" and wish to access the JSON data underlying the `TabBookResult`, pass in a path for `file` and you will get a JSON file written there as well.

Examples

```
## Not run:
m <- newMultitable(~ gender + age4 + marstat, data=ds)
tabBook(m, ds[ds$income > 1000000,], format="xlsx", file="wealthy-tab-book.xlsx")
book <- tabBook(m, ds) # Returns a TabBookResult
tables <- prop.table(book, 2)

## End(Not run)
```

tabbook-methods

TabBookResult and MultitableResult methods

Description

`TabBookResult` and `MultitableResult` methods

Usage

```
## S4 method for signature 'TabBookResult'
length(x)

## S4 method for signature 'TabBookResult,numeric'
x[[i, j, ...]]

## S4 method for signature 'TabBookResult,character'
x[[i, j, ...]]

## S4 method for signature 'TabBookResult'
dim(x)

## S4 method for signature 'TabBookResult'
names(x)

## S4 method for signature 'TabBookResult'
aliases(x)

## S4 method for signature 'TabBookResult'
descriptions(x)
```

```
## S4 method for signature 'MultitableResult'
length(x)

## S4 method for signature 'MultitableResult,ANY'
x[[i, j, ...]]

## S4 method for signature 'MultitableResult'
names(x)

## S4 method for signature 'MultitableResult'
aliases(x)

## S4 method for signature 'MultitableResult'
descriptions(x)
```

Arguments

x	a TabBookResult or MultitableResult
i	an index into x
j	an index into x, ignored
...	also ignored

Value

Returns what you'd expect.

table	<i>Table function for Crunch objects</i>
-------	--

Description

Table function for Crunch objects

Usage

```
table(..., exclude, useNA = c("no", "ifany", "always"), dnn, deparse.level)
```

Arguments

...	CrunchVariables to tabulate
exclude	see base::table
useNA	see base::table
dnn	see base::table
deparse.level	see base::table

Value

a table object

See Also

[base::table](#)

temp.options	<i>Set some global options temporarily</i>
--------------	--

Description

Set some global options temporarily

Usage

```
temp.options(...)
```

```
temp.option(...)
```

Arguments

... named options to set

Value

an S3 class "contextManager" object

See Also

[with-context-manager ContextManager](#)

tojson-crunch	<i>toJSON methods for Crunch objects</i>
---------------	--

Description

crunch uses the jsonlite package for JSON serialization and deserialization. Unfortunately, [jsonlite::toJSON\(\)](#) does not allow for defining S4 methods for other object types. So, crunch::toJSON wraps jsonprep, which exists to translate objects to base R objects, which jsonlite::toJSON can handle. jsonprep is defined as an S4 generic, and it is exported, so you can define methods for it if you have other objects that you want to successfully serialize to JSON.

Usage

```

jsonprep(x, ...)

## S4 method for signature 'AbstractCategories'
jsonprep(x, ...)

## S4 method for signature 'ANY'
jsonprep(x, ...)

## S4 method for signature 'ShojiOrder'
jsonprep(x, ...)

## S4 method for signature 'OrderGroup'
jsonprep(x, ...)

toJSON(x, ...)

```

Arguments

```

x           the object
...        additional arguments

```

Value

jsonprep returns a base R object that jsonlite::toJSON can handle. toJSON returns the JSON-serialized character object.

See Also

[jsonlite::toJSON\(\)](#)

toVariable

Generic method for converting objects to Crunch representations

Description

R objects are converted to Crunch objects using the following rules:

Usage

```

toVariable(x, ...)

## S4 method for signature 'character'
toVariable(x, ...)

## S4 method for signature 'numeric'
toVariable(x, ...)

```

```
## S4 method for signature 'factor'  
toVariable(x, ...)  
  
## S4 method for signature 'Date'  
toVariable(x, ...)  
  
## S4 method for signature 'POSIXt'  
toVariable(x, ...)  
  
## S4 method for signature 'AsIs'  
toVariable(x, ...)  
  
## S4 method for signature 'VariableDefinition'  
toVariable(x, ...)  
  
## S4 method for signature 'logical'  
toVariable(x, ...)  
  
## S4 method for signature 'CrunchExpr'  
toVariable(x, ...)
```

Arguments

x	the object
...	additional arguments

Details

- Character vectors are converted into Crunch text variables
- Numeric vectors are converted into Crunch numeric variables
- Factors are converted to categorical variables
- Date and POSIXt vectors are converted into Crunch datetime variables
- Logical vectors are converted to Crunch categorical variables
- [VariableDefinitions](#) are not converted, but the function can still append additional metadata

If you have other object types you wish to convert to Crunch variables, you can declare methods for `toVariable`

Value

a list object suitable for POSTing to the Crunch API. See the API documentation for specifications.

Transforms-class *Transformations of variable and cube views*

Description

Transformations allow you to change how a variable or cube is displayed without changing the underlying data.

Usage

```
Transforms(..., data = NULL)

## S4 method for signature 'CrunchCube'
transforms(x)

## S4 method for signature 'VariableCatalog'
transforms(x)

## S4 replacement method for signature 'CrunchCube,list'
transforms(x) <- value

## S4 replacement method for signature 'CrunchCube,NULL`'
transforms(x) <- value

## S4 method for signature 'CrunchVariable'
transforms(x)

## S4 method for signature 'VariableTuple'
transforms(x)

## S4 replacement method for signature 'CrunchVariable,Transforms'
transforms(x) <- value

## S4 replacement method for signature 'CrunchVariable,NULL`'
transforms(x) <- value
```

Arguments

...	For the constructor function <code>Transforms</code> you can pass in attributes via ...
data	For the constructor function <code>Transforms</code> you can either pass in attributes via ... or you can create the objects with a fully defined <code>list</code> representation of the objects via the <code>data</code> argument. See the examples.
x	For the attribute getters and setters, an object of class <code>Transforms</code>
value	For [<code><-</code> , the replacement <code>Transforms</code> to insert

Getting transformations

The `transforms(x)` methods can be used with `Variables` and `CrunchCubes` to get what transformations are currently set. For variables, they return a single `Transforms` object that includes all transformations for the variable. For `CrunchCubes`, it returns a named list with the same length as the number of dimensions of the cube with each dimension's transformations.

Currently, `Insertions` (e.g. `Subtotal()` and `Heading()`) are the only type of transformations that are supported.

Setting transformations on a variable

The `transforms(x) <- value` methods can be used to assign transformations for a specific variable. `value` must be a `Transforms` object. This allows you to set transformations on categorical variables. These transformations will automatically show up in any new `CrunchCubes` that contain this variable.

Setting transformations on a CrunchCube

The `transforms(x) <- value` methods can also be used to assign transformations to a `CrunchCube` that has already been calculated. `value` must be a named list of `Transforms` objects. The names of this list must correspond to dimensions in the cube (those dimensions correspondences are matched based on variable aliases). You don't have to provide an entry for each dimension, but any dimension you do provide will be overwritten fully.

Removing transformations

To remove transformations from a variable or `CrunchCube`, use `transforms(x) <- NULL`.

type	<i>Change Crunch variable types</i>
------	-------------------------------------

Description

Numeric, text, and categorical variables can be cast to one another by assigning them a new "type". This modifies the storage of the data on the server and should only be done in narrow circumstances, as in when importing data from a different file format has resulted in incorrect types being specified.

Usage

```
## S4 method for signature 'CrunchVariable'
type(x)

## S4 replacement method for signature 'CrunchVariable'
type(x) <- value
```

Arguments

x	a Variable
value	For the setter, a character value in <code>c("numeric", "text", "categorical")</code>

Value

Getter returns character; setter returns x duly modified.

unbind	<i>Split an array or multiple-response variable into its CategoricalVariables</i>
--------	---

Description

Split an array or multiple-response variable into its CategoricalVariables

Usage

```
unbind(x)
```

Arguments

x a CategoricalArrayVariable or MultipleResponseVariable

Value

invisibly, the API response from DELETEing the array variable definition. If you [refresh\(\)](#) the corresponding dataset after unbinding, you should see the array variable removed and its subvariables promoted to regular variables.

unshare	<i>Revoke a user's access to a dataset</i>
---------	--

Description

Revoke a user's access to a dataset

Usage

```
unshare(dataset, users)
```

Arguments

dataset a CrunchDataset
users character: email address(es) or URLs of the users or teams to unshare with.

Value

Invisibly, the dataset.

See Also

[share](#)

var-categories	<i>Get and set Categories on Variables</i>
----------------	--

Description

Get and set Categories on Variables

Usage

```
## S4 method for signature 'VariableTuple'  
categories(x)  
  
## S4 method for signature 'CrunchVariable'  
categories(x)  
  
## S4 method for signature 'CategoricalVariable'  
categories(x)  
  
## S4 method for signature 'CategoricalArrayVariable'  
categories(x)  
  
## S4 method for signature 'VariableEntity'  
categories(x)  
  
## S4 replacement method for signature 'CategoricalVariable,Categories'  
categories(x) <- value  
  
## S4 replacement method for signature 'CategoricalArrayVariable,Categories'  
categories(x) <- value  
  
## S4 replacement method for signature 'CategoricalVariable,numeric'  
categories(x) <- value  
  
## S4 replacement method for signature 'CategoricalVariable,character'  
categories(x) <- value  
  
## S4 replacement method for signature 'CategoricalVariable,ANY'  
categories(x) <- value  
  
## S4 replacement method for signature 'CategoricalArrayVariable,numeric'  
categories(x) <- value  
  
## S4 replacement method for signature 'CategoricalArrayVariable,character'  
categories(x) <- value  
  
## S4 replacement method for signature 'CategoricalArrayVariable,ANY'  
categories(x) <- value
```

```
## S4 replacement method for signature 'CrunchVariable,ANY'
categories(x) <- value
```

Arguments

x a Variable
value for the setters, an object of class Categories to set.

Value

Getters return Categories; setters return x duly modified.

variable-update	<i>Update variables with expressions or values</i>
-----------------	--

Description

Update variables with expressions or values

Usage

```
## S4 replacement method for signature 'CrunchVariable,ANY,missing,ANY'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY,missing,`NULL`'
x[i, j] <- value

## S4 replacement method for signature 'TextVariable,ANY,missing,character'
x[i, j] <- value

## S4 replacement method for signature 'NumericVariable,ANY,missing,numeric'
x[i, j] <- value

## S4 replacement method for signature 'DatetimeVariable,ANY,missing,Date'
x[i, j] <- value

## S4 replacement method for signature 'DatetimeVariable,ANY,missing,POSIXt'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY,missing,CrunchExpr'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY,missing,CrunchVariable'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY,missing,CrunchLogicalExpr'
```

```

x[i, j] <- value

## S4 replacement method for signature 'CategoricalVariable,ANY,missing,numeric'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalVariable,ANY,missing,character'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalVariable,ANY,missing,factor'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalArrayVariable,ANY,missing,numeric'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalArrayVariable,ANY,missing,character'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalArrayVariable,ANY,missing,factor'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY,missing,logical'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY'
is.na(x) <- value

```

Arguments

x	a Variable
i	a CrunchLogicalExpr or R index, optionally
j	Invalid
value	an R vector or a CrunchExpr with which to update

Value

x duly modified

VariableCatalog-class *Collection of Variables within a Dataset*

Description

A VariableCatalog contains references to all variables in a dataset, plus some descriptive metadata about each. Each VariableCatalog also contains a [VariableOrder](#) that governs how variables within it are organized.

VariableDefinition *Construct a variable definition*

Description

Crunch variables are created by posting a `VariableDefinition` to the Crunch server. The `VariableDefinition` contains the information the server requires to calculate the variable. This can information can either be in the form of the actual data which you would like to include in the variable, or a derivation which tells the server how to derive the new variable from existing ones. This function converts an R vector or set of attributes into a variable definition which can be posted to the server.

Usage

```
VariableDefinition(data, ...)
```

```
VarDef(data, ...)
```

Arguments

<code>data</code>	an R vector of data to convert to the Crunch payload format. See toVariable for how R data types are converted. This function can also be used to construct a <code>VariableDefinition</code> directly by passing attributes to <code>...</code> This is only recommended for advanced users who are familiar with the Crunch API.
<code>...</code>	additional attributes to be included in the <code>VariableDefinition</code>

Value

a `VariableDefinition` object, ready to POST to Crunch.

See Also

`toVariable`

Examples

```
VariableDefinition(rnorm(5), name="Some numbers",
  description="Generated pseudorandomly from the normal distribution")
VarDef(name="Integers", values=1:5, type="numeric",
  description="When creating variable definitions with 'values', you must
  specify 'type', and categorical variables will require 'categories'.")
```

variableMetadata	<i>Get all variable metadata for a dataset</i>
------------------	--

Description

Crunch stores variable information in several catalogs containing information about the variable class, its missingness and subvariables. This function allows you to access that information.

Usage

```
variableMetadata(dataset)
```

Arguments

dataset CrunchDataset

Value

A VariableCatalog with all variable properties, including categories and subvariables.

VariableOrder-class	<i>Organize Variables within a Dataset</i>
---------------------	--

Description

Variables in the Crunch web application can be viewed in an ordered, hierarchical list. These objects and methods allow you to modify that order from R.

Details

A VariableOrder object is a subclass of `list` that contains VariableGroups. VariableGroup objects contain a group name and an set of "entities", which can be variable references or other nested VariableGroups.

Slots

`group` character, the name of the VariableGroup. In the constructor and more generally, this field can be referenced as "name" as well.

`entities` a character vector of variable URLs, or a list containing a combination of variable URLs and VariableGroup objects.

`duplicates` logical: should duplicate variable references be allowed in this object? Default is FALSE.

`vars` either NULL or a [VariableCatalog](#). If not NULL, it will be used to look up variable names from the URLs.

versions	<i>Access the saved versions of a dataset</i>
----------	---

Description

This function allows you to see a dataset's savepoints. These can then be passed to [restoreVersion\(\)](#) to load the previously saved version of a dataset.

Usage

```
versions(x)
```

Arguments

x a CrunchDataset

Value

an object of class `VersionCatalog`. Supported methods on the catalog include "names" and "times-tamps".

See Also

[saveVersion](#) [restoreVersion](#)

webApp	<i>View a Dataset in the Web Application</i>
--------	--

Description

Convenience function that will use your system's "open" command to open a dataset in our web application in your default browser.

Usage

```
webApp(dataset)
```

Arguments

dataset a CrunchDataset

Details

Note that this function does not do anything on Windows.

Value

Nothing; called for side effect of opening your web browser.

weight	<i>Dataset weights</i>
--------	------------------------

Description

weight lets you view and set your user's currently applied weight on the server. weightVariables lets you view all of the variables that have been designated as valid to use as weights.

Usage

```
weight(x)

weight(x) <- value

is.weight(x)

## S4 replacement method for signature 'NumericVariable'
is.weight(x) <- value
```

Arguments

x	a Dataset
value	a Variable, VariableDefinition, or NULL. If a VariableDefinition is passed, the variable will first be created and then set as the datasets weight. Set to NULL to remove existing weights from the dataset.

Value

For the weight getter, a Variable if there is a weight, else NULL. For the setter, x, modified accordingly. weightVariables returns the aliases (or names, according to options(crunch.namekey.dataset)), of the variables designated as weights.

See Also

[weightVariables\(\)](#) [makeWeight\(\)](#)

weightVariables	<i>Get a dataset's weightVariables</i>
-----------------	--

Description

Get a dataset's weightVariables

Usage

```
## S4 method for signature 'CrunchDataset'
weightVariables(x)

## S4 method for signature 'VariableCatalog'
weightVariables(x)
```

Arguments

x a CrunchDataset

Value

weightVariables returns a character vector of the aliases of the variables that are eligible to be used as weights.

See Also

[weight\(\)](#) [makeWeight\(\)](#) [modifyWeightVariables\(\)](#)

which *"which" method for CrunchLogicalExpr*

Description

NOTE: this isn't correct. Don't use it yet.

Usage

```
## S4 method for signature 'CrunchLogicalExpr'
which(x, arr.ind = FALSE, useNames = TRUE)
```

Arguments

x CrunchLogicalExpr
arr.ind Ignored
useNames Ignored

Value

Integer row indices where x is true. Note that this does not return a Crunch expression. Use this when you need to translate to R values. For filtering a Crunch expression by x, don't use which.

with-context-manager *Context manager's "with" method*

Description

Context manager's "with" method

Usage

```
## S3 method for class 'contextManager'
with(data, expr, ...)
```

Arguments

data	contextManager
expr	code to evaluate within that context
...	additional arguments. One additional supported argument is "as", which lets you assign the return of your "enter" function to an object you can access.

Value

Nothing.

See Also

[ContextManager](#)

write.csv.gz *Write CSV to a compressed file*

Description

Write CSV to a compressed file

Usage

```
write.csv.gz(x, file, na = "", row.names = FALSE, ...)
```

Arguments

x	A data.frame or similar CSV-writable object
file	character destination to write the gzipped CSV to
na	See utils::write.csv . This just changes the default to a Crunch-friendly empty string.
row.names	logical: write out row names? See utils::write.csv .
...	Additional arguments passed to write.csv .

Value

A csv file written to dist

[,CrunchExpr,CrunchLogicalExpr,ANY-method
"Subset" a Variable

Description

These methods subset variables by creating Expressions, which can be composed and evaluated as needed.

Usage

```
## S4 method for signature 'CrunchExpr,CrunchLogicalExpr,ANY'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'CrunchExpr,logical,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchExpr,numeric,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchVariable,CrunchExpr,ANY'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'CrunchVariable,numeric,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchVariable,logical,ANY'
x[i, j, ..., drop = TRUE]
```

Arguments

x	a Variable
i	a CrunchExpr, logical, or numeric
j	Invalid
...	additional arguments, ignored
drop	Invalid

Value

a CrunchExpr containing references to the variable x and the filter logic contained in i

\$,AbstractCategory-method

Access Category fields directly

Description

Don't do this. Instead, use the category setters.

Usage

```
## S4 method for signature 'AbstractCategory'  
x$name
```

```
## S4 replacement method for signature 'AbstractCategory'  
x$name <- value
```

Arguments

x	a Category
name	a field within x
value	a value for that field to update

Value

\$ returns the value of the desired field. Setter returns x duly modified.

See Also

[describe-category](#)

Index

- !,CrunchExpr-method (expressions), [62](#)
- !=,CategoricalVariable,character-method (expressions), [62](#)
- !=,CategoricalVariable,factor-method (expressions), [62](#)
- .Insertion (Insertions-class), [72](#)
- ==,CategoricalVariable,character-method (expressions), [62](#)
- ==,CategoricalVariable,factor-method (expressions), [62](#)
- [,AbstractCategories,ANY,ANY-method (Categories-class), [17](#)
- [,AbstractCategories,character,ANY-method (Categories-class), [17](#)
- [,AbstractCategories,numeric,ANY-method (Categories-class), [17](#)
- [,CategoricalArrayVariable,character,ANY-method (subvars-extract), [129](#)
- [,CategoricalArrayVariable,missing,ANY-method (subvars-extract), [129](#)
- [,CategoricalArrayVariable,missing,character-method (subvars-extract), [129](#)
- [,CrunchDataset,ANY,ANY-method (dataset-extract), [40](#)
- [,CrunchDataset,CrunchLogicalExpr,ANY-method (dataset-extract), [40](#)
- [,CrunchDataset,CrunchLogicalExpr,missing-method (dataset-extract), [40](#)
- [,CrunchDataset,VariableGroup,ANY-method (dataset-extract), [40](#)
- [,CrunchDataset,VariableOrder,ANY-method (dataset-extract), [40](#)
- [,CrunchDataset,character,ANY-method (dataset-extract), [40](#)
- [,CrunchDataset,logical,missing-method (dataset-extract), [40](#)
- [,CrunchDataset,missing,ANY-method (dataset-extract), [40](#)
- [,CrunchExpr,CrunchLogicalExpr,ANY-method, [149](#)
- [,CrunchExpr,logical,ANY-method ([,CrunchExpr,CrunchLogicalExpr,ANY-method), [149](#)
- [,CrunchExpr,numeric,ANY-method ([,CrunchExpr,CrunchLogicalExpr,ANY-method), [149](#)
- [,CrunchVariable,CrunchExpr,ANY-method ([,CrunchExpr,CrunchLogicalExpr,ANY-method), [149](#)
- [,CrunchVariable,logical,ANY-method ([,CrunchExpr,CrunchLogicalExpr,ANY-method), [149](#)
- [,CrunchVariable,numeric,ANY-method ([,CrunchExpr,CrunchLogicalExpr,ANY-method), [149](#)
- cubeDims,ANY,ANY-method (cube-methods), [37](#)
- MemberCatalog,character,ANY-method (catalog-extract), [13](#)
- MemberOrderGroup,ANY,ANY-method (ShojiOrder-extract), [117](#)
- [,OrderGroup,character,ANY-method (ShojiOrder-extract), [117](#)
- [,PermissionCatalog,character,ANY-method (catalog-extract), [13](#)
- ShojiCatalog,ANY,ANY-method (catalog-extract), [13](#)
- [,ShojiCatalog,character,ANY-method (catalog-extract), [13](#)
- [,ShojiCatalog,logical,ANY-method (catalog-extract), [13](#)
- [,ShojiCatalog,numeric,ANY-method (catalog-extract), [13](#)
- [,ShojiOrder,ANY,ANY-method (ShojiOrder-extract), [117](#)
- [,ShojiOrder,character,ANY-method (ShojiOrder-extract), [117](#)
- [,Subvariables,character,ANY-method

- (subvars-extract), 129
- [,UserCatalog,character,ANY-method
(catalog-extract), 13
- [,VariableCatalog,VariableGroup,ANY-method
(catalog-extract), 13
- [,VariableCatalog,VariableOrder,ANY-method
(catalog-extract), 13
- [.CrunchDataFrame(CrunchDataFrame), 33
- [<- ,AbstractCategories,character,ANY,ANY-method
(Categories-class), 17
- [<- ,CategoricalArrayVariable,ANY,missing,character-method
(variable-update), 141
- [<- ,CategoricalArrayVariable,ANY,missing,factor-method
(variable-update), 141
- [<- ,CategoricalArrayVariable,ANY,missing,numeric-method
(variable-update), 141
- [<- ,CategoricalVariable,ANY,missing,character-method
(variable-update), 141
- [<- ,CategoricalVariable,ANY,missing,factor-method
(variable-update), 141
- [<- ,CategoricalVariable,ANY,missing,numeric-method
(variable-update), 141
- [<- ,Categories,ANY,ANY,ANY-method
(Categories-class), 17
- [<- ,CrunchDataset,ANY,missing,list-method
(dataset-update), 44
- [<- ,CrunchDataset,CrunchExpr,ANY,ANY-method
(dataset-update), 44
- [<- ,CrunchVariable,ANY,missing,ANY-method
(variable-update), 141
- [<- ,CrunchVariable,ANY,missing,CrunchExpr-method
(variable-update), 141
- [<- ,CrunchVariable,ANY,missing,CrunchLogicalExpr-method
(variable-update), 141
- [<- ,CrunchVariable,ANY,missing,CrunchVariable-method
(variable-update), 141
- [<- ,CrunchVariable,ANY,missing,NULL-method
(variable-update), 141
- [<- ,CrunchVariable,ANY,missing,logical-method
(variable-update), 141
- [<- ,DatetimeVariable,ANY,missing,Date-method
(variable-update), 141
- [<- ,DatetimeVariable,ANY,missing,POSIXt-method
(variable-update), 141
- [<- ,NumericVariable,ANY,missing,numeric-method
(variable-update), 141
- [<- ,ShojiCatalog,ANY,missing,ShojiCatalog-method
(catalog-extract), 13
- [<- ,ShojiOrder,ANY,missing,ShojiOrder-method
(ShojiOrder-extract), 117
- [<- ,ShojiOrder,character,missing,ShojiOrder-method
(ShojiOrder-extract), 117
- [<- ,Subvariables,ANY,missing,ANY-method
(subvars-extract), 129
- [<- ,Subvariables,ANY,missing,Subvariables-method
(subvars-extract), 129
- [<- ,Subvariables,character,missing,Subvariables-method
(subvars-extract), 129
- [<- ,TextFileVariable,ANY,missing,character-method
(variable-update), 141
- [<- ,VariableCatalog,VariableGroup,missing,VariableCatalog-
method
(catalog-extract), 13
- [<- ,VariableCatalog,VariableOrder,missing,VariableCatalog-
method
(catalog-extract), 13
- [<- ,CrunchDataFrame(CrunchDataFrame),
method
33
- [<- ,AbstractCategories,character-method
(Categories-class), 17
- [<- ,CategoricalArrayVariable,ANY-method
(subvars-extract), 129
- [,CategoricalArrayVariable,character-method
(subvars-extract), 129
- [,CategoricalVariable,ANY-method
(subvars-extract), 129
- [,CategoricalVariable,ANY,ANY-method
(Categories-class), 17
- [,CategoricalVariable,ANY-method
(subvars-extract), 129
- [,CrunchDataset,ANY-method
(dataset-extract), 40
- [,CrunchDataset,character-method
(dataset-extract), 40
- [,DatasetCatalog,numeric-method
(catalog-extract), 13
- [,FilterCatalog,numeric-method
(catalog-extract), 13
- [,MethodCatalog,character-method
(catalog-extract), 13
- [,MultitableCatalog,numeric-method
(catalog-extract), 13
- [,MultitableResult,ANY-method
(tabbook-methods), 132
- [,OrderGroup,ANY-method
(ShojiOrder-extract), 117
- [,OrderGroup,character-method
(ShojiOrder-extract), 117
- [,PermissionCatalog,character-method
(catalog-extract), 13
- [,ProjectCatalog,numeric-method
(catalog-extract), 13
- [,Session,ANY-method
(session-extract), 114

- [[, ShojiCatalog, ANY-method
(catalog-extract), 13
- [[, ShojiCatalog, character-method
(catalog-extract), 13
- [[, ShojiOrder, ANY-method
(ShojiOrder-extract), 117
- [[, ShojiOrder, character-method
(ShojiOrder-extract), 117
- [[, Subvariables, character-method
(subvars-extract), 129
- [[, Subvariables, numeric-method
(subvars-extract), 129
- [[, TabBookResult, character-method
(tabbook-methods), 132
- [[, TabBookResult, numeric-method
(tabbook-methods), 132
- [[, TeamCatalog, numeric-method
(catalog-extract), 13
- [[, UserCatalog, character-method
(catalog-extract), 13
- [[, VariableCatalog, numeric-method
(catalog-extract), 13
- [[. CrunchDataFrame (CrunchDataFrame), 33
- [[<-, AbstractCategories, character, ANY, ANY-method
(Categories-class), 17
- [[<-, CategoricalArrayVariable, ANY, missing, ANY-method
(subvars-extract), 129
- [[<-, CategoricalArrayVariable, character, missing, ANY-method
(subvars-extract), 129
- [[<-, CrunchDataset, ANY, ANY, ANY-method
(dataset-update), 44
- [[<-, CrunchDataset, ANY, missing, CrunchGeography-method
(dataset-update), 44
- [[<-, CrunchDataset, ANY, missing, CrunchVariable-method
(dataset-update), 44
- [[<-, CrunchDataset, ANY, missing, NULL-method
(dataset-update), 44
- [[<-, CrunchDataset, character, missing, ANY-method
(dataset-update), 44
- [[<-, CrunchDataset, character, missing, CrunchGeography-method
(dataset-update), 44
- [[<-, CrunchDataset, character, missing, CrunchLogicalExpr-method
(dataset-update), 44
- [[<-, CrunchDataset, character, missing, CrunchVariable-method
(dataset-update), 44
- [[<-, CrunchDataset, character, missing, NULL-method
(dataset-update), 44
- [[<-, DatasetCatalog, character, missing, DatasetCatalog-method
(catalog-extract), 13
- [[<-, FilterCatalog, character, missing, CrunchFilter-method
(catalog-extract), 13
- [[<-, FilterCatalog, character, missing, CrunchLogicalExpr-method
(catalog-extract), 13
- [[<-, FilterCatalog, numeric, missing, CrunchFilter-method
(catalog-extract), 13
- [[<-, FilterCatalog, numeric, missing, CrunchLogicalExpr-method
(catalog-extract), 13
- [[<-, MemberCatalog, ANY, missing, ANY-method
(catalog-extract), 13
- [[<-, MemberCatalog, character, missing, NULL-method
(catalog-extract), 13
- [[<-, MultitableCatalog, ANY, missing, NULL-method
(catalog-extract), 13
- [[<-, MultitableCatalog, character, missing, formula-method
(catalog-extract), 13
- [[<-, MultitableCatalog, numeric, missing, formula-method
(catalog-extract), 13
- [[<-, OrderGroup, ANY, missing, OrderGroup-method
(ShojiOrder-extract), 117
- [[<-, OrderGroup, character, missing, NULL-method
(ShojiOrder-extract), 117
- [[<-, OrderGroup, character, missing, OrderGroup-method
(ShojiOrder-extract), 117
- [[<-, OrderGroup, character, missing, ShojiOrder-method
(ShojiOrder-extract), 117
- [[<-, OrderGroup, character, missing, character-method
(ShojiOrder-extract), 117
- [[<-, OrderGroup, character, missing, list-method
(ShojiOrder-extract), 117
- [[<-, OrderGroup, numeric, missing, NULL-method
(ShojiOrder-extract), 117
- [[<-, ProjectCatalog, character, missing, CrunchProject-method
(catalog-extract), 13
- [[<-, ProjectCatalog, character, missing, list-method
(catalog-extract), 13
- [[<-, Session, ANY, ANY, ANY-method
(session-extract), 114
- [[<-, ShojiOrder, ANY, missing, ANY-method
(ShojiOrder-extract), 117
- [[<-, ShojiOrder, ANY, missing, NULL-method
(ShojiOrder-extract), 117
- [[<-, ShojiOrder, ANY, missing, OrderGroup-method
(ShojiOrder-extract), 117
- [[<-, ShojiOrder, character, missing, NULL-method
(ShojiOrder-extract), 117
- [[<-, ShojiOrder, character, missing, OrderGroup-method
(ShojiOrder-extract), 117

- (ShojiOrder-extract), 117
- [[<- , ShojiOrder, character, missing, ShojiOrder-method (ShojiOrder-extract), 117
- [[<- , ShojiOrder, character, missing, character-method (ShojiOrder-extract), 117
- [[<- , ShojiOrder, character, missing, list-method (ShojiOrder-extract), 117
- [[<- , Subvariables, ANY, missing, ANY-method (subvars-extract), 129
- [[<- , Subvariables, ANY, missing, CrunchVariable-method (subvars-extract), 129
- [[<- , Subvariables, ANY, missing, NULL-method (subvars-extract), 129
- [[<- , Subvariables, character, missing, CrunchVariable-method (subvars-extract), 129
- [[<- , TeamCatalog, character, missing, CrunchTeam-method (catalog-extract), 13
- [[<- , TeamCatalog, character, missing, list-method (catalog-extract), 13
- [[<- , VariableCatalog, character, missing, CrunchVariable-method (catalog-extract), 13
- [[<- , VariableCatalog, character, missing, Variable-method (catalog-extract), 13
- [[<- , VariableGroup, character, missing, CrunchDataset-method (ShojiOrder-extract), 117
- [[<- , VariableOrder, character, missing, CrunchDataset-method (ShojiOrder-extract), 117
- [[<- . CrunchDataFrame (CrunchDataFrame), 33
- \$. AbstractCategory-method, 150
- \$. CategoricalArrayVariable-method (subvars-extract), 129
- \$. CrunchDataset-method (dataset-extract), 40
- \$. OrderGroup-method (ShojiOrder-extract), 117
- \$. Session-method (session-extract), 114
- \$. ShojiCatalog-method (catalog-extract), 13
- \$. ShojiOrder-method (ShojiOrder-extract), 117
- \$. CrunchDataFrame (CrunchDataFrame), 33
- \$<- , AbstractCategory-method (\$, AbstractCategory-method), 150
- \$<- , CategoricalArrayVariable-method (subvars-extract), 129
- \$<- , CrunchDataset-method (dataset-extract), 40
- \$<- , ShojiOrder-method (ShojiOrder-extract), 117
- \$<- , CrunchDataset-method (dataset-update), 44
- \$<- , ShojiOrder-method (ShojiOrder-extract), 117
- \$<- , Session-method (session-extract), 114
- \$<- , ShojiCatalog-method (catalog-extract), 13
- \$<- , ShojiOrder-method (ShojiOrder-extract), 117
- \$<- , CrunchDataFrame (CrunchDataFrame), 33
- %in%, CategoricalVariable, character-method (expressions), 62
- %in%, CategoricalVariable, factor-method (expressions), 62
- %in%, CategoricalVariable, numeric-method (expressions), 62
- %in%, DatetimeVariable, Date-method (expressions), 62
- %in%, DatetimeVariable, POSIXt-method (expressions), 62
- %in%, DatetimeVariable, character-method (expressions), 62
- %in%, NumericVariable, numeric-method (expressions), 62
- %in%, TextVariable, character-method (expressions), 62
- addGeoMetadata, 6
- addSubvariable, 7
- addSubvariables (addSubvariable), 7
- addVariables, 7, 65
- alias, CrunchVariable-method (describe), 54
- alias<- (describe), 54
- alias<- , CrunchVariable-method (describe), 54
- aliases (names, BatchCatalog-method), 97
- aliases, CrunchCube-method (cube-methods), 37
- aliases, MultitableResult-method (tabbook-methods), 132
- aliases, TabBookResult-method (tabbook-methods), 132
- aliases, VariableCatalog-method (names, BatchCatalog-method), 97
- aliases<- (names, BatchCatalog-method), 97

- aliases<- ,VariableCatalog-method
(names, BatchCatalog-method), 97
- allVariables (dataset-variables), 46
- allVariables, CrunchDataset-method
(dataset-variables), 46
- allVariables<- (dataset-variables), 46
- allVariables<- ,CrunchDataset, VariableCatalog-method
(dataset-variables), 46
- anchor (Insertions-class), 72
- anchor, Heading-method
(Insertions-class), 72
- anchor, Insertion-method
(Insertions-class), 72
- anchor, Subtotal-method
(Insertions-class), 72
- anchor<- (Insertions-class), 72
- anchor<- ,Heading-method
(Insertions-class), 72
- anchor<- ,Insertion-method
(Insertions-class), 72
- anchor<- ,Subtotal-method
(Insertions-class), 72
- anchors (Insertions-class), 72
- anchors, Insertions-method
(Insertions-class), 72
- appendDataset, 8
- appendDataset(), 111
- appendStream, 8
- appendStream(), 105
- applyTransforms
(subtotalArray, CrunchCube-method),
127
- archive
(is.archived, DatasetCatalog-method),
77
- archive-and-publish
(is.archived, DatasetCatalog-method),
77
- are.Headings (Subtotal-class), 124
- are.Subtotals (Subtotal-class), 124
- arguments (Insertions-class), 72
- arguments, Heading-method
(Insertions-class), 72
- arguments, Insertion-method
(Insertions-class), 72
- arguments, Subtotal-method
(Insertions-class), 72
- arguments<- (Insertions-class), 72
- arguments<- ,Heading-method
(Insertions-class), 72
- arguments<- ,Insertion-method
(Insertions-class), 72
- arguments<- ,Subtotal-method
(Insertions-class), 72
- as.data.frame, 10
- as.data.frame.BatchCatalog
(catalog-dataframes), 12
- as.data.frame.CrunchDataFrame
(dataset-to-R), 43
- as.data.frame.CrunchDataset
(dataset-to-R), 43
- as.data.frame.FilterCatalog
(catalog-dataframes), 12
- as.data.frame.ShojiCatalog
(catalog-dataframes), 12
- as.data.frame.VariableCatalog
(catalog-dataframes), 12
- as.environment, CrunchDataset-method, 9
- as.vector(), 44
- as.vector, CrunchExpr-method, 9
- as.vector, CrunchVariable-method
(as.vector, CrunchExpr-method),
9
- availableGeodata
(CrunchGeography-class), 34
- availableGeodataFeatures, 10
- base::array, 39
- base::dim(), 57
- base::duplicated, 48
- base::duplicated(), 59
- base::levels(), 19
- base::margin.table(), 36, 37
- base::match(), 63
- base::max(), 32
- base::mean(), 32
- base::min(), 32
- base::names(), 99
- base::prop.table(), 36, 37
- base::round(), 37
- base::table, 133, 134
- base::table(), 29
- bases (cube-computing), 36
- bases, CrunchCube-method
(cube-computing), 36
- bases, MultitableResult-method
(cube-computing), 36

- bases, TabBookResult-method
(cube-computing), 36
- batches, 11
- bin (expressions), 62
- c, 12
- c-categories, 11
- c.Categories (c-categories), 11
- c.Category (c-categories), 11
- catalog-dataframes, 12
- catalog-extract, 13
- catalog-length, 17
- CategoricalArrayVariable
(CrunchVariable-class), 36
- CategoricalArrayVariable-class
(CrunchVariable-class), 36
- CategoricalVariable
(CrunchVariable-class), 36
- CategoricalVariable-class
(CrunchVariable-class), 36
- Categories, 12, 56, 97, 99
- Categories (Categories-class), 17
- categories (var-categories), 140
- categories(), 73
- categories, CategoricalArrayVariable-method
(var-categories), 140
- categories, CategoricalVariable-method
(var-categories), 140
- categories, CrunchVariable-method
(var-categories), 140
- categories, VariableEntity-method
(var-categories), 140
- categories, VariableTuple-method
(var-categories), 140
- Categories-class, 17
- categories<- (var-categories), 140
- categories<-, CategoricalArrayVariable, ANY-method
(var-categories), 140
- categories<-, CategoricalArrayVariable, Categories-method
(var-categories), 140
- categories<-, CategoricalArrayVariable, character-method
(var-categories), 140
- categories<-, CategoricalArrayVariable, numeric-method
(var-categories), 140
- categories<-, CategoricalVariable, ANY-method
(var-categories), 140
- categories<-, CategoricalVariable, Categories-method
(var-categories), 140
- categories<-, CategoricalVariable, character-method
(var-categories), 140
- categories<-, CategoricalVariable, numeric-method
(var-categories), 140
- categories<-, CrunchVariable, ANY-method
(var-categories), 140
- categoriesFromLevels, 19
- Category (Categories-class), 17
- Category-class (Categories-class), 17
- category-extract
(\$, AbstractCategory-method),
150
- changeCategoryID, 19
- cleanseBatches, 20
- collapseCategories, 21
- combine, 21
- combine(), 21
- compareDatasets, 22
- conditionalTransform, 23
- consent, 25
- ContextManager, 25, 25, 134, 148
- contextManager, 148
- contextManager (ContextManager), 25
- copy (copyVariable), 27
- copy(), 22
- copyOrder, 26
- copyVariable, 27
- crDELETE (http-methods), 71
- createDataset, 107
- createDataset(), 99
- createWithPreparedData, 28
- crGET (http-methods), 71
- crPATCH (http-methods), 71
- crPOST (http-methods), 71
- crPUT (http-methods), 71
- crtabs, 28
- crtabs(), 9
- crunch, 29
- crunch, 29
- crunch-package (crunch), 29
- crunchAPI, 31
- crunchAPI, 71
- CrunchBox, 107
- CrunchBox (crunchBox), 32
- crunchBox, 32
- crunchBox(), 59
- CrunchDataFrame, 33
- CrunchDataset, 104

- CrunchDataset (CrunchDataset-class), 34
- CrunchDataset-class, 34
- CrunchExpr, 52
- CrunchGeography, 6
- CrunchGeography
 - (CrunchGeography-class), 34
- CrunchGeography-class, 34
- CrunchVariable-class, 36
- cube-computing, 36
- cube-methods, 37
- cube-residuals, 39
- cut, NumericVariable-method
 - (crunch-cut), 29

- dashboard, 40
- dashboard<- (dashboard), 40
- data.frame, 33
- dataset-extract, 40
- dataset-owner, 42
- dataset-to-R, 43
- dataset-update, 44
- dataset-variables, 46
- DatasetGroup (DatasetOrder-class), 47
- DatasetGroup-class
 - (DatasetOrder-class), 47
- DatasetOrder (DatasetOrder-class), 47
- DatasetOrder-class, 47
- datasets, 47
- datasets<- (datasets), 47
- DatetimeVariable
 - (CrunchVariable-class), 36
- DatetimeVariable-class
 - (CrunchVariable-class), 36
- dedupeOrder, 48
- delete, 49, 50
- delete(), 50
- delete, ANY-method (delete), 49
- delete, CrunchDataset-method (delete), 49
- delete, CrunchProject-method (delete), 49
- delete, CrunchTeam-method (delete), 49
- delete, CrunchVariable-method (delete), 49
- delete, Multitable-method (delete), 49
- delete, ShojiObject-method (delete), 49
- delete, VariableTuple-method (delete), 49
- deleteDataset, 50, 50
- deleteSubvariable, 129
- deleteSubvariable (deleteSubvariables), 51
- deleteSubvariables, 51
- deleteVariable (deleteVariables), 51
- deleteVariables, 51
- derivation (derivations), 52
- derivation, CrunchVariable-method
 - (derivations), 52
- derivation<- (derivations), 52
- derivation<- , CrunchVariable, ANY-method
 - (derivations), 52
- derivation<- , CrunchVariable, NULL-method
 - (derivations), 52
- derivations, 52
- deriveArray (makeArray), 85
- describe, 54
- describe-catalog
 - (names, BatchCatalog-method), 97
- describe-category
 - (name, AbstractCategory-method), 96
- description (describe), 54
- description, CrunchDataset-method
 - (describe), 54
- description, CrunchVariable-method
 - (describe), 54
- description, Geodata-method (describe), 54
- description<- (describe), 54
- description<- , CrunchDataset-method
 - (describe), 54
- description<- , CrunchVariable-method
 - (describe), 54
- descriptions
 - (names, BatchCatalog-method), 97
- descriptions, CrunchCube-method
 - (cube-methods), 37
- descriptions, MultitableResult-method
 - (tabbook-methods), 132
- descriptions, TabBookResult-method
 - (tabbook-methods), 132
- descriptions, VariableCatalog-method
 - (names, BatchCatalog-method), 97
- descriptions, VersionCatalog-method
 - (names, BatchCatalog-method), 97
- descriptions<-
 - (names, BatchCatalog-method), 97
- descriptions<- , VariableCatalog-method
 - (names, BatchCatalog-method), 97
- dichotomize, 56, 97

- dichotomize, CategoricalArrayVariable, ANY-method (dichotomize), [56](#)
- dichotomize, CategoricalVariable, ANY-method (dichotomize), [56](#)
- dichotomize, Categories, character-method (dichotomize), [56](#)
- dichotomize, Categories, logical-method (dichotomize), [56](#)
- dichotomize, Categories, numeric-method (dichotomize), [56](#)
- digits (describe), [54](#)
- digits, CrunchVariable-method (describe), [54](#)
- digits<- (describe), [54](#)
- digits<-, CrunchVariable-method (describe), [54](#)
- digits<-, NumericVariable-method (describe), [54](#)
- dim, CrunchCube-method (cube-methods), [37](#)
- dim, CrunchDataset-method (dim-dataset), [57](#)
- dim, CubeDims-method (cube-methods), [37](#)
- dim, TabBookResult-method (tabbook-methods), [132](#)
- dim-dataset, [57](#)
- dim.CrunchDataFrame (CrunchDataFrame), [33](#)
- dimensions (cube-methods), [37](#)
- dimensions, CrunchCube-method (cube-methods), [37](#)
- dimensions<- (cube-methods), [37](#)
- dimensions<-, CrunchCube, CubeDims-method (cube-methods), [37](#)
- dimnames, CrunchCube-method (cube-methods), [37](#)
- dimnames, CubeDims-method (cube-methods), [37](#)
- dropRows, [58](#)
- deduplicated, [58](#)
- deduplicated, CrunchExpr-method (deduplicated), [58](#)
- deduplicated, CrunchVariable-method (deduplicated), [58](#)
- deduplicates, [48](#)
- deduplicates (ShojiOrder-slots), [120](#)
- deduplicates, OrderGroup-method (ShojiOrder-slots), [120](#)
- deduplicates, ShojiOrder-method (ShojiOrder-slots), [120](#)
- deduplicates, VariableCatalog-method (ShojiOrder-slots), [120](#)
- deduplicates<- (ShojiOrder-slots), [120](#)
- deduplicates<-, OrderGroup, logical-method (ShojiOrder-slots), [120](#)
- deduplicates<-, ShojiOrder, logical-method (ShojiOrder-slots), [120](#)
- deduplicates<-, VariableCatalog, logical-method (ShojiOrder-slots), [120](#)
- emails (names, BatchCatalog-method), [97](#)
- emails, ShojiCatalog-method (names, BatchCatalog-method), [97](#)
- embedCrunchBox, [59](#)
- endDate (describe), [54](#)
- endDate, CrunchDataset-method (describe), [54](#)
- endDate<- (describe), [54](#)
- endDate<-, CrunchDataset-method (describe), [54](#)
- entities (ShojiOrder-slots), [120](#)
- entities, list-method (ShojiOrder-slots), [120](#)
- entities, OrderGroup-method (ShojiOrder-slots), [120](#)
- entities, ShojiOrder-method (ShojiOrder-slots), [120](#)
- entities<- (ShojiOrder-slots), [120](#)
- entities<-, OrderGroup-method (ShojiOrder-slots), [120](#)
- entities<-, ShojiOrder-method (ShojiOrder-slots), [120](#)
- exclusion, [58](#), [60](#)
- exclusion<- (exclusion), [60](#)
- exportDataset, [61](#)
- exportDataset(), [10](#)
- expressions, [62](#)
- expropriateUser, [63](#)
- extendDataset (joinDatasets), [81](#)
- filter-catalog, [64](#)
- filters (filter-catalog), [64](#)
- filters(), [100](#)
- filters, CrunchDataset-method (filter-catalog), [64](#)
- filters<- (filter-catalog), [64](#)
- filters<-, CrunchDataset-method (filter-catalog), [64](#)

- flattenOrder, 65
- flipArrays, 65
- folder, 66
- folder(), 95
- folder<- (folder), 66
- forkDataset, 67
- fortify, 67
- func (Insertions-class), 72
- func, Heading-method (Insertions-class), 72
- func, Insertion-method (Insertions-class), 72
- func, Subtotal-method (Insertions-class), 72
- func<- (Insertions-class), 72
- funcs (Insertions-class), 72
- funcs, Insertions-method (Insertions-class), 72
- geo (CrunchGeography-class), 34
- geo(), 6
- geo, CrunchVariable-method (CrunchGeography-class), 34
- geo<- (CrunchGeography-class), 34
- geo<- , CrunchVariable, CrunchGeography-method (CrunchGeography-class), 34
- geo<- , CrunchVariable, NULL-method (CrunchGeography-class), 34
- Geodata (CrunchGeography-class), 34
- Geodata-class (CrunchGeography-class), 34
- getTeams, 68, 91
- getTeams(), 90
- grouped, 68, 122
- Heading (Subtotal-class), 124
- Heading(), 74, 138
- Heading-class (Subtotal-class), 124
- headings, 74
- hiddenVariables, 69
- hiddenVariables<- (hideVariables), 70
- hide, 50, 52, 69, 70
- hide(), 51
- hide, CrunchVariable-method (hide), 69
- hide, VariableCatalog-method (hide), 69
- hideVariables, 70, 70
- http-methods, 71
- icon (project-icon), 108
- icon<- (project-icon), 108
- id (name, AbstractCategory-method), 96
- id, AbstractCategory-method (name, AbstractCategory-method), 96
- id, CrunchDataset-method (describe), 54
- id, AbstractCategory (Categories-class), 17
- ids (Categories-class), 17
- ids, AbstractCategories-method (Categories-class), 17
- ids, VariableCatalog-method (names, BatchCatalog-method), 97
- ids, AbstractCategories (Categories-class), 17
- ids<- (Categories-class), 17
- ids<- , Categories-method (Categories-class), 17
- importMultitable, 71
- index (shoji-index), 116
- index, ShojiCatalog-method (shoji-index), 116
- index<- (shoji-index), 116
- index<- , ShojiCatalog-method (shoji-index), 116
- Insertion (Insertions-class), 72
- Insertion-class (Insertions-class), 72
- Insertions, 138
- Insertions (Insertions-class), 72
- Insertions-class, 72
- interactVariables, 74
- is-na-categories, 75
- is-public, 76
- is-selected-categories, 77
- is.archived (is.archived, DatasetCatalog-method), 77
- is.archived, CrunchDataset-method (is.archived, DatasetCatalog-method), 77
- is.archived, DatasetCatalog-method, 77
- is.archived<- (is.archived, DatasetCatalog-method), 77
- is.archived<- , CrunchDataset, logical-method (is.archived, DatasetCatalog-method), 77
- is.archived<- , DatasetCatalog, logical-method

- (is.archived, DatasetCatalog-method), 77
- is.Array (is.dataset), 79
- is.CA (is.dataset), 79
- is.Categorical (is.dataset), 79
- is.CategoricalArray (is.dataset), 79
- is.CrunchExpr (is.dataset), 79
- is.dataset, 79
- is.Datetime (is.dataset), 79
- is.derived (derivations), 52
- is.derived, CrunchVariable-method (derivations), 52
- is.derived<- (derivations), 52
- is.derived<-, CrunchVariable, logical-method (derivations), 52
- is.dichotomized (dichotomize), 56
- is.dichotomized, Categories-method (dichotomize), 56
- is.draft
 - (is.archived, DatasetCatalog-method), 77
- is.draft, CrunchDataset-method (is.archived, DatasetCatalog-method), 77
- is.draft, DatasetCatalog-method (is.archived, DatasetCatalog-method), 77
- is.draft<-
 - (is.archived, DatasetCatalog-method), 77
- is.draft<-, CrunchDataset, logical-method (is.archived, DatasetCatalog-method), 77
- is.draft<-, DatasetCatalog, logical-method (is.archived, DatasetCatalog-method), 77
- is.editor, 80
- is.editor, MemberCatalog-method (is.editor), 80
- is.editor, PermissionCatalog-method (is.editor), 80
- is.editor, PermissionTuple-method (is.editor), 80
- is.editor<- (is.editor), 80
- is.editor<-, MemberCatalog, logical-method (is.editor), 80
- is.Expr (is.dataset), 79
- is.Geodata (is.dataset), 79
- is.Heading (Subtotal-class), 124
- is.MR (is.dataset), 79
- is.Multiple (is.dataset), 79
- is.MultipleResponse (is.dataset), 79
- is.na, Categories-method (is-na-categories), 75
- is.na, Category-method (is-na-categories), 75
- is.na, CrunchVariable-method (expressions), 62
- is.na, CubeDims-method (cube-methods), 37
- is.na<-, Categories, character-method (is-na-categories), 75
- is.na<-, Categories, logical-method (is-na-categories), 75
- is.na<-, Category, logical-method (is-na-categories), 75
- is.na<-, CrunchVariable, ANY-method (variable-update), 141
- is.Numeric (is.dataset), 79
- is.public (is-public), 76
- is.public, CrunchFilter-method (is-public), 76
- is.public, Multitable-method (is-public), 76
- is.public, MultitableCatalog-method (is-public), 76
- is.public<- (is-public), 76
- is.public<-, CrunchFilter-method (is-public), 76
- is.public<-, Multitable-method (is-public), 76
- is.public<-, MultitableCatalog-method (is-public), 76
- is.published
 - (is.archived, DatasetCatalog-method), 77
- is.published, CrunchDataset-method (is.archived, DatasetCatalog-method), 77
- is.published, DatasetCatalog-method (is.archived, DatasetCatalog-method), 77
- is.published<-
 - (is.archived, DatasetCatalog-method), 77
- is.published<-, CrunchDataset, logical-method (is.archived, DatasetCatalog-method), 77

- 77
- is.published<-, DatasetCatalog, logical-method
(is.archived, DatasetCatalog-method),
77
- is.selected
(name, AbstractCategory-method),
96
- is.selected, Categories-method
(is-selected-categories), 77
- is.selected, Category-method
(name, AbstractCategory-method),
96
- is.selected<- (is-selected-categories),
77
- is.selected<-, Categories-method
(is-selected-categories), 77
- is.selected<-, Category-method
(is-selected-categories), 77
- is.shoji (is.dataset), 79
- is.Subtotal (Subtotal-class), 124
- is.Text (is.dataset), 79
- is.variable (is.dataset), 79
- is.weight (weight), 146
- is.weight<- (weight), 146
- is.weight<-, NumericVariable-method
(weight), 146
- is.weightVariable
(modifyWeightVariables), 92
- is.weightVariable<-
(modifyWeightVariables), 92
- is.weightVariable<-, NumericVariable-method
(modifyWeightVariables), 92

- joinDatasets, 81
- jsonlite::toJSON(), 134, 135
- jsonprep (tojson-crunch), 134
- jsonprep, AbstractCategories-method
(tojson-crunch), 134
- jsonprep, ANY-method (tojson-crunch), 134
- jsonprep, OrderGroup-method
(tojson-crunch), 134
- jsonprep, ShojiOrder-method
(tojson-crunch), 134

- length, MultitableResult-method
(tabbook-methods), 132
- length, OrderGroup-method
(ShojiOrder-length), 120
- length, ShojiCatalog-method
(catalog-length), 17
- length, ShojiOrder-method
(ShojiOrder-length), 120
- length, TabBookResult-method
(tabbook-methods), 132
- listDatasets, 82
- listDatasets(), 50
- loadDataset, 83
- loadDataset(), 82
- locateEntity, 83
- lock, 84
- login, 84
- logout, 85

- makeArray, 85
- makeCaseVariable, 30, 86
- makeMR (makeArray), 85
- makeWeight, 87
- makeWeight(), 146, 147
- margin.table (cube-computing), 36
- margin.table, CrunchCube-method
(cube-computing), 36
- matchCatToFeat, 89
- matchCatToFeat(), 6
- max (crunch-uni), 31
- max, CrunchVariable-method (crunch-uni),
31
- max, DatetimeVariable-method
(crunch-uni), 31
- max, NumericVariable-method
(crunch-uni), 31
- me, 89
- mean (crunch-uni), 31
- mean, CrunchVariable-method
(crunch-uni), 31
- mean, NumericVariable-method
(crunch-uni), 31
- measures (cube-methods), 37
- measures, CrunchCube-method
(cube-methods), 37
- median (crunch-uni), 31
- members
(members<-, CrunchTeam, MemberCatalog-method),
90
- members, CrunchProject-method
(members<-, CrunchTeam, MemberCatalog-method),
90

- members, CrunchTeam-method
(members<-, CrunchTeam, MemberCatalog-method), 96
- members<- , CrunchTeam, MemberCatalog-method, 90
- members<-
(members<-, CrunchTeam, MemberCatalog-method), 90
- members<- , CrunchProject, character-method
(members<-, CrunchTeam, MemberCatalog-method), 90
- members<- , CrunchProject, MemberCatalog-method
(members<-, CrunchTeam, MemberCatalog-method), 90
- members<- , CrunchTeam, character-method
(members<-, CrunchTeam, MemberCatalog-method), 90
- merge, 81, 91
- merge.CrunchDataset (joinDatasets), 81
- mergeFork, 92
- methods::show, 123
- min (crunch-uni), 31
- min, CrunchVariable-method (crunch-uni), 31
- min, DatetimeVariable-method
(crunch-uni), 31
- min, NumericVariable-method
(crunch-uni), 31
- mkdir (mv), 95
- modifyWeightVariables, 92
- modifyWeightVariables(), 147
- moveToGroup, 93
- moveToGroup<- (moveToGroup), 93
- MultipleResponseVariable
(CrunchVariable-class), 36
- MultipleResponseVariable-class
(CrunchVariable-class), 36
- multitable-catalog, 94
- multitables (multitable-catalog), 94
- multitables, CrunchDataset-method
(multitable-catalog), 94
- multitables<- (multitable-catalog), 94
- multitables<- , CrunchDataset-method
(multitable-catalog), 94
- mv, 95
- mv(), 66
- na-omit-categories, 96
- na.omit, Categories-method
(na-omit-categories), 96
- name (describe), 54
- name, AbstractCategory-method, 96
- name, CrunchDataset-method (describe), 54
- name, CrunchVariable-method (describe), 54
- name, OrderGroup-method
(ShojiOrder-slots), 120
- name, ShojiObject-method (describe), 54
- name<- (describe), 54
- name<- , AbstractCategory-method
(name, AbstractCategory-method), 96
- name<- , CrunchDataset-method (describe), 54
- name<- , CrunchVariable-method
(describe), 54
- name<- , Multitable-method (describe), 54
- name<- , NULL-method
(name, AbstractCategory-method), 96
- name<- , OrderGroup-method
(ShojiOrder-slots), 120
- names, AbstractCategories-method
(Categories-class), 17
- names, BatchCatalog-method, 97
- names, CategoricalArrayVariable-method
(names, BatchCatalog-method), 97
- names, CrunchCube-method (cube-methods), 37
- names, CrunchDataset-method
(names, BatchCatalog-method), 97
- names, MultitableResult-method
(tabbook-methods), 132
- names, OrderGroup-method
(ShojiOrder-slots), 120
- names, ShojiCatalog-method
(names, BatchCatalog-method), 97
- names, ShojiOrder-method
(ShojiOrder-slots), 120
- names, TabBookResult-method
(tabbook-methods), 132
- names, VersionCatalog-method
(names, BatchCatalog-method), 97
- names.CrunchDataFrame
(CrunchDataFrame), 33
- names<- , AbstractCategories-method

- (Categories-class), 17
- names<-, MultitableCatalog-method
 - (names, BatchCatalog-method), 97
- names<-, ShojiCatalog-method
 - (names, BatchCatalog-method), 97
- names<-, ShojiOrder-method
 - (ShojiOrder-slots), 120
- ncol, CrunchDataset-method
 - (dim-dataset), 57
- newDataset, 99
- newDatasetByColumn(), 100
- newDatasetFromFile(), 100
- newFilter, 100
- newMultitable, 101
- newProject, 102
- notes (describe), 54
- notes, CrunchCube-method (cube-methods), 37
- notes, CrunchDataset-method (describe), 54
- notes, CrunchVariable-method (describe), 54
- notes, VariableCatalog-method
 - (names, BatchCatalog-method), 97
- notes<- (describe), 54
- notes<-, CrunchDataset-method
 - (describe), 54
- notes<-, CrunchVariable-method
 - (describe), 54
- notes<-, VariableCatalog-method
 - (names, BatchCatalog-method), 97
- noTransforms, 103
- NumericVariable (CrunchVariable-class), 36
- NumericVariable-class
 - (CrunchVariable-class), 36
- ordering, 26, 104
- ordering, CrunchDataset-method
 - (ordering), 104
- ordering, DatasetCatalog-method
 - (ordering), 104
- ordering, VariableCatalog-method
 - (ordering), 104
- ordering<- (ordering), 104
- ordering<-, CrunchDataset-method
 - (ordering), 104
- ordering<-, DatasetCatalog-method
 - (ordering), 104
- ordering<-, VariableCatalog-method
 - (ordering), 104
- owner (dataset-owner), 42
- owner, CrunchDataset-method
 - (dataset-owner), 42
- owner<- (dataset-owner), 42
- owner<-, CrunchDataset-method
 - (dataset-owner), 42
- ownerNames (owners), 104
- owners, 104
- pendingStream, 105
- permissions, 105
- permissions, CrunchDataset-method
 - (permissions), 105
- pk, 106
- pk, CrunchDataset-method (pk), 106
- pk<- (pk), 106
- pk<-, CrunchDataset-method (pk), 106
- preCrunchBoxCheck, 107
- preCrunchBoxCheck(), 32
- prepareDataForCrunch, 107
- prepareDataForCrunch(), 28
- project-icon, 108
- projects, 108
- projects(), 102
- prop.table (cube-computing), 36
- prop.table, CrunchCube-method
 - (cube-computing), 36
- prop.table, MultitableResult-method
 - (cube-computing), 36
- prop.table, TabBookResult-method
 - (cube-computing), 36
- publish
 - (is.archived, DatasetCatalog-method), 77
- refresh, 109
- refresh(), 139
- refresh, CrunchDataset-method (refresh), 109
- refresh, CrunchVariable-method
 - (refresh), 109
- refresh, ShojiObject-method (refresh), 109
- removeEmptyGroups, 110
- resetPassword, 110
- restoreVersion, 111, 112, 145
- restoreVersion(), 111, 145

- rollup (expressions), 62
- round (cube-computing), 36
- round, CrunchCube-method (cube-computing), 36
- rstandard, CrunchCube-method (cube-residuals), 39

- saveVersion, 111, 111, 145
- saveVersion(), 111
- scoreCatToFeat, 112
- sd (crunch-uni), 31
- sd, CrunchVariable-method (crunch-uni), 31
- sd, NumericVariable-method (crunch-uni), 31
- searchDatasets, 112
- self, 113
- self, CrunchVariable-method (self), 113
- self, ShojiObject-method (self), 113
- session, 113
- session-extract, 114
- setDashboardURL (dashboard), 40
- settings, 115
- settings(), 88
- settings<- (settings), 115
- share, 116, 139
- shoji-index, 116
- ShojiObject (ShojiObject-class), 117
- ShojiObject-class, 117
- ShojiOrder-extract, 117
- ShojiOrder-length, 120
- ShojiOrder-slots, 120
- show, Categories-method (show-crunch), 122
- show, Category-method (show-crunch), 122
- show, CrunchCube-method (show-crunch), 122
- show, CrunchExpr-method (show-crunch), 122
- show, CrunchGeography-method (show-crunch), 122
- show, CrunchLogicalExpr-method (show-crunch), 122
- show, CrunchVariable-method (show-crunch), 122
- show, Insertion-method (show-crunch), 122
- show, Insertions-method (show-crunch), 122
- show, MultitableResult-method (show-crunch), 122
- show, OrderGroup-method (show-crunch), 122
- show, ShojiObject-method (show-crunch), 122
- show-crunch, 122
- showTransforms (showTransforms, CrunchCube-method), 123
- showTransforms, CategoricalVariable-method (showTransforms, CrunchCube-method), 123
- showTransforms, CrunchCube-method, 123
- startDate (describe), 54
- startDate, CrunchDataset-method (describe), 54
- startDate<- (describe), 54
- startDate<-, CrunchDataset-method (describe), 54
- stats::chisq.test, 39
- stats::formula, 101
- stats::formula(), 101
- stats::lm(), 43
- stats::median(), 32
- stats::sd(), 32
- stats::xtabs(), 28
- subset, CrunchDataset-method (dataset-extract), 40
- Subtotal (Subtotal-class), 124
- Subtotal(), 74, 138
- Subtotal-class, 124
- subtotalArray (subtotalArray, CrunchCube-method), 127
- subtotalArray, CrunchCube-method, 127
- Subtotals, 127
- subtotals, 74
- subtotals (Subtotal-class), 124
- subtotals, CrunchVariable-method (Subtotal-class), 124
- subtotals, VariableTuple-method (Subtotal-class), 124
- subtotals<- (Subtotal-class), 124
- subtotals<-, CrunchVariable, ANY-method (Subtotal-class), 124
- subtotals<-, CrunchVariable, NULL-method (Subtotal-class), 124

- subtotals<- , Insertion, ANY-method
(Insertions-class), 72
- SubtotalsHeadings (Subtotal-class), 124
- Subvariables, 97, 99
- Subvariables (Subvariables-class), 128
- subvariables, 7
- subvariables (Subvariables-class), 128
- subvariables, CategoricalArrayVariable-method
(Subvariables-class), 128
- subvariables, VariableTuple-method
(Subvariables-class), 128
- Subvariables-class, 128
- subvariables<- (Subvariables-class), 128
- subvariables<- , CategoricalArrayVariable, ANY-method
(Subvariables-class), 128
- subvariables<- , CategoricalArrayVariable, Subvariables-class
(Subvariables-class), 128
- subvars-extract, 129

- tabBook, 131
- tabBook(), 37
- tabbook-methods, 132
- table, 133
- teams, 68
- teams
(members<- , CrunchTeam, MemberCatalog-method),
90
- temp.option (temp.options), 134
- temp.options, 134
- TextVariable (CrunchVariable-class), 36
- TextVariable-class
(CrunchVariable-class), 36
- timestamps (names, BatchCatalog-method),
97
- timestamps, VersionCatalog-method
(names, BatchCatalog-method), 97
- toJSON (tojson-crunch), 134
- tojson-crunch, 134
- toVariable, 135, 143
- toVariable, AsIs-method (toVariable), 135
- toVariable, character-method
(toVariable), 135
- toVariable, CrunchExpr-method
(toVariable), 135
- toVariable, Date-method (toVariable), 135
- toVariable, factor-method (toVariable),
135
- toVariable, logical-method (toVariable),
135
- toVariable, numeric-method (toVariable),
135
- toVariable, POSIXt-method (toVariable),
135
- toVariable, VariableDefinition-method
(toVariable), 135
- transformations, 72
- Transforms (Transforms-class), 137
- transforms (Transforms-class), 137
- transforms, CrunchCube-method
(Transforms-class), 137
- transforms, CrunchVariable-method
(Transforms-class), 137
- transforms, VariableCatalog-method
(Transforms-class), 137
- transforms, VariableTuple-method
(Transforms-class), 137
- Transforms-class, 137
- transforms<- (Transforms-class), 137
- transforms<- , CrunchCube, list-method
(Transforms-class), 137
- transforms<- , CrunchCube, NULL-method
(Transforms-class), 137
- transforms<- , CrunchVariable, NULL-method
(Transforms-class), 137
- transforms<- , CrunchVariable, Transforms-method
(Transforms-class), 137
- type, 138
- type, CrunchVariable-method (type), 138
- type<- (type), 138
- type<- , CrunchVariable-method (type), 138
- types (names, BatchCatalog-method), 97
- types, CrunchCube-method (cube-methods),
37
- types, VariableCatalog-method
(names, BatchCatalog-method), 97

- unbind, 139
- undichotomize (dichotomize), 56
- undichotomize, CategoricalArrayVariable-method
(dichotomize), 56
- undichotomize, CategoricalVariable-method
(dichotomize), 56
- undichotomize, Categories-method
(dichotomize), 56
- ungrouped (grouped), 68
- unhide (hide), 69
- unhide, CrunchVariable-method (hide), 69
- unhide, VariableCatalog-method (hide), 69

- unhideVariables (hideVariables), 70
- unlock (lock), 84
- unshare, 116, 139
- utils::write.csv, 148
- utils::write.table(), 61
- value (name, AbstractCategory-method), 96
- value, Category-method
 - (name, AbstractCategory-method), 96
- value<- (name, AbstractCategory-method), 96
- value<-, Category-method
 - (name, AbstractCategory-method), 96
- values (Categories-class), 17
- values, Categories-method
 - (Categories-class), 17
- values<- (Categories-class), 17
- values<-, Categories-method
 - (Categories-class), 17
- var-categories, 140
- VarDef (VariableDefinition), 143
- variable-extract
 - ([, CrunchExpr, CrunchLogicalExpr, ANY-method), 149
- variable-to-R
 - (as.vector, CrunchExpr-method), 9
- variable-update, 141
- VariableCatalog, 104, 144
- VariableCatalog
 - (VariableCatalog-class), 142
- VariableCatalog-class, 142
- VariableDefinition, 8, 22, 30, 75, 87, 136, 143
- VariableDefinition(), 88
- VariableGroup (VariableOrder-class), 144
- VariableGroup-class
 - (VariableOrder-class), 144
- variableMetadata, 144
- VariableOrder, 26, 68, 104, 122, 142
- VariableOrder (VariableOrder-class), 144
- VariableOrder-class, 144
- variables (dataset-variables), 46
- variables, CrunchCube-method
 - (cube-methods), 37
- variables, CrunchDataset-method
 - (dataset-variables), 46
- variables, CubeDims-method
 - (cube-methods), 37
- variables, SearchResults-method
 - (dataset-variables), 46
- variables<- (dataset-variables), 46
- variables<-, CrunchDataset, VariableCatalog-method
 - (dataset-variables), 46
- versions, 111, 112, 145
- versions(), 111
- webApp, 145
- weight, 29, 131, 146
- weight(), 29, 88, 147
- weight<- (weight), 146
- weightVariables, 146
- weightVariables(), 146
- weightVariables, CrunchDataset-method
 - (weightVariables), 146
- weightVariables, VariableCatalog-method
 - (weightVariables), 146
- weightVariables<-
 - (modifyWeightVariables), 92
- weightVariables<-, CrunchDataset-method
 - (modifyWeightVariables), 92
- which, CrunchLogicalExpr-method (which), 147
- with-context-manager, 148
- with.contextManager
 - (with-context-manager), 148
- with_consent (consent), 25
- with_consent(), 49, 51, 52, 64
- write.csv (exportDataset), 61
- write.csv, CrunchDataset-method
 - (exportDataset), 61
- write.csv.gz, 148