

Package ‘ipumsr’

December 15, 2017

Title Read 'IPUMS' Extract Files

Version 0.1.1

Contact ipums@umn.edu

URL <https://www.ipums.org>, <https://github.com/mnpopcenter/ipumsr>

BugReports <https://github.com/mnpopcenter/ipumsr/issues>

Description An easy way to import census, survey and geographic data provided by 'IPUMS' into R plus tools to help use the associated metadata to make analysis easier. 'IPUMS' data describing 1.4 billion individuals drawn from over 750 censuses and surveys is available free of charge from our website <<https://ipums.org>>.

License Mozilla Public License 2.0

Encoding UTF-8

LazyData true

Imports dplyr (>= 0.7.0), haven, purrr, raster, readr, rlang, stringr, tibble, tidyr, xml2, Rcpp

RoxygenNote 6.0.1

Suggests DT, ggplot2, htmltools, knitr, rgdal, rmarkdown, rstudioapi, scales, sf, sp, shiny, testthat, covr

VignetteBuilder knitr

LinkingTo Rcpp

NeedsCompilation yes

Author Greg Freedman Ellis [aut, cre],
Derek Burk [ctb],
Joe Grover [ctb],
Minnesota Population Center [cph]

Maintainer Greg Freedman Ellis <gfellis@umn.edu>

Repository CRAN

Date/Publication 2017-12-15 18:02:08 UTC

R topics documented:

dplyr_select_style	2
ipums_conditions	3
ipums_example	4
ipums_file_info	4
ipums_list_files	5
ipums_shape_left_join	6
ipums_var_info	7
ipums_view	8
ipums_website	9
join_failures	10
lbl	11
lbl_add	11
lbl_clean	12
lbl_collapse	13
lbl_na_if	14
lbl_relabel	15
read_ipums_codebook	16
read_ipums_ddi	17
read_ipums_micro	18
read_ipums_sf	19
read_nhgis	20
set_ipums_var_attributes	22
zap_ipums_attributes	23
Index	24

dplyr_select_style *Select-style helpers from dplyr*

Description

Several arguments in `ipumsr` allow syntax for selecting variables based on `dplyr`'s `select` function. See details for more information.

Details

There are 3 broad categories of methods for specifying arguments for these select-style parameters.

- "Character Vector" A character vector of names (such as `c("var1", "var2", "var3")`)
- "'Bare' Vector" A vector of 'bare' names (such as `c(var1, var2, var3)`)
- "Helper Functions" Helper functions from `dplyr::select` such as `starts_with()`, `contains` and others.

Examples

```
# For microdata, use this syntax to load variables
# Load 3 variables by name
cps_file <- ipums_example("cps_00006.xml")
data <- read_ipums_micro(cps_file, vars = c("YEAR", "MONTH", "PERNUM"))

# Load same 3 variables using bare names
data <- read_ipums_micro(cps_file, vars = c(YEAR, MONTH, PERNUM))

# Use helper functions to load all variables that start with "WT"
data <- read_ipums_micro(cps_file, vars = starts_with("WT"))

# Use bare names and helper function to load YEAR, MONTH and all variables with 'INC' in name
data <- read_ipums_micro(cps_file, vars = c(YEAR, MONTH, contains("INC")))

# For geographic extracts, `data_layer` and `shape_layer` arguments use the same conventions
# to select file names from within zip files.
# (This extract only contains 1 type of file, but some have multiple)
csv_file <- ipums_example("nhgis0008_csv.zip")
data <- read_nhgis(
  csv_file,
  data_layer = contains("pmsa")
)
```

ipums_conditions

Get IPUMS citation and conditions

Description

Gets information about citation and conditions from a DDI.

Usage

```
ipums_conditions(object = NULL)
```

Arguments

object A DDI object (loaded with [read_ipums_ddi](#)). If NULL (the default), will use the conditions from the dataset you loaded most recently.

ipums_example	<i>Get path to ipums example datasets</i>
---------------	---

Description

Get access to example extracts.

Usage

```
ipums_example(path = NULL)
```

Arguments

path Name of file. If 'NULL', the example files will be listed.

Value

The filepath to an example file, or if path is empty, a vector of all available files.

Examples

```
ipums_example() # Lists all available examples
ipums_example("cps_00006.xml") # Gives filepath for a cps DDI
```

ipums_file_info	<i>Get IPUMS file information</i>
-----------------	-----------------------------------

Description

Get IPUMS metadata information about the data file loaded into R from an ipums_ddi

Usage

```
ipums_file_info(object, type = NULL)
```

Arguments

object An ipums_ddi object (loaded with [read_ipums_ddi](#)).

type NULL to load all types, or one of "ipums_project", "extract_data", "extract_notes", "conditions" or "citation".

Value

If type is NULL, a list with the ipums_project, extract_date, extract_notes, conditions, and citation. Otherwise a string with the type of information requested in type.

Examples

```
ddi <- read_ipums_ddi(ipums_example("cps_00006.xml"))
ipums_file_info(ddi)
```

ipums_list_files	<i>List files available for analysis in an IPUMS extract zip file</i>
------------------	---

Description

Find which files can be loaded from an IPUMS extract zip file.

Usage

```
ipums_list_files(file, types = NULL, data_layer = NULL,
  shape_layer = NULL, raster_layer = NULL)

ipums_list_data(file, data_layer = NULL)

ipums_list_shape(file, shape_layer = NULL)

ipums_list_raster(file, raster_layer = NULL)
```

Arguments

file	An IPUMS extract zip file
types	One or more of "data", "shape", or "raster" indicating what type of files to look for.
data_layer	dplyr select -style notation for the data files to look for
shape_layer	dplyr select -style notation for the shape files to look for
raster_layer	dplyr select -style notation for the raster files to look for

Value

A tibble data.frame containing the files available

Examples

```
nhgis_file <- ipums_example("nhgis0008_csv.zip")
ipums_list_files(nhgis_file) # Only one extract available
```

ipums_shape_left_join *Join data to geographic boundaries*

Description

Helpers for joining shape files downloaded from the IPUMS website to data from extracts. Because of historical reasons, the attributes of (like variable type) of variables in the shape files does not always match those in the data files.

Usage

```
ipums_shape_left_join(data, shape_data, by, suffix = c("", "SHAPE"),
  verbose = TRUE)
```

```
ipums_shape_right_join(data, shape_data, by, suffix = c("", "SHAPE"),
  verbose = TRUE)
```

```
ipums_shape_inner_join(data, shape_data, by, suffix = c("", "SHAPE"),
  verbose = TRUE)
```

```
ipums_shape_full_join(data, shape_data, by, suffix = c("", "SHAPE"),
  verbose = TRUE)
```

Arguments

data	A dataset, usually one that has been aggregated to a geographic level.
shape_data	A shape file (loaded with read_ipums_sf or read_ipums_sp)
by	A vector of variable names to join on. Like the dplyr join functions, named vectors indicate that the names are different between the data and shape file. shape files to load. Accepts a character vector specifying the file name, or dplyr_select_style conventions. Can load multiple shape files, which will be combined.
suffix	For variables that are found in both, but aren't joined on, a suffix to put on the variables. Defaults to nothing for data variables and "_SHAPE" for variables from the shape file.
verbose	If TRUE, will report information about geometries dropped in the merge.

Value

returns a sf or a SpatialPolygonsDataFrame depending on what was passed in.

Examples

```
# Note that these examples use NHGIS data so that they use the example data provided,
# but the functions read_nhgis_sf/read_nhgis_sp perform this merge for you.
```

```

data <- read_nhgis(ipums_example("nhgis0008_csv.zip"))

if (require(sf)) {
  sf <- read_ipums_sf(ipums_example("nhgis0008_shape_small.zip"))
  data_sf <- ipums_shape_inner_join(data, sf, by = "GISJOIN")
}

if (require(sp) && require(rgdal)) {
  sp <- read_ipums_sp(ipums_example("nhgis0008_shape_small.zip"))
  data_sp <- ipums_shape_inner_join(data, sp, by = "GISJOIN")
}

## Not run:
# Sometimes variable names won't match between datasets (for example in IPUMS international)
data <- read_ipums_micro("ipumsi_00004.xml")
shape <- read_ipums_sf("geo2_br1980_2010.zip")
data_sf <- ipums_shape_inner_join(data, shape, by = c("GEO2" = "GEOLEVEL2"))

## End(Not run)

```

ipums_var_info

Get IPUMS variable information

Description

Get IPUMS metadata information about variables loaded into R. Will try to read the metadata from the loaded datasets, but it is more reliable to load the DDI into a separate object and use it instead.

Usage

```

ipums_var_info(object, vars = NULL)

ipums_var_desc(object, var = NULL)

ipums_var_label(object, var = NULL)

ipums_val_labels(object, var = NULL)

```

Arguments

object	A DDI object (loaded with read_ipums_ddi), a data.frame with ipums metadata attached, or a single column from an ipums data.frame.
vars	dplyr select -style notation for the variables to give information about
var	select-style notation for a single variable

`ipums_var_info()` loads all available variable information for one or more variables into a data.frame. If `object` is a vector, it will include the variable label, variable description and value labels. If `object` is a data.frame, it will

include it for all variables (or only those specified by vars). If it is a DDI, it will also include information used to read the data from disk, including start/end position in the fixed-width file, implied decimals and variable type.

`ipums_var_desc()` loads the variable description for a single variable.

`ipums_var_label()` loads the short variable label for a single variable.

`ipums_val_labels()` loads the value labels for a single variable.

Note that many R functions drop attributes that provide this information. In order to make sure that they are available, it is best to keep a copy of the separate from the data you are manipulating using `read_ipums_ddi`. Then you can refer to the IPUMS documentation in this object.

Value

`ipums_var_info` returns a `tbl_df` data frame with variable information, and the other functions return a length 1 character vector.

Examples

```
ddi <- read_ipums_ddi(ipums_example("cps_00006.xml"))
```

```
ipums_var_info(ddi)
ipums_var_desc(ddi, MONTH)
ipums_var_label(ddi, MONTH)
ipums_val_labels(ddi, MONTH)
```

ipums_view

View a static webpage with variable information from a IPUMS extract

Description

Requires that `htmltools`, `shiny` and `DT` are installed.

Usage

```
ipums_view(x, out_file = NULL, launch = TRUE)
```

Arguments

<code>x</code>	A DDI or other object with <code>ipums</code> attributes (such as data loaded from an extract). Note that the file level information (like extract notes) are only available from the DDI.
<code>out_file</code>	Optionally specify a location to save HTML file. <code>NULL</code> the default makes a temporary file.
<code>launch</code>	Logical indicating whether to launch the website.

Value

The filepath to the html (silently if launch is TRUE)

Examples

```
ddi <- read_ipums_ddi(ipums_example("cps_00006.xml"))
## Not run:
ipums_view(ddi)
ipums_view(ddi, "codebook.html", launch = FALSE)

## End(Not run)
```

ipums_website	<i>Launch a browser window to the ipums website</i>
---------------	---

Description

Takes a DDI (or you can specify a project directly) and a variable name, and makes a best guess at the URL for the variable's page on the IPUMS website. Note that NHGIS and TerraPop do not have accessible pages for variables.

Usage

```
ipums_website(x, var, project = NULL, launch = TRUE, verbose = TRUE,
  var_label = NULL, homepage_if_missing = TRUE)
```

Arguments

x	A DDI or empty (if specifying project)
var	A single variable name in a character vector
project	If not using a DDI (or object with a project attribute) A name of an IPUMS project, one of: "IPUMS-USA", "IPUMS-CPS", "IPUMS-International", "IPUMS-DHS", "ATUS-X", "AHTUS-X", "MTUS-X", "NHIS", "Higher Ed", "NHGIS", or "IPUMS Terra"
launch	If TRUE, launch the website.
verbose	If TRUE, message user if no variable specific websites are available
var_label	Sometimes the variable label is useful for finding the correct URL. Only needed if not passing in the ddi object.
homepage_if_missing	If TRUE, Return homepage if project does not provide variable specific web pages.

Details

Because some variables are constructed during the extract creation process, the URL may not always work unfortunately.

Value

The url to the page on ipums.org (silently if launch is TRUE)

Examples

```
ddi <- read_ipums_ddi(ipums_example("cps_00006.xml"))
ipums_website(ddi, "MONTH", launch = FALSE)

## Not run:
# Launches website
ipums_website(ddi, "MONTH")

## End(Not run)

# Can also specify project instead of using DDI
ipums_website(var = "RECTYPE", project = "IPUMS-CPS", launch = FALSE)
```

join_failures

Report on observations dropped by a join

Description

Helper for learning which observations were dropped from a dataset because they were not joined on.

Usage

```
join_failures(join_results)
```

Arguments

join_results A dataset that has just been created by a shape join (like `ipums_shape_left_join`)

Value

returns a list of data.frames, where the first item (shape) is the observations dropped from the shape file and the second (data) is the observations dropped from the data.

lbl	<i>Make a label placeholder object</i>
-----	--

Description

Helper to make a placeholder for a label-value pair.

Usage

```
lbl(...)
```

Arguments

... Either one or two arguments, possibly named `.val` and `.lbl`. If a single unnamed value, represents the label, if 2 unnamed values, the first is the value and the second is the label.

Value

A `label_placeholder` object, useful in functions like [lbl_add](#)

See Also

Other `lbl_helpers`: [lbl_add](#), [lbl_clean](#), [lbl_collapse](#), [lbl_na_if](#), [lbl_relabel](#), [zap_ipums_attributes](#)

Examples

```
x <- haven::labelled(  
  c(100, 200, 105, 990, 999, 230),  
  c(`Unknown` = 990, NIU = 999)  
)  
  
lbl_add(x, lbl(100, "$100"), lbl(105, "$105"), lbl(200, "$200"), lbl(230, "$230"))
```

lbl_add	<i>Add labels for unlabelled values</i>
---------	---

Description

Add labels for values that don't already have them.

Usage

```
lbl_add(x, ...)
```

```
lbl_add_vals(x, labeller = as.character, vals = NULL)
```

Arguments

x	A labelled vector
...	Labels formed by lbl indicating the value and label to be added.
labeller	A function that takes a single argument of the values and returns the labels. Defaults to <code>as.character</code> . as_function , so also accepts quosure-style lambda functions. See examples for more details.
vals	Vector of values to be labelled. NULL, the default labels all values that are in the data, but aren't already labelled.

Value

A `haven::labeled` vector

See Also

Other `lbl_helpers`: [lbl_clean](#), [lbl_collapse](#), [lbl_na_if](#), [lbl_relabel](#), [lbl](#), [zap_ipums_attributes](#)

Examples

```
x <- haven::labelled(
  c(100, 200, 105, 990, 999, 230),
  c(`Unknown` = 990, NIU = 999)
)

lbl_add(x, lbl(100, "$100"), lbl(105, "$105"), lbl(200, "$200"), lbl(230, "$230"))

lbl_add_vals(x)
lbl_add_vals(x, ~paste0("$", .))
lbl_add_vals(x, vals = c(100, 200))
```

`lbl_clean`

Clean unused labels

Description

Remove labels that do not appear in the data.

Usage

```
lbl_clean(x)
```

Arguments

x	A labelled vector
---	-----------------------------------

Value

A haven::labeled vector

See Also

Other lbl_helpers: [lbl_add](#), [lbl_collapse](#), [lbl_na_if](#), [lbl_relabel](#), [lbl](#), [zap_ipums_attributes](#)

Examples

```
x <- haven::labelled(
  c(1, 2, 3, 1, 2, 3, 1, 2, 3),
  c(Q1 = 1, Q2 = 2, Q3 = 3, Q4= 4)
)

lbl_clean(x)
```

lbl_collapse

Collapse labelled values to labels that already exist

Description

Converts values to a new value based on their label and value in a [labelled](#) vector. If the newly assigned value does not match an already existing labelled value, the smallest value's label is used. Ignores any value that does not have a label.

Usage

```
lbl_collapse(x, .fun)
```

Arguments

x	A labelled vector
.fun	A function that takes .val and .lbl (the values and labels) and returns the values of the label you want to change it to. It is passed to a function similar to as_function , so also accepts quosure-style lambda functions (that use values .val and .lbl). See examples for more information.

Value

A haven::labeled vector

See Also

Other lbl_helpers: [lbl_add](#), [lbl_clean](#), [lbl_na_if](#), [lbl_relabel](#), [lbl](#), [zap_ipums_attributes](#)

Examples

```
x <- haven::labelled(
  c(10, 10, 11, 20, 30, 99, 30, 10),
  c(Yes = 10, `Yes - Logically Assigned` = 11, No = 20, Maybe = 30, NIU = 99)
)

lbl_collapse(x, ~(.val %% 10) * 10)
# Notice that 90 get's NIU from 99 even though 90 didn't have a label in original

lbl_collapse(x, ~ifelse(.lbl == 10, 11, .lbl))
# But here 10 is assigned 11's label

# You can also use the more explicit function notation
lbl_collapse(x, function(.val, .lbl) (.val %% 10) * 10)

# Or even the name of a function
collapse_function <- function(.val, .lbl) (.val %% 10) * 10
lbl_collapse(x, "collapse_function")
```

lbl_na_if*Set labelled values to missing*

Description

Convert values to NA based on their label and value in a [labelled](#) vector. Ignores any value that does not have a label.

Usage

```
lbl_na_if(x, .predicate)
```

Arguments

<code>x</code>	A labelled vector
<code>.predicate</code>	A function that takes <code>.val</code> and <code>.lbl</code> (the values and labels) and returns TRUE or FALSE. It is passed to a function similar to as_function , so also accepts quosure-style lambda functions (that use values <code>.val</code> and <code>.lbl</code>). See examples for more information.

Value

A `haven::labeled` vector

See Also

Other `lbl_helpers`: [lbl_add](#), [lbl_clean](#), [lbl_collapse](#), [lbl_relabel](#), [lbl](#), [zap_ipums_attributes](#)

Examples

```
x <- haven::labelled(
  c(10, 10, 11, 20, 30, 99, 30, 10),
  c(Yes = 10, `Yes - Logically Assigned` = 11, No = 20, Maybe = 30, NIU = 99)
)

lbl_na_if(x, ~.val >= 90)
lbl_na_if(x, ~.lbl %in% c("Maybe"))
lbl_na_if(x, ~.val >= 90 | .lbl %in% c("Maybe"))

# You can also use the more explicit function notation
lbl_na_if(x, function(.val, .lbl) .val >= 90)

# Or even the name of a function
na_function <- function(.val, .lbl) .val >= 90
lbl_na_if(x, "na_function")
```

lbl_relabel	<i>Relabel labelled values</i>
-------------	--------------------------------

Description

Converts values to a new value (that may or may not exist) based on their label and value in a [labelled](#) vector. Ignores any value that does not have a label.

Usage

```
lbl_relabel(x, ...)
```

Arguments

x	A labelled vector
...	Two-sided formulas where the left hand side is a label placeholder (created with the lbl function) or a value that already exists in the data and the right hand side is a function that returns a logical vector that indicates which labels should be relabeled. The right hand side is passed to a function similar to as_function , so also accepts quosure-style lambda functions (that use values <code>.val</code> and <code>.lbl</code>). See examples for more information.

Value

A `haven::labeled` vector

See Also

Other `lbl_helpers`: [lbl_add](#), [lbl_clean](#), [lbl_collapse](#), [lbl_na_if](#), [lbl](#), [zap_ipums_attributes](#)

Examples

```
x <- haven::labelled(
  c(10, 10, 11, 20, 30, 99, 30, 10),
  c(Yes = 10, `Yes - Logically Assigned` = 11, No = 20, Maybe = 30, NIU = 99)
)

lbl_relabel(
  x,
  lbl(10, "Yes/Yes-ish") ~ .val %in% c(10, 11),
  lbl(90, "???", .val == 99 | .lbl == "Maybe"
)

# If relabelling to labels that already exist, don't need to specify both label
# and value:
# If just bare, assumes it is a value:
lbl_relabel(x, 10 ~ .val == 11)
# Use single argument to lbl for the label
lbl_relabel(x, lbl("Yes") ~ .val == 11)
# Or can use named arguments
lbl_relabel(x, lbl(.val = 10) ~ .val == 11)
```

read_ipums_codebook *Read metadata from a text codebook in a NHGIS or Terra area-level extract*

Description

Read text formatted codebooks provided by some IPUMS extract systems such as NHGIS and Terra Area-level extracts in a format analogous to the DDI's available for other projects.

Usage

```
read_ipums_codebook(cb_file, data_layer = NULL)
```

Arguments

cb_file	Filepath to the codebook (either the .zip file directly downloaded from the website, or the path to the unzipped .txt file).
data_layer	dplyr select -style notation for uniquely identifying the data layer to load. Required for reading from .zip files for extracts with multiple files.

Value

A ipums_ddi object with information on the variables included in the csv file of a NHGIS extract.

See Also

Other ipums_metadata: [read_ipums_ddi](#)

Examples

```
# Example NHGIS extract
nhgis_file <- ipums_example("nhgis0008_csv.zip")
ddi <- read_ipums_codebook(nhgis_file)
```

read_ipums_ddi	<i>Read metadata about an IPUMS extract from a DDI (.xml) file</i>
----------------	--

Description

Reads the metadata about an IPUMS extract from a DDI file into R. Includes information about variable and value labels, terms of usage for the data and positions for the fixed-width file.

Usage

```
read_ipums_ddi(ddi_file, data_layer = NULL)
```

Arguments

ddi_file	Filepath to DDI xml file
data_layer	If ddi_file is an extract with multiple DDIs, dplyr select -style notation indicating which .xml data layer to load.

Value

An ipums_ddi object with metadata information.

See Also

Other ipums_metadata: [read_ipums_codebook](#)

Examples

```
# Example extract DDI
ddi_file <- ipums_example("cps_00006.xml")
ddi <- read_ipums_ddi(ddi_file)
```

read_ipums_micro	<i>Read data from an IPUMS extract</i>
------------------	--

Description

Reads a dataset downloaded from the IPUMS extract system. For IPUMS projects with microdata, it relies on a downloaded DDI codebook and a fixed-width file. Loads the data with value labels (using [labelled](#) format) and variable labels. See 'Details' for more information on how record types are handled by the ipumsr package.

Usage

```
read_ipums_micro(ddi, vars = NULL, n_max = Inf, data_file = NULL,
  verbose = TRUE, rectype_convert = NULL, var_attrs = c("val_labels",
  "var_label", "var_desc"))
```

```
read_ipums_micro_list(ddi, vars = NULL, n_max = Inf, data_file = NULL,
  verbose = TRUE, rectype_convert = NULL, var_attrs = c("val_labels",
  "var_label", "var_desc"))
```

Arguments

ddi	Either a filepath to a DDI xml file downloaded from the website, or a ipums_ddi object parsed by read_ipums_ddi
vars	Names of variables to load. Accepts a character vector of names, or dplyr_select_style conventions. For hierarchical data, the rectype id variable will be added even if it is not specified.
n_max	The maximum number of records to load.
data_file	Specify a directory to look for the data file. If left empty, it will look in the same directory as the DDI file.
verbose	Logical, indicating whether to print progress information to console.
rectype_convert	(Usually determined by project) A named vector indicating a conversion from the rectype in data to DDI. Not usually needed to be specified by the user.
var_attrs	Variable attributes to add from the DDI, defaults to adding all (val_labels, var_label and var_desc). See set_ipums_var_attributes for more details.

Details

Some IPUMS projects have data for multiple types of records (eg Household and Person). When downloading data from many of these projects you have the option for the IPUMS extract system to "rectangularize" the data, meaning that the data is transformed so that each row of data represents only one type of record.

There also is the option to download "hierarchical" extracts, which are a single file with record types mixed in the rows. The ipumsr package offers two methods for importing this data.

read_ipums_micro loads this data into a "long" format where the record types are mixed in the rows, but the variables are NA for the record types that they do not apply to.

read_ipums_micro_list loads the data into a list of data frames objects, where each data frame contains only one record type. The names of the data frames in the list are the text from the record type labels without 'Record' (often 'HOUSEHOLD' for Household and 'PERSON' for Person).

Value

read_ipums_micro returns a single tbl_df data frame, and read_ipums_micro_list returns a list of data frames, named by the Record Type. See 'Details' for more information.

See Also

Other ipums_read: [read_ipums_sf](#), [read_nhgis](#), [read_terra_area](#), [read_terra_micro](#), [read_terra_raster](#)

Examples

```
# Rectangular example file
cps_rect_ddi_file <- ipums_example("cps_00006.xml")

cps <- read_ipums_micro(cps_rect_ddi_file)
# Or load DDI separately to keep the metadata
ddi <- read_ipums_ddi(cps_rect_ddi_file)
cps <- read_ipums_micro(ddi)

# Hierarchical example file
cps_hier_ddi_file <- ipums_example("cps_00010.xml")

# Read in "long" format and you get 1 data frame
cps_long <- read_ipums_micro(cps_hier_ddi_file)
head(cps_long)

# Read in "list" format and you get a list of multiple data frames
cps_list <- read_ipums_micro_list(cps_hier_ddi_file)
head(cps_list$PERSON)
head(cps_list$HOUSEHOLD)
```

read_ipums_sf

Read boundary files from an IPUMS extract

Description

Reads the boundary files from an IPUMS extract into R as simple features (sf) objects or SpatialPolygonsDataFrame (sp) objects.

Usage

```
read_ipums_sf(shape_file, shape_layer = NULL, bind_multiple = TRUE,
              verbose = TRUE)
```

```
read_ipums_sp(shape_file, shape_layer = NULL, bind_multiple = TRUE,
              verbose = TRUE)
```

Arguments

shape_file	Filepath to one or more .shp files, a .zip file from an IPUMS extract or a path to an unzipped folder.
shape_layer	For .zip extracts with multiple datasets, the name of the shape files to load. Accepts a character vector specifying the file name, or dplyr_select_style conventions. Can load multiple shape files, which will be combined.
bind_multiple	If TRUE, will combine multiple shape files found into a single object.
verbose	If TRUE, will report progress information

Value

read_ipums_sf returns a sf object and read_ipums_sp returns a SpatialPolygonsDataFrame.

See Also

Other ipums_read: [read_ipums_micro](#), [read_nhgis](#), [read_terra_area](#), [read_terra_micro](#), [read_terra_raster](#)

Examples

```
shape_file <- ipums_example("nhgis0008_shape_small.zip")
# If sf package is available, can load as sf object
if (require(sf)) {
  sf_data <- read_ipums_sf(shape_file)
}

# If sp package is available, can load as SpatialPolygonsDataFrame
if (require(sp) && require(rgdal)) {
  sp_data <- read_ipums_sp(shape_file)
}
```

read_nhgis

Read data from an NHGIS extract

Description

Reads a dataset downloaded from the NHGIS extract system. Relies on csv files (with or without the extra header row).

Usage

```
read_nhgis(data_file, data_layer = NULL, verbose = TRUE,
           var_attrs = c("val_labels", "var_label", "var_desc"))

read_nhgis_sf(data_file, shape_file, data_layer = NULL,
              shape_layer = data_layer, verbose = TRUE, var_attrs = c("val_labels",
                              "var_label", "var_desc"))

read_nhgis_sp(data_file, shape_file, data_layer = NULL,
              shape_layer = data_layer, verbose = TRUE, var_attrs = c("val_labels",
                              "var_label", "var_desc"))
```

Arguments

data_file	Filepath to the data (either the .zip file directly downloaded from the website, the path to the unzipped folder, or the path to the unzipped .csv file directly).
data_layer	For .zip extracts with multiple datasets, the name of the data to load. Accepts a character vector specifying the file name, or dplyr_select_style conventions. Data layer must uniquely identify a dataset.
verbose	Logical, indicating whether to print progress information to console.
var_attrs	Variable attributes to add from the codebook, defaults to adding all (val_labels, var_label and var_desc). See set_ipums_var_attributes for more details.
shape_file	Filepath to the shape files (either the .zip file directly downloaded from the website, or the path to the unzipped folder, or the unzipped .shp file directly).
shape_layer	(Defaults to using the same value as data_layer) Specification of which shape files to load using the same semantics as data_layer. Can load multiple shape files, which will be combined.

Value

read_nhgis returns a tbl_df with only the tabular data, read_nhgis_sf returns a sf object with data and the shapes, and read_nhgis_sp returns a SpatialPolygonsDataFrame with data and shapes.

See Also

Other ipums_read: [read_ipums_micro](#), [read_ipums_sf](#), [read_terra_area](#), [read_terra_micro](#), [read_terra_raster](#)

Examples

```
csv_file <- ipums_example("nhgis0008_csv.zip")
shape_file <- ipums_example("nhgis0008_shape_small.zip")

data_only <- read_nhgis(csv_file)

# If sf package is available, can load as sf object
if (require(sf)) {
```

```

sf_data <- read_nhgis_sf(csv_file, shape_file)
}

# If sp package is available, can load as SpatialPolygonsDataFrame
if (require(rgdal) && require(sp)) {
  sp_data <- read_nhgis_sp(csv_file, shape_file)
}

```

```
set_ipums_var_attributes
```

Add IPUMS variable attributes to a data.frame

Description

Add variable attributes from an IPUMS DDI to the variables in a data.frame. This function is usually called automatically for you inside of the read_* functions (such as read_ipums_micro or read_ipums_nhgis), but they can be useful other times as well. For example, if you store the data in a database, you can store the data without attributes in the database and add them on after loading a subset into a data.frame.

Usage

```
set_ipums_var_attributes(data, var_info, var_attrs = c("val_labels",
  "var_label", "var_desc"))
```

Arguments

data	A data.frame
var_info	An ipums_ddi object or a data.frame with the variable information (equivalent to getting ipums_var_info on a DDI).
var_attrs	One or more of val_labels, var_label and var_desc describing what kinds of attributes you want to add. If NULL, will not add any attributes.

Details

Attribute val_labels adds the haven::labelled class attributes and the corresponding value labels for variables that have value labels.

Attribute var_label Adds a short summary of the variable's contents that to the attribute "label". This label is viewable in the Rstudio Viewer.

Attribute var_desc Adds a longer summary of the variable's contents to the attribute "var_desc" when available.

Value

A tbl_df data.frame with data and IPUMS attributes

Examples

```

ddi_file <- ipums_example("cps_00006.xml")
ddi <- read_ipums_ddi(ddi_file)
cps <- read_ipums_micro(ddi, var_attrs = NULL) # Don't load with attributes

ipums_var_desc(cps$YEAR) # Not available

# But, we can add on attributes after loading
cps_with_attr <- set_ipums_var_attributes(cps, ddi)
ipums_var_desc(cps_with_attr$YEAR)

```

zap_ipums_attributes *Remove all IPUMS attributes from a variable (or all variables in a data.frame)*

Description

Helper to remove ipums attributes (including value labels from the labelled class, the variable label and the variable description). These attributes can sometimes get in the way of functions like the dplyr join functions so you may want to remove them.

Usage

```
zap_ipums_attributes(x)
```

Arguments

x A variable or a whole data.frame to remove attributes from

Value

A variable or data.frame

See Also

Other lbl_helpers: [lbl_add](#), [lbl_clean](#), [lbl_collapse](#), [lbl_na_if](#), [lbl_relabel](#), [lbl](#)

Examples

```

cps <- read_ipums_micro(ipums_example("cps_00006.xml"))
annual_unemployment <- data.frame(YEAR = c(1962, 1963), unemp = c(5.5, 5.7))

# Avoids warning 'Column `YEAR` has different attributes on LHS and RHS of join'
cps$YEAR <- zap_ipums_attributes(cps$YEAR)
cps <- dplyr::left_join(cps, annual_unemployment, by = "YEAR")

```

Index

`as_function`, [12–15](#)

`dplyr_select_style`, [2, 6, 18, 20, 21](#)

`ipums_conditions`, [3](#)

`ipums_example`, [4](#)

`ipums_file_info`, [4](#)

`ipums_list_data` (`ipums_list_files`), [5](#)

`ipums_list_files`, [5](#)

`ipums_list_raster` (`ipums_list_files`), [5](#)

`ipums_list_shape` (`ipums_list_files`), [5](#)

`ipums_shape_full_join`
 (`ipums_shape_left_join`), [6](#)

`ipums_shape_inner_join`
 (`ipums_shape_left_join`), [6](#)

`ipums_shape_left_join`, [6, 10](#)

`ipums_shape_right_join`
 (`ipums_shape_left_join`), [6](#)

`ipums_val_labels` (`ipums_var_info`), [7](#)

`ipums_var_desc` (`ipums_var_info`), [7](#)

`ipums_var_info`, [7](#)

`ipums_var_label` (`ipums_var_info`), [7](#)

`ipums_view`, [8](#)

`ipums_website`, [9](#)

`join_failures`, [10](#)

`labelled`, [12–15, 18](#)

`lbl`, [11, 12–15, 23](#)

`lbl_add`, [11, 11, 13–15, 23](#)

`lbl_add_vals` (`lbl_add`), [11](#)

`lbl_clean`, [11, 12, 12, 13–15, 23](#)

`lbl_collapse`, [11–13, 13, 14, 15, 23](#)

`lbl_na_if`, [11–13, 14, 15, 23](#)

`lbl_relabel`, [11–14, 15, 23](#)

`read_ipums_codebook`, [16, 17](#)

`read_ipums_ddi`, [3, 4, 7, 8, 16, 17, 18](#)

`read_ipums_micro`, [18, 20, 21](#)

`read_ipums_micro_list`
 (`read_ipums_micro`), [18](#)

`read_ipums_sf`, [6, 19, 19, 21](#)

`read_ipums_sp` (`read_ipums_sf`), [19](#)

`read_nhgis`, [19, 20, 20](#)

`read_nhgis_sf` (`read_nhgis`), [20](#)

`read_nhgis_sp` (`read_nhgis`), [20](#)

`read_terra_area`, [19–21](#)

`read_terra_micro`, [19–21](#)

`read_terra_raster`, [19–21](#)

`select`, [2, 5, 7, 16, 17](#)

`set_ipums_var_attributes`, [18, 21, 22](#)

`zap_ipums_attributes`, [11–15, 23](#)