

Package ‘mbbfd’

July 18, 2017

Type Package

Title Maxwell Boltzmann Bose Einstein Fermi Dirac Distribution and
Destruction Rate Modelling

Version 0.8.8.1

Description Distributions that are typically used for exposure rating in
general insurance, in particular to price reinsurance contracts.
The vignettes show code snippets to fit the distribution to
empirical data.

License GPL-2

Depends R (>= 3.4), fitdistrplus (>= 1.0-7), alabama

ByteCompile yes

Suggests testthat, copula, pander, knitcitations, rmarkdown, knitr,
lattice

LinkingTo Rcpp

Imports Rcpp, utils, actuar, gsl, MASS

URL <http://github.com/spedygiorgio/mbbfd>

BugReports <http://github.com/spedygiorgio/mbbfd/issues>

VignetteBuilder knitr

NeedsCompilation yes

Author Giorgio Spedicato [aut, cre],
Christophe Dutang [aut],
Markus Gesmann [ctb]

Maintainer Giorgio Spedicato <spedicato_giorgio@yahoo.it>

Repository CRAN

Date/Publication 2017-07-18 20:29:15 UTC

R topics documented:

mbbefd-package	2
asiacomrisk	3
beaonre	5
bootDR	6
ecf	8
etl	9
exposureCurve	10
fitDR	11
g2a	14
gbeta	14
graph-eccomp	16
itagradescore	17
lossalae	18
mbbefd-distr	19
oibeta	21
oidistribution	22
oigbeta	23
oistpareto	24
oiunif	25
stpareto	27
swissRe	28
Index	30

mbbefd-package	<i>MBBEFD distribution, destruction rate and exposure curve modelling</i>
----------------	---

Description

The idea of this package emerged in 2013 from G Spedicato who at this time worked in the area of quantitative risk assessment. In 2015, M Gesmann and C Dutang joined the project. This project is hosted in [github](#).

This package contains the definition of the MBBEFD distributions (distribution function, density, quantile functions, random generation, aka d , p , q , r) as well as MBBEFD exposure curve (ec) and raw moments (m).

This package also focuses on other distributions used for destruction rate modelling, that is the beta, the shifted truncated Pareto and the generalized beta distributions. Due to the presence of total loss, a one-inflated version of the previous distributions is also provided.

The vignette shows code snippets to fit the distribution to empirical data: [Exposure rating, destruction rate models and the mbbefd package](#).

Details

Package: mbbefd
Type: Package
Version: 0.8-8
Date: 2017-02-22
License: GPL 2

Author(s)

Giorgio Alfredo Spedicato [cre, aut], Christophe Dutang [aut] and Markus Gesmann [ctb]
Maintainer: Giorgio Spedicato <spedicato_giorgio@yahoo.it>

References

BERNEGGER, STEFAN. THE SWISS RE EXPOSURE CURVES AND THE MBBEFD DISTRIBUTION CLASS. *Astin Bulletin* (1997): 99.

See Also

See [mbbefd-distr](#) for the MBBEFD distribution;
see [swissRe](#), [exposureCurve](#) for exposure curves;
see [gbeta](#), [stpareto](#) for finite-support distributions;
see [oidistribution](#), [oibeta](#), [oigbeta](#), [oiunif](#), [oistpareto](#) for one-inflated distributions.

asiacomrisk

Large commercial risks in Asia-Pacific

Description

A completed project by the Insurance Risk and Finance Research Centre (www.IRFRC.com) has assembled a unique dataset from Large Commercial Risk losses in Asia-Pacific (APAC) covering the period 2000-2013. The data was generously contributed by one global reinsurance company and two large Lloyd's syndicates in London. This dataset is the result of the project co-lead by Dr Milidonis (IRFRC and University of Cyprus) and Enrico Biffis (Imperial College Business School), which can be referred to as the IRFRC LCR Dataset.

As expected, the dataset is fully anonymised, as the LCR losses are aggregated along a few dimensions. First, data is categorised based on the World Bank's economic development classification. This means that losses either come from developed or developing countries. The second dimension used to aggregate the data is the time period covered. Data is grouped into (at least) two time-periods: the period before and after the 2008 crisis.

A large commercial risk (LCR) is defined as a loss caused by man-made risks (e.g. fire, explosion, etc.). We exclude natural catastrophe events, and started by focusing on claims that made the

data provider incur a loss amount of at least EUR 1 million. We then extended our dataset to include claims leading to loss amounts smaller than EUR 1 million. Given time constraints, we only partially extended loss data by obtaining FGU losses larger than EUR 140k. One should note that any selection bias arising from the data collection exercise is driven by both data quality and reliability. Based on our experience, the latter two attributes are homogeneous across developed and developing countries APAC claims.

For further details, see the technical report: Benedetti, Biffis and Milidonis (2015a).

Usage

```
data(asiacomrisk)
```

Format

asiacomrisk contains 7 columns:

Period A character string for the period: "2000-2003", "2004-2008", "2009-2010", "2011-2013".

FGU From the Ground Up Loss (USD).

TIV Total Insurable Value (TIV) replaced with Total Sum Insured (TSI) when the TIV is not available (USD).

CountryStatus A character string for the country status: "Developped", "Emerging".

Usage A character string for the type of exposure hit by the loss: "Commercial", "Energy", "Manufacturing", "Misc.", "Residential".

SubUsage A character string for a precised type of exposure hit by the loss: "Commercial", "Energy", "General industry", "Metals/Mines/Chemicals", "Misc.", "Residential", "Utility".

DR A numeric for the destruction rate (FGU divided TIV capped to 1).

Source

<http://irfrc.ntu.edu.sg/Research/completedprojects/Pages/Large-Commercial-Risks.aspx>

References

Benedetti, D., Biffis, E., and Milidonis, A. (2015a). *Large Commercial Risks (LCR) in Insurance: Focus on Asia-Pacific*, Insurance Risk and Finance Research Centre Technical report.

Benedetti, D., Biffis, E., and Milidonis, A. (2015b). *Large Commercial Exposures and Tail Risk: Evidence from the Asia-Pacific Property and Casualty Insurance Market*, Working paper.

Chavez-Demoulin, V., Embrechts, P., and Hofert, M. (2015). *An extreme value approach for modeling operational risk losses depending on covariates*, The Journal of Risk and Insurance.

Examples

```
# (1) load of data
#
data(asiacomrisk)
dim(asiacomrisk)

# (2) basic boxplots
#

asiacomrisk
boxplot(DR ~ Usage, data=asiacomrisk)
boxplot(DR ~ SubUsage, data=asiacomrisk)
boxplot(DR ~ Period, data=asiacomrisk)
boxplot(DR ~ CountryStatus, data=asiacomrisk)
```

beaonre

AON Re Belgian dataset

Description

The dataset was collected by the reinsurance broker AON Re Belgium and comprise 1,823 fire losses for which the building type and the sum insured are available.

Usage

```
data(beaonre)
```

Format

beaonre contains three columns and 1823 rows:

BuildType The building type either A, B, C, D, E or F.

ClaimCost The loss amount in thousand of Danish Krone (DKK).

SumInsured The sum insured in thousand of Danish Krone (DKK).

Source

<http://lstat.kuleuven.be/Wiley/>

References

Dataset used in Beirlant, Dierckx, Goegebeur and Matthys (1999), *Tail index estimation and an exponential regression model*, *Extremes* 2, 177-200.

Examples

```
# (1) load of data
#
data(beaonre)

# (2) plot and description of data
#

boxplot(ClaimCost ~ BuildType, data=beaonre, log="y",
        xlab="Building type", ylab="Claim size", main="AON Re Belgium data")
```

 bootDR

Bootstrap simulation of destruction rate models

Description

Uses parametric or nonparametric bootstrap resampling in order to simulate uncertainty in the parameters of the distribution fitted to destruction rate data. Generic methods are `print`, `plot`, `summary`.

Usage

```
bootDR(f, bootmethod="param", niter=1001, silent=TRUE)
```

Arguments

<code>f</code>	An object of class "fitDR", output of the <code>fitDR</code> function.
<code>bootmethod</code>	A character string coding for the type of resampling : "param" for a parametric resampling and "nonparam" for a nonparametric resampling of data.
<code>niter</code>	The number of samples drawn by bootstrap.
<code>silent</code>	A logical to remove or show warnings and errors when bootstrapping.

Details

Samples are drawn by parametric bootstrap (resampling from the distribution fitted by `fitDR`) or nonparametric bootstrap (resampling with replacement from the data set). On each bootstrap sample the estimation process is used to estimate bootstrapped values of parameters. When that function fails to converge, NA values are returned. Medians and 2.5 and 97.5 percentiles are computed by removing NA values.

This method returns an object of class "bootDR" inheriting from the "bootdist" class. Therefore the following generic methods are defined: `print`, `plot`, `summary`.

Value

bootDR returns an object of class "bootDR" inheriting from the "bootdist" class. That is a list with 6 components,

estim	a data frame containing the bootstrapped values of parameters.
converg	a vector containing the codes for convergence obtained if an iterative method is used to estimate parameters on each bootstrapped data set (and 0 if a closed formula is used).
method	A character string coding for the type of resampling : "param" for a parametric resampling and "nonparam" for a nonparametric resampling.
nbboot	The number of samples drawn by bootstrap.
CI	bootstrap medians and 95 percent confidence percentile intervals of parameters.
fitpart	The object of class "fitDR" on which the bootstrap procedure was applied.

Generic functions:

`print` The print of a "bootDR" object shows the bootstrap parameter estimates. If inferior to the whole number of bootstrap iterations, the number of iterations for which the estimation converges is also printed.

`summary` The summary provides the median and 2.5 and 97.5 percentiles of each parameter. If inferior to the whole number of bootstrap iterations, the number of iterations for which the estimation converges is also printed in the summary.

`plot` The plot shows the bootstrap estimates with `stripchart` function for univariate parameters and `plot` function for multivariate parameters.

Author(s)

Christophe Dutang

References

Cullen AC and Frey HC (1999), *Probabilistic techniques in exposure assessment*. Plenum Press, USA, pp. 181-241.

Delignette-Muller ML and Dutang C (2015), *fitdistrplus: An R Package for Fitting Distributions*. Journal of Statistical Software, 64(4), 1-34.

See Also

See `mledist`, `mmedist`, `qmedist`, `mgedist` for details on parameter estimation. See `bootdist` for details on generic function. See `fitDR` for estimation procedures.

Examples

```
# We choose a low number of bootstrap replicates in order to satisfy CRAN running times
# constraint.
# For practical applications, we recommend to use at least niter=501 or niter=1001.
```

eecf

Empirical Exposure Curve Function

Description

Compute an empirical exposure curve function.

Usage

eecf(x)

Arguments

x numeric vector of the observations for eecf; for the methods, an object of class "eecf".

Details

TODO!

Value

A numeric value or a vector.

Author(s)

Dutang Christophe

References

TODO

See Also

[exposureCurve](#).

Examples

#TODO

etl	<i>Empirical total loss</i>
-----	-----------------------------

Description

Compute the empirical total loss.

Usage

```
etl(x, na.rm=FALSE)
```

Arguments

x	numeric vector of the observations.
na.rm	a logical value indicating whether NA values should be stripped before the computation proceeds.

Details

Compute the empirical total loss defined as the proportion of full destruction rates, that is observations that equal 1.

Value

A numeric value or a vector.

Author(s)

Dutang Christophe

References

TODO

Examples

```
#TODO
```

exposureCurve

Exposure curves for the beta and the uniform distributions.

Description

An exposure curve is defined between x between 0 and 1 and represents the ratio of the limited expected value to unlimited expected value.

Usage

```
ecbeta(x, shape1, shape2)
ecunif(x, min = 0, max =1)
```

Arguments

<code>x</code>	<code>x</code> value, percentage of damage to total loss
<code>shape1</code> , <code>shape2</code>	parameters for the beta distribution.
<code>min</code> , <code>max</code>	parameters for the uniform distribution.

Details

`ecbeta`, `ecunif` is the theoretical exposure curve function for beta and uniform distribution.

Value

A numeric value

Author(s)

Giorgio Spedicato Christophe Dutang

References

BERNEGGER, STEFAN. THE SWISS RE EXPOSURE CURVES AND THE MBBEFD DISTRIBUTION CLASS. *Astin Bulletin* (1997): 99.

See Also

`ecmbbefd` and `ecMBBEFD` are implemented in [mbbefd-distr](#). See also [Uniform](#), [Beta](#), [swissRe](#).

Examples

```
x <- 0.2
ecbeta(x, 2, 3)
ecunif(x)
```

fitDR

*Fit of destruction rate models***Description**

Fit of univariate distributions to destruction rate data by maximum likelihood (mle), moment matching (mme), quantile matching (qme) or maximizing goodness-of-fit estimation (mge). The latter is also known as minimizing distance estimation. Generic methods are print, plot, summary, quantile, logLik, vcov and coef.

Usage

```
fitDR(x, dist, method="mle", start=NULL, optim.method="default", ...)
```

Arguments

x	A numeric vector.
dist	A character string "name" naming a distribution among "oiunif", "oistpareto", "oibeta", "oigbeta", "mbbefd", "MBBEFD".
method	A character string coding for the fitting method: "mle" for 'maximum likelihood estimation', "tlmme" for 'total-loss-moment matching estimation'.
start	A named list giving the initial values of parameters of the named distribution or a function of data computing initial values and returning a named list. This argument may be omitted (default) for some distributions for which reasonable starting values are computed (see the 'details' section of mledist).
optim.method	"default" or an optimization method to pass to optim .
...	Further arguments to be passed to "fitdist" when method != "tlmme". See fitdist for details on parameter estimation.

Details

The fitted distribution (dist) has its d, p, q, r functions defined in the man page: [oiunif](#), [oistpareto](#), [oibeta](#), [oigbeta](#), [mbbefd](#), [MBBEFD](#).

The two possible fitting methods are described below:

When method="mle" Maximum likelihood estimation consists in maximizing the log-likelihood. A numerical optimization is carried out in [mledist](#) via [optim](#) to find the best values (see [mledist](#) for details). For one-inflated distributions, the probability parameter is estimated by a closed-form formula and other parameters use a two-optimization procedures.

When method="tlmme" Total loss and moment matching estimation consists in equalizing theoretical and empirical total loss as well as theoretical and empirical moments. The theoretical and the empirical moments are matched numerically, by minimization of the sum of squared differences between observed and theoretical quantities (see [mmedist](#) for details).

For one-inflated distributions, by default, direct optimization of the log-likelihood (or other criteria depending of the chosen method) is performed using `optim`, with the "L-BFGS-B" method for distributions characterized by more than one parameter and the "Brent" method for distributions characterized by only one parameter. Note that when errors are raised by `optim`, it's a good idea to start by adding traces during the optimization process by adding `control=list(trace=1, REPORT=1)`. For the MBBEFD distribution, `constrOptim.nl` is used.

A pre-fitting process is carried out for the following distributions "mbbefd", "MBBEFD" and "oigbeta" before the main optimization.

The estimation process is carried out via `fitdist` from the `fitdistrplus` package and the output object will inherit from the "fitdist" class. Therefore, the following generic methods are available `print`, `plot`, `summary`, `quantile`, `logLik`, `vcov` and `coef`.

Value

`fitDR` returns an object of class "fitDR" inheriting from the "fitdist" class. That is a list with the following components:

<code>estimate</code>	the parameter estimates.
<code>method</code>	the character string coding for the fitting method : "mle" for 'maximum likelihood estimation', "tlmme" for 'matching total loss moment estimation'.
<code>sd</code>	the estimated standard errors, NA if numerically not computable or NULL if not available.
<code>cor</code>	the estimated correlation matrix, NA if numerically not computable or NULL if not available.
<code>vcov</code>	the estimated variance-covariance matrix, NULL if not available.
<code>loglik</code>	the log-likelihood.
<code>aic</code>	the Akaike information criterion.
<code>bic</code>	the the so-called BIC or SBC (Schwarz Bayesian criterion).
<code>n</code>	the length of the data set.
<code>data</code>	the data set.
<code>distname</code>	the name of the distribution.
<code>fix.arg</code>	the named list giving the values of parameters of the named distribution that must be kept fixed rather than estimated by maximum likelihood or NULL if there are no such parameters.
<code>fix.arg.fun</code>	the function used to set the value of <code>fix.arg</code> or NULL.
<code>discrete</code>	the input argument or the automatic definition by the function to be passed to functions <code>gofstat</code> , <code>plotdist</code> and <code>cdfcomp</code> .
<code>dots</code>	the list of further arguments passed in <code>...</code> to be used in <code>bootdist</code> in iterative calls to <code>mledist</code> , <code>mmedist</code> , <code>qmedist</code> , <code>mgedist</code> or NULL if no such arguments.
<code>weights</code>	the vector of weights used in the estimation process or NULL.

Generic functions:

`print` The print of a "fitDR" object shows few traces about the fitting method and the fitted distribution.

- summary** The summary provides the parameter estimates of the fitted distribution, the log-likelihood, AIC and BIC statistics and when the maximum likelihood is used, the standard errors of the parameter estimates and the correlation matrix between parameter estimates.
- plot** The plot of an object of class "fitDR" returned by `fitdist` uses the function `plotdist`. An object of class "fitdist" or a list of objects of class "fitDR" corresponding to various fits using the same data set may also be plotted using a cdf plot (function `cdfcomp`), a density plot (function `denscomp`), a density Q-Q plot (function `qqcomp`), or a P-P plot (function `ppcomp`).
- logLik** Extracts the estimated log-likelihood from the "fitDR" object.
- vcov** Extracts the estimated var-covariance matrix from the "fitDR" object (only available when `method = "mle"`).
- coef** Extracts the fitted coefficients from the "fitDR" object.

Author(s)

Christophe Dutang.

References

- Cullen AC and Frey HC (1999), *Probabilistic techniques in exposure assessment*. Plenum Press, USA, pp. 81-155.
- Venables WN and Ripley BD (2002), *Modern applied statistics with S*. Springer, New York, pp. 435-446.
- Vose D (2000), *Risk analysis, a quantitative guide*. John Wiley & Sons Ltd, Chichester, England, pp. 99-143.
- Delignette-Muller ML and Dutang C (2015), *fitdistrplus: An R Package for Fitting Distributions*. Journal of Statistical Software, 64(4), 1-34.

See Also

See `mledist`, `mmedist`, for details on parameter estimation. See `gofstat` for goodness-of-fit statistics. See `plotdist`, `graphcomp` for graphs. See `bootDR` for bootstrap procedures. See `optim` for base R optimization procedures. See `quantile.fitdist`, another generic function, which calculates quantiles from the fitted distribution. See `quantile` for base R quantile computation.

Examples

```
# (1) fit of a one-inflated beta distribution by maximum likelihood estimation
#
n <- 1e3
set.seed(12345)
x <- roibeta(n, 3, 2, 1/6)

f1 <- fitDR(x, "oibeta", method="mle")
summary(f1)

plot(bootdist(f1, niter=11), enhance=TRUE, trueval=c(3, 2, 1/6))
```

g2a *Get a parameter known g and b*

Description

g2a returns the a parameter known g and b

Usage

```
g2a(g, b)
```

Arguments

g	the g parameter
b	the b parameter

Value

a real value

See Also

[mbbefd-distr.](#)

Examples

```
g2a(10,2)
```

gbeta *The generalized Beta of the first kind Distribution*

Description

Density, distribution function, quantile function and random generation for the GB1 distribution with parameters shape0, shape1 and shape2.

Usage

```

dgbeta(x, shape0, shape1, shape2, log = FALSE)
pgbeta(q, shape0, shape1, shape2, lower.tail = TRUE, log.p = FALSE)
qgbeta(p, shape0, shape1, shape2, lower.tail = TRUE, log.p = FALSE)
rgbeta(n, shape0, shape1, shape2)
ecgbeta(x, shape0, shape1, shape2)
mgbeta(order, shape0, shape1, shape2)

```

Arguments

<code>x, q</code>	vector of quantiles.
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required.
<code>shape0, shape1, shape2</code>	positive parameters of the GB1 distribution.
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as <code>log(p)</code> .
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.
<code>order</code>	order of the raw moment.

Details

The GB1 distribution with parameters $\text{shape0} = g$, $\text{shape1} = a$ and $\text{shape2} = b$ has density

$$f(x) = \frac{\Gamma(a+b)}{\Gamma(a)\Gamma(b)} x^{a/g-1} (1-x^{1/g})^{b-1} / g$$

for $a, b, g > 0$ and $0 \leq x \leq 1$ where the boundary values at $x = 0$ or $x = 1$ are defined as by continuity (as limits).

Value

`dgbeta` gives the density, `pgbeta` the distribution function, `qgbeta` the quantile function, and `rgbeta` generates random deviates.

References

Becker, R. A., Chambers, J. M. and Wilks, A. R. (1988) *The New S Language*. Wadsworth & Brooks/Cole.

Abramowitz, M. and Stegun, I. A. (1972) *Handbook of Mathematical Functions*. New York: Dover. Chapter 6: Gamma and Related Functions.

Johnson, N. L., Kotz, S. and Balakrishnan, N. (1995) *Continuous Univariate Distributions*, volume 2, especially chapter 25. Wiley, New York.

See Also

[Distributions](#) for other standard distributions.

Examples

```
#TODO
```

Description

eccomp plots the empirical exposure curve distribution against fitted exposure curve functions.

Usage

```
eccomp(ft, xlim, ylim, main, xlab, ylab, do.points=TRUE,
       datapch, datacol, fitlty, fitcol, addlegend = TRUE,
       legendtext, xlegend = "bottomright",
       ylegend = NULL, ...)
```

Arguments

ft	One "DR" object or a list of objects of class "DR".
xlim	The x -limits of the plot.
ylim	The y -limits of the plot.
main	A main title for the plot, see also title .
xlab	A label for the x -axis, defaults to a description of x .
ylab	A label for the y -axis, defaults to a description of y .
datapch	An integer specifying a symbol to be used in plotting data points, see also points .
datacol	A specification of the color to be used in plotting data points.
fitcol	A (vector of) color(s) to plot fitted distributions. If there are fewer colors than fits they are recycled in the standard fashion.
fitlty	A (vector of) line type(s) to plot fitted distributions/densities. If there are fewer colors than fits they are recycled in the standard fashion. See also par .
addlegend	If TRUE, a legend is added to the plot.
legendtext	A character or expression vector of length ≥ 1 to appear in the legend, see also legend .
xlegend, ylegend	The x and y co-ordinates to be used to position the legend. They can be specified by keyword or in any way which is accepted by 'xy.coords': see legend for details.
do.points	logical; if TRUE, also draw points at the x -locations. Default is true. For large dataset ($n > 1e4$), do.points is ignored and no point is drawn.
...	Further graphical arguments passed to graphical functions used in cdfcomp , denscomp , ppcomp and qqcomp .

Details

eccomp provides a exposure curve plot of each fitted distribution along with the eecf.

By default a legend is added to these plots. Many graphical arguments are optional, dedicated to personalize the plots, and fixed to default values if omitted.

Author(s)

Christophe Dutang.

See Also

See [plot](#), [legend](#), [eecf](#).

Examples

```
# (1)
```

itagradescore

Italian grade scores

Description

This dataset contains scores of an university admission test. The total score is subdivided into four areas (Italian, English, abstract reasoning, science). Each subitem can have a point of pass at the end.

Usage

```
data(itagradescore)
```

Format

itagradescore contains 10 columns:

Number a numeric for the record number.

ID a factor for the identification code.

Correct A score of correct answers.

Wrong A score of wrong answers.

Null A score of null answers.

ItalianLanguage A score for the Italian language test.

EnglishLanguage A score for the English language test.

LogicalReasoning A score for the logic test.

Science A score for the science test.

TotalScore The sum of the four scores (i.e. four previous columns).

Source

Internal

Examples

```
# (1) load of data
#
data(itagradescore)
dim(itagradescore)
```

lossalae

General Liability Claims

Description

The lossalae is a data frame of 1500 rows and 4 columns containing 1,500 general liability claims randomly chosen from late settlement lags and were provided by Insurance Services Office, Inc. Each claim consists of an indemnity payment (the loss, X1) and an allocated loss adjustment expense (ALAE). ALAE are types of insurance company expenses that are specifically attributable to the settlement of individual claims such as lawyers' fees and claims investigation expenses. The third column is the underwriting limit of the policy and the fourth column indicates a censored observation.

Usage

```
data(lossalae_full)
```

Format

lossalae_full contains four columns:

Loss A numeric vector containing the indemnity payments (USD).

ALAE A numeric vector containing the allocated loss adjustment expenses (USD).

Limit A numeric vector containing the policy limit (USD).

Censored A binary indicating that the payments are capped to their policy limit (USD).

Source

Frees, E. W. and Valdez, E. A. (1998) Understanding relationships using copulas. *North American Actuarial Journal*, **2**, 1–15.

<http://lstat.kuleuven.be/Wiley/>

References

- Klugman, S. A. and Parsa, R. (1999) Fitting bivariate loss distributions with copulas. *Insurance: Mathematics and Economics*, **24**, 139–148.
- Beirlant, J., Goegebeur, Y., Segers, J. and Teugels, J. L. (2004) *Statistics of Extremes: Theory and Applications.*, Chichester, England: John Wiley and Sons.
- Cebrian, A.C., Denuit, M. and Lambert, P. (2003). *Analysis of bivariate tail dependence using extreme value copulas: An application to the SOA medical large claims database*, Belgian Actuarial Bulletin, Vol. 3, No. 1.

Examples

```
# (1) load of data
#
data(lossalaefull)
```

mbbefd-distr	<i>The MBBEFD distribution (two parametrizations)</i>
--------------	---

Description

These functions perform probabilistic analysis as well as random sampling on the MBBEFD distribution: the 1st parametrization MBBEFD(a,b) is implemented in <d,p,q,r>mbbefd, the 2nd parametrization MBBEFD(g,b) is implemented in <d,p,q,r>MBBEFD. We also provide raw moments, exposure curve function and total loss.

Usage

```
dmbbefd(x, a, b, log=FALSE, g)
pmbbefd(q, a, b, lower.tail = TRUE, log.p = FALSE, g)
qmbbefd(p, a, b, lower.tail = TRUE, log.p = FALSE, g)
rmbbefd(n, a, b)
ecmbbefd(x, a, b)
mmbbefd(order, a, b)
tlmbbefd(a, b)

dMBBEFD(x, g, b, log=FALSE)
pMBBEFD(q, g, b, lower.tail = TRUE, log.p = FALSE)
qMBBEFD(p, g, b, lower.tail = TRUE, log.p = FALSE)
rMBBEFD(n, g, b)
ecMBBEFD(x, g, b)
mMBBEFD(order, g, b)
tlMBBEFD(g, b)
```

Arguments

x, q	vector of quantiles.
p	vector of probabilities.
n	number of observations. If <code>length(n) > 1</code> , the length is take to be the number required.
a, b, g	shape parameters. For <code>.mbbefd</code> functions, g is computed from a.
order	order of the raw moment.
log, log.p	logical; if TRUE, probabilities p are given as $\log(p)$.
lower.tail	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.

Details

it shall be remebered that $g = \frac{1}{p_1} = \frac{a+b}{(a+1)*b}$.

Value

A numeric value or a vector.

Author(s)

Giorgio Spedicato, Dutang Christophe

References

BERNEGGER, STEFAN. THE SWISS RE EXPOSURE CURVES AND THE MBBEFD DISTRIBUTION CLASS. *Astin Bulletin* (1997): 99.

See Also

[swissRe](#), [exposureCurve](#).

Examples

```
#1st parametrization
#
aPar=0.2
bPar=0.04
rmbbefd(n=10,a=aPar,b=bPar) #for random generation
qmbbefd(p=0.7,a=aPar,b=bPar) #for quantiles
dmbbefd(x=0.5,a=aPar,b=bPar) #for density
pmbbefd(q=0.5,a=aPar,b=bPar) #for distribution function

#2nd parametrization
#
gPar=2
bPar=0.04
rMBBEFD(n=10,g=gPar,b=bPar) #for random generation
qMBBEFD(p=0.7,g=gPar,b=bPar) #for quantiles
dMBBEFD(x=0.5,g=gPar,b=bPar) #for density
```

```
pMBBEFD(q=0.5,g=gPar,b=bPar) #for distribution function
```

oibeta *One-inflated beta distribution*

Description

These functions perform probabilistic analysis as well as random sampling on one-inflated beta distribution.

Usage

```
doibeta(x, shape1, shape2, p1, ncp=0, log=FALSE)
poibeta(q, shape1, shape2, p1, ncp=0, lower.tail = TRUE, log.p = FALSE)
qoibeta(p, shape1, shape2, p1, ncp=0, lower.tail = TRUE, log.p = FALSE)
roibeta(n, shape1, shape2, p1, ncp=0)
ecoibeta(x, shape1, shape2, p1, ncp=0)
moibeta(order, shape1, shape2, p1, ncp=0)
tloibeta(shape1, shape2, p1, ncp=0)
```

Arguments

x, q	vector of quantiles.
p	vector of probabilities.
n	number of observations. If $\text{length}(n) > 1$, the length is take to be the number required.
p1, shape1, shape2, ncp	parameters.
order	order of the raw moment.
log, log.p	logical; if TRUE, probabilities p are given as $\log(p)$.
lower.tail	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.

Details

d,p,q,ec,m,tl-oibeta functions computes the density function, the distribution function, the quantile function, the exposure curve function, raw moments and total loss of the one-inflated beta distribution. roibeta generates random variates of this distribution.

Value

A numeric value or a vector.

Author(s)

Dutang Christophe

See Also[mbbefd-distr](#) and [oidistribution](#).**Examples**

#TODO

oidistribution *One-inflated distributions*

Description

These functions perform probabilistic analysis as well as random sampling on one-inflated distributions.

Usage

```
doifun(x, dfun, p1, log=FALSE, ...)
poifun(q, pfun, p1, lower.tail = TRUE, log.p = FALSE, ...)
qoifun(p, qfun, p1, lower.tail = TRUE, log.p = FALSE, ...)
roifun(n, rfun, p1, ...)
ecoifun(x, ecfun, mfun, p1, ...)
moifun(order, mfun, p1, ...)
tloifun(p1, ...)
```

Arguments

<code>x, q</code>	vector of quantiles.
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is take to be the number required.
<code>dfun, pfun, qfun, rfun</code>	<code>d, p, q, r</code> functions of the original distribution.
<code>p1</code>	parameter for the probability at $x=1$.
<code>ecfun, mfun</code>	exposure curve and moment functions which should have arguments <code>x, ...</code> and <code>order, ...</code> respectively.
<code>order</code>	order of the raw moment.
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.
<code>...</code>	further arguments to pass to <code>dfun, pfun, qfun, rfun, ecfun, mfun</code> .

Details

`d`, `p`, `q`, `ec`, `m`, `t1` functions of `oi`fun computes the density function, the distribution function, the quantile function, the exposure curve function, raw moments and total loss of an one-inflated distribution of an original distribution specified by `d`, `p`, `q`, `ec`, `m`-fun. `roi`fun generates random variates of the resulting distribution.

Value

A numeric value or a vector.

Author(s)

Dutang Christophe

See Also

[oibeta](#), [oiunif](#), [oistpareto](#) and [oidistribution](#).

oigbeta

One-inflated generalized beta of the first kind (GB1) distribution

Description

These functions perform probabilistic analysis as well as random sampling on one-inflated GB1 distribution.

Usage

```
doigbeta(x, shape0, shape1, shape2, p1, log=FALSE)
poigbeta(q, shape0, shape1, shape2, p1, lower.tail = TRUE, log.p = FALSE)
qoigbeta(p, shape0, shape1, shape2, p1, lower.tail = TRUE, log.p = FALSE)
roigbeta(n, shape0, shape1, shape2, p1)
ecoigbeta(x, shape0, shape1, shape2, p1)
moigbeta(order, shape0, shape1, shape2, p1)
tloigbeta(shape0, shape1, shape2, p1)
```

Arguments

<code>x</code> , <code>q</code>	vector of quantiles.
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is take to be the number required.
<code>p1</code> , <code>shape0</code> , <code>shape1</code> , <code>shape2</code>	shape parameters.

order order of the raw moment.
 log, log.p logical; if TRUE, probabilities p are given as log(p).
 lower.tail logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.

Details

d,p,q,ec,m,tl-oigbeta functions computes the density function, the distribution function, the quantile function, the exposure curve function, raw moments and total loss of the one-inflated GB1 distribution. roigbeta generates random variates of this distribution.

Value

A numeric value or a vector.

Author(s)

Dutang Christophe

See Also

[mbbefd-distr](#) and [oidistribution](#).

Examples

```
#TODO
```

oistpareto

One-inflated shifted truncated pareto distribution

Description

These functions perform probabilistic analysis as well as random sampling on one-inflated shifted truncated pareto distribution.

Usage

```
doistpareto(x, a, p1, log=FALSE)
poistpareto(q, a, p1, lower.tail = TRUE, log.p = FALSE)
qoistpareto(p, a, p1, lower.tail = TRUE, log.p = FALSE)
roistpareto(n, a, p1)
ecoistpareto(x, a, p1)
moistpareto(order, a, p1)
tloistpareto(a, p1)
```


Arguments

<code>x, q</code>	vector of quantiles.
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is take to be the number required.
<code>a, p1</code>	parameters.
<code>order</code>	order of the raw moment.
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.

Details

`d,p,q,ec,m,tl-oi`stpareto functions computes the density function, the distribution function, the quantile function, the exposure curve function, raw moments and total loss of the one-inflated shifted truncated pareto distribution. `roistpareto` generates random variates of this distribution.

Value

A numeric value or a vector.

Author(s)

Dutang Christophe

See Also

[mbbefd-distr](#) and [oidistribution](#).

Examples

```
#TODO
```

 oiunif

One-inflated uniform distribution

Description

These functions perform probabilistic analysis as well as random sampling on one-inflated uniform distribution.

Usage

```
doiunif(x, p1, log=FALSE)
poiunif(q, p1, lower.tail = TRUE, log.p = FALSE)
qoiunif(p, p1, lower.tail = TRUE, log.p = FALSE)
roiunif(n, p1)
ecoiunif(x, p1)
moiunif(order, p1)
tloiunif(p1)
```

Arguments

<code>x, q</code>	vector of quantiles.
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is take to be the number required.
<code>p1</code>	parameter.
<code>order</code>	order of the raw moment.
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.

Details

`d,p,q,ec,m,tl-oiunif` functions computes the density function, the distribution function, the quantile function, the exposure curve function, raw moments and total loss of the one-inflated uniform distribution. `roiunif` generates random variates of this distribution.

Value

A numeric value or a vector.

Author(s)

Dutang Christophe

See Also

[mbbefd-distr](#) and [oidistribution](#).

Examples

```
#TODO
```

`stpareto`*The shifted truncated Pareto distribution*

Description

These functions perform probabilistic analysis as well as random sampling on the shifted truncated Pareto distribution.

Usage

```
dstpareto(x, a, log=FALSE)
pstpareto(q, a, lower.tail = TRUE, log.p = FALSE)
qstpareto(p, a, lower.tail = TRUE, log.p = FALSE)
rstpareto(n, a)
mstpareto(order, a)
ecstpareto(x, a)
```

Arguments

<code>x, q</code>	vector of quantiles.
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is take to be the number required.
<code>order</code>	order of the raw moment.
<code>a</code>	shape parameter.
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.

Details

TODO!

Value

A numeric value or a vector.

Author(s)

Dutang Christophe

References

TODO

See Also

[mbbefd-distr](#), [exposureCurve](#)

Examples

```
dstpareto(0:4/4, 2)
```

```
pstpareto(0:4/4, 1/2)
```

swissRe

Swiss Re exposure curve generation function

Description

This function turns out the MBBEFD b and g parameters for the famous Swiss Re (SR) exposure curves.

Usage

```
swissRe(c)
```

Arguments

c A numeric value

Details

The four Swiss Re Y1-Y4 are defined for $c=1.5, 2, 3, 4$. In addition $c=5$ coincides with a curve used by Lloyds for industrial risks exposure rating.

Value

A named two dimensional vector

Author(s)

Giorgio Spedicato

References

BERNEGGER, STEFAN. THE SWISS RE EXPOSURE CURVES AND THE MBBEFD DISTRIBUTION CLASS. *Astin Bulletin* (1997): 99.

See Also

[mbbefd-distr](#).

Examples

```
pars <- swissRe(4)
losses <- rMBBEFD(n=1000,b=pars[1],g=pars[2])
mean(losses)
```

Index

*Topic **datasets**

asiacomrisk, 3
beaonre, 5
itagradescore, 17
lossalae, 18

*Topic **distribution**

bootDR, 6
fitDR, 11
gbeta, 14
graph-eccomp, 16
oibeta, 21
oidistribution, 22
oigbeta, 23
oistpareto, 24
oiunif, 25
stpareto, 27

*Topic **package**

mbbefd-package, 2

asiacomrisk, 3

beaonre, 5
Beta, 10
bootdist, 7, 12
bootDR, 6, 13

cdfcomp, 12, 13
constrOptim.nl, 12

denscomp, 13
dgbeta (gbeta), 14
dgbeta1 (gbeta), 14
Distributions, 15
dMBBEFD (mbbefd-distr), 19
dmbbefd (mbbefd-distr), 19
dMBBEFD1 (mbbefd-distr), 19
dmbbefd1 (mbbefd-distr), 19
dMBBEFD2 (mbbefd-distr), 19
dmbbefd2 (mbbefd-distr), 19
doibeta (oibeta), 21

doifun (oidistribution), 22
doigbeta (oigbeta), 23
doistpareto (oistpareto), 24
doiunif (oiunif), 25
dstpareto (stpareto), 27

ecbeta (exposureCurve), 10
eccomp (graph-eccomp), 16
ecgbeta (gbeta), 14
ecMBBEFD (mbbefd-distr), 19
ecmbbefd (mbbefd-distr), 19
ecoibeta (oibeta), 21
ecoifun (oidistribution), 22
ecoigbeta (oigbeta), 23
ecoistpareto (oistpareto), 24
ecoifun (oiunif), 25
ecstpareto (stpareto), 27
ecunif (exposureCurve), 10
eecf, 8, 17
etl, 9
exposureCurve, 3, 8, 10, 20, 28

fitdist, 11
fitDR, 6, 7, 11

g2a, 14
gbeta, 3, 14
gofstat, 12, 13
graph-eccomp, 16
graphcomp, 13

itagradescore, 17

legend, 16, 17
lossalae, 18
lossalaeFull (lossalae), 18

MBBEFD, 11
MBBEFD (mbbefd-distr), 19
mbbefd, 11
mbbefd (mbbefd-package), 2

- mbbefd-distr, [19](#)
- mbbefd-package, [2](#)
- mgbeta (gbeta), [14](#)
- mgedist, [7](#), [12](#)
- mledist, [7](#), [11–13](#)
- mMBBEFD (mbbefd-distr), [19](#)
- mmbbefd (mbbefd-distr), [19](#)
- mmedist, [7](#), [11–13](#)
- moibeta (oibeta), [21](#)
- moifun (oidistribution), [22](#)
- moigbeta (oigbeta), [23](#)
- moistpareto (oistpareto), [24](#)
- moiunif (oiunif), [25](#)
- mstpareto (stpareto), [27](#)

- oibeta, [3](#), [11](#), [21](#), [23](#)
- oidistribution, [3](#), [22](#), [22](#), [23–26](#)
- oigbeta, [3](#), [11](#), [23](#)
- oistpareto, [3](#), [11](#), [23](#), [24](#)
- oiunif, [3](#), [11](#), [23](#), [25](#)
- optim, [11–13](#)

- par, [16](#)
- pgbeta (gbeta), [14](#)
- plot, [7](#), [17](#)
- plotdist, [12](#), [13](#)
- pMBBEFD (mbbefd-distr), [19](#)
- pmbbefd (mbbefd-distr), [19](#)
- poibeta (oibeta), [21](#)
- poifun (oidistribution), [22](#)
- poigbeta (oigbeta), [23](#)
- points, [16](#)
- poistpareto (oistpareto), [24](#)
- poiunif (oiunif), [25](#)
- ppcomp, [13](#)
- pstpareto (stpareto), [27](#)

- qgbeta (gbeta), [14](#)
- qMBBEFD (mbbefd-distr), [19](#)
- qmbbefd (mbbefd-distr), [19](#)
- qmedist, [7](#), [12](#)
- qoibeta (oibeta), [21](#)
- qoifun (oidistribution), [22](#)
- qoigbeta (oigbeta), [23](#)
- qoistpareto (oistpareto), [24](#)
- qoiunif (oiunif), [25](#)
- qqcomp, [13](#)
- qstpareto (stpareto), [27](#)
- quantile, [13](#)

- quantile.fitdist, [13](#)

- rgbeta (gbeta), [14](#)
- rMBBEFD (mbbefd-distr), [19](#)
- rmbbefd (mbbefd-distr), [19](#)
- roibeta (oibeta), [21](#)
- roifun (oidistribution), [22](#)
- roigbeta (oigbeta), [23](#)
- roistpareto (oistpareto), [24](#)
- roiunif (oiunif), [25](#)
- rstpareto (stpareto), [27](#)

- stpareto, [3](#), [27](#)
- stripchart, [7](#)
- swissRe, [3](#), [10](#), [20](#), [28](#)

- title, [16](#)
- tlMBBEFD (mbbefd-distr), [19](#)
- tlmbbefd (mbbefd-distr), [19](#)
- tloibeta (oibeta), [21](#)
- tloifun (oidistribution), [22](#)
- tloigbeta (oigbeta), [23](#)
- tloistpareto (oistpareto), [24](#)
- tloiunif (oiunif), [25](#)

- Uniform, [10](#)